

TCB

GRANT OF EQUIPMENT  
AUTHORIZATION

TCB

## Certification

Issued Under the Authority of the  
Federal Communications Commission

By:

Bay Area Compliance Laboratory Corp.  
1274 Anvilwood Avenue  
Sunnyvale, CA 94089

Date of Grant: 07/10/2021

Application Dated: 07/10/2021

Shenzhen Huafului Technology Co., Ltd  
Unit 1401 14/F, Jin qi zhi gu mansion Liu xian  
street ,Xili, Nan shan district  
Shenzhen,  
China

Attention: Paul Liu

## NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is  
VALID ONLY for the equipment identified hereon for use under the Commission's  
Rules and Regulations listed below.

FCC IDENTIFIER: 2AHZ5KK7

Name of Grantee: Shenzhen Huafului Technology Co., Ltd

Equipment Class: PCS Licensed Transmitter held to ear  
Notes: Smartphone

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	824.2 - 848.8	0.441	2.5 PM	243KGXW
	22H	824.2 - 848.8	0.204	2.5 PM	242KG7W
	22H	826.4 - 846.6	0.122	2.5 PM	4M20F9W
	24E	1850.2 - 1909.8	0.275	2.5 PM	245KGXW
	24E	1850.2 - 1909.8	0.227	2.5 PM	245KG7W
	24E	1852.4 - 1907.6	0.175	2.5 PM	4M18F9W
	24E	1850.7 - 1909.3	0.192	2.5 PM	1M10G7D
	24E	1850.7 - 1909.3	0.193	2.5 PM	1M10G7W
	24E	1852.5 - 1907.5	0.194	2.5 PM	4M55G7D
	24E	1852.5 - 1907.5	0.191	2.5 PM	4M51G7W
	24E	1860.0 - 1900.0	0.154	2.5 PM	17M9G7D
	24E	1860.0 - 1900.0	0.155	2.5 PM	18M0G7W
	27	1720.0 - 1745.0	0.19	2.5 PM	18M0G7D
	27	1720.0 - 1745.0	0.19	2.5 PM	18M0D7W
	22H	824.7 - 848.3	0.119	2.5 PM	1M10G7D
	22H	824.7 - 848.3	0.119	2.5 PM	1M10D7W
	22H	829.0 - 844.0	0.119	2.5 PM	8M98G7D
	22H	829.0 - 844.0	0.118	2.5 PM	8M94D7W
	27	2507.5 - 2562.5	0.193	2.5 PM	13M5G7D
	27	2507.5 - 2562.5	0.192	2.5 PM	13M3D7W
	27	2510.0 - 2560.0	0.191	2.5 PM	18M0G7D
	27	2510.0 - 2560.0	0.194	2.5 PM	18M0D7W
	27	709.0 - 711.0	0.106	2.5 PM	8M98G7D

<b>27</b>	<b>709.0 - 711.0</b>	<b>0.106</b>	<b>2.5 PM</b>	<b>8M94D7W</b>
<b>22H</b>	<b>831.5 - 841.5</b>	<b>0.161</b>	<b>2.5 PM</b>	<b>13M6G7D</b>
<b>22H</b>	<b>831.5 - 841.5</b>	<b>0.143</b>	<b>2.5 PM</b>	<b>13M5D7W</b>
<b>27</b>	<b>1717.5 - 1772.5</b>	<b>0.186</b>	<b>2.5 PM</b>	<b>13M5G7D</b>
<b>27</b>	<b>1717.5 - 1772.5</b>	<b>0.188</b>	<b>2.5 PM</b>	<b>13M5D7W</b>
<b>27</b>	<b>1720.0 - 1770.0</b>	<b>0.189</b>	<b>2.5 PM</b>	<b>17M9G7D</b>
<b>27</b>	<b>1720.0 - 1770.0</b>	<b>0.187</b>	<b>2.5 PM</b>	<b>18M0D7W</b>
<b>27</b>	<b>2580.0 - 2610.0</b>	<b>0.172</b>	<b>2.5 PM</b>	<b>17M9G7D</b>
<b>27</b>	<b>2580.0 - 2610.0</b>	<b>0.173</b>	<b>2.5 PM</b>	<b>18M0D7W</b>
<b>27</b>	<b>2307.5 - 2312.5</b>	<b>0.164</b>	<b>2.5 PM</b>	<b>4M54G7D</b>
<b>27</b>	<b>2307.5 - 2312.5</b>	<b>0.164</b>	<b>2.5 PM</b>	<b>4M54G7W</b>
<b>27</b>	<b>2310.0 - 2310.0</b>	<b>0.16</b>	<b>2.5 PM</b>	<b>9M00G7D</b>
<b>27</b>	<b>2310.0 - 2310.0</b>	<b>0.158</b>	<b>2.5 PM</b>	<b>8M96D7W</b>
<b>27</b>	<b>2352.5 - 2357.5</b>	<b>0.171</b>	<b>2.5 PM</b>	<b>4M52G7D</b>
<b>27</b>	<b>2352.5 - 2357.5</b>	<b>0.171</b>	<b>2.5 PM</b>	<b>4M52G7W</b>
<b>27</b>	<b>2355.0 - 2355.0</b>	<b>0.17</b>	<b>2.5 PM</b>	<b>9M00G7D</b>
<b>27</b>	<b>2355.0 - 2355.0</b>	<b>0.172</b>	<b>2.5 PM</b>	<b>9M00D7W</b>
<b>27</b>	<b>2562.5 - 2647.5</b>	<b>0.184</b>	<b>2.5 PM</b>	<b>13M5G7D</b>
<b>27</b>	<b>2562.5 - 2647.5</b>	<b>0.183</b>	<b>2.5 PM</b>	<b>13M5D7W</b>
<b>27</b>	<b>2565.0 - 2645.0</b>	<b>0.178</b>	<b>2.5 PM</b>	<b>19M4G7D</b>
<b>27</b>	<b>2565.0 - 2645.0</b>	<b>0.185</b>	<b>2.5 PM</b>	<b>19M3D7W</b>
<b>90</b>	<b>816.5 - 821.5</b>	<b>0.16</b>	<b>2.5 PM</b>	<b>4M52G7D</b>
<b>90</b>	<b>816.5 - 821.5</b>	<b>0.137</b>	<b>2.5 PM</b>	<b>4M50D7W</b>
<b>90</b>	<b>819.0 - 819.0</b>	<b>0.164</b>	<b>2.5 PM</b>	<b>8M96G7D</b>
<b>90</b>	<b>819.0 - 819.0</b>	<b>0.134</b>	<b>2.5 PM</b>	<b>8M96D7W</b>

Output power listed is ERP for operation below 1 GHz and EIRP for operation above 1 GHz. LTE supports 1.4/3/5/10/15/20 MHz BW modes in Band 2/4/66, 1.4/3/5/10 MHz BW modes in Band 5/26, 5/10/15/20 MHz BW modes in Band 7/38/41, 5/10 MHz BW modes in Band 17/40, and 1.4/3/5/10/15 MHz BW mode in Band 26. The antenna(s) used for this transmitter must not be co-located with any other transmitters except in accordance with FCC multi-transmitter product procedures. SAR compliance for body-worn operating conditions is restricted to belt clips, holsters or similar accessories that have no metallic component in the assembly and must provide a minimum separation distance of 10mm between the device and the body. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. The highest reported SAR for head, body-worn accessory, product specific, and simultaneous transmission exposure conditions are 0.57 W/kg, 0.61 W/kg, 0.76 W/kg, and 0.88 W/kg, respectively.

This device contains functions that are not operational in U.S Territories. This filing is only applicable for US operations.