

---

# SAR Test Report

---

Report No.: AGC00552200701FH01

**FCC ID** : 2AHZ5NOTE7

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION** : Smart Phone

**BRAND NAME** : CUBOT

**MODEL NAME** : NOTE 7

**APPLICANT** : Shenzhen Huafurui Technology Co., Ltd.

**DATE OF ISSUE** : Sep. 11.2020

**STANDARD(S)** : IEEE Std. 1528:2013  
FCC 47 CFR Part 2§2.1093:2013  
IEEE Std C95.1™-2005  
IEC 62209-1: 2016

**REPORT VERSION** : V1.0

Attestation of Global Compliance(Shenzhen) Co., Ltd.



### Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 11.2020	Valid	Initial Release

## Test Report

Applicant Name	Shenzhen Huafurui Technology Co., Ltd.
Applicant Address	Unit 1401 14/F, Jin qi zhi gu mansion Liu xian street, Xili, Nan shan district, Shenzhen, China
Manufacturer Name	Shenzhen Huafurui Technology Co., Ltd.
Manufacturer Address	Unit 1401 14/F, Jin qi zhi gu mansion Liu xian street, Xili, Nan shan district, Shenzhen, China
Factory Name	Shenzhen Huafurui Technology Co., Ltd.
Factory Address	Unit 1401 14/F, Jin qi zhi gu mansion Liu xian street, Xili, Nan shan district, Shenzhen, China
Product Designation	Smart Phone
Brand Name	CUBOT
Model Name	NOTE 7
EUT Voltage	DC3.8V by battery
Applicable Standard	IEEE Std. 1528:2013 FCC 47 CFR Part 2§2.1093:2013 IEEE Std C95.1™-2005 IEC 62209-1: 2016
Test Date	Aug. 01.2020 to Aug. 10.2020
Report Template	AGCRT-US-4G/SAR (2018-01-01)

Note: The results of testing in this report apply to the product/system which was tested only.

*Jack Gui*

Prepared By

Jack Gui (Project Engineer)

Aug. 10.2020

*Angela Li*

Reviewed By

Angela Li (Reviewer)

Sep. 11.2020

*Forrest Lei*

Approved By

Forrest Lei (Authorized Officer)

Sep. 11.2020

## TABLE OF CONTENTS

<b>1. SUMMARY OF MAXIMUM SAR VALUE .....</b>	<b>5</b>
<b>2. GENERAL INFORMATION.....</b>	<b>6</b>
2.1. EUT DESCRIPTION.....	6
<b>3. SAR MEASUREMENT SYSTEM.....</b>	<b>8</b>
3.1. THE DASY5 SYSTEM USED FOR PERFORMING COMPLIANCE TESTS CONSISTS OF FOLLOWING ITEMS.....	8
3.2. DASY5 E-FIELD PROBE.....	9
3.3. DATA ACQUISITION ELECTRONICS DESCRIPTION .....	9
3.4. ROBOT.....	10
3.5. LIGHT BEAM UNIT .....	10
3.6. DEVICE HOLDER .....	11
3.7. MEASUREMENT SERVER.....	11
3.8. PHANTOM.....	12
<b>4. SAR MEASUREMENT PROCEDURE .....</b>	<b>13</b>
4.1. SPECIFIC ABSORPTION RATE (SAR) .....	13
4.2. SAR MEASUREMENT PROCEDURE .....	14
4.3. RF EXPOSURE CONDITIONS.....	16
<b>5. TISSUE SIMULATING LIQUID .....</b>	<b>18</b>
5.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID.....	18
5.2. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS.....	19
5.3. TISSUE CALIBRATION RESULT.....	20
<b>6. SAR SYSTEM CHECK PROCEDURE.....</b>	<b>22</b>
6.1. SAR SYSTEM CHECK PROCEDURES.....	22
6.2. SAR SYSTEM CHECK.....	23
<b>7. EUT TEST POSITION.....</b>	<b>25</b>
7.2. CHEEK POSITION .....	26
7.3. TILT POSITION.....	26
7.4. BODY WORN POSITION.....	27
<b>8. SAR EXPOSURE LIMITS .....</b>	<b>28</b>
<b>9. TEST FACILITY .....</b>	<b>29</b>
<b>10. TEST EQUIPMENT LIST .....</b>	<b>30</b>
<b>11. MEASUREMENT UNCERTAINTY .....</b>	<b>31</b>
<b>12. CONDUCTED POWER MEASUREMENT .....</b>	<b>34</b>
<b>13. TEST RESULTS .....</b>	<b>60</b>
13.1. SAR TEST RESULTS SUMMARY .....	60
<b>APPENDIX A. SAR SYSTEM CHECK DATA .....</b>	<b>87</b>
<b>APPENDIX B. SAR MEASUREMENT DATA.....</b>	<b>95</b>
<b>APPENDIX C. TEST SETUP PHOTOGRAPHS .....</b>	<b>138</b>
<b>APPENDIX D. CALIBRATION DATA.....</b>	<b>145</b>

## 1. SUMMARY OF MAXIMUM SAR VALUE

The maximum results of Specific Absorption Rate (SAR) found during testing for EUT are as follows:

Frequency Band	Highest Reported 1g-SAR(W/Kg)		SAR Test Limit (W/Kg)
	Head	Body-worn	
GSM 850	0.342	0.723	1.6
PCS 1900	0.205	1.075	
UMTS Band II	0.179	1.100	
UMTS Band IV	0.292	1.070	
UMTS Band V	0.280	0.435	
LTE Band 2	0.247	1.166	
LTE Band 4	0.342	1.126	
LTE Band 5	0.448	0.679	
LTE Band 7	0.445	0.536	
LTE Band 12	0.219	0.405	
LTE Band 17	0.261	0.568	
WIFI 2.4G	0.363	0.138	
Simultaneous Reported SAR	1.199		
SAR Test Result	PASS		

This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/Kg) specified in IEEE Std. 1528:2013; FCC 47CFR § 2.1093; IEEE/ANSI C95.1:2005 and the following specific FCC Test Procedures:

- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 648474 D04 Handset SAR v01r03
- KDB 865664 D01 SAR Measurement 100MHz to 6GHz v01r04
- KDB 941225 D01 3G SAR Procedures v03r01
- KDB 941225 D06 Hotspot Mode v02r01
- KDB 248227 D01 802 11 Wi-Fi SAR v02r02
- KDB 941225 D05 SAR for LTE Devices v02r05

## 2. GENERAL INFORMATION

### 2.1. EUT Description

General Information	
Product Designation	Smart Phone
Test Model	NOTE 7
Hardware Version	TE647_MAIN_PCB_V1.1
Software Version	CUBOT_NOTE 7_A041C_V01_20200422
Device Category	Portable
RFXposure Environment	Uncontrolled
Antenna Type	Internal
GSM and GPRS& EGPRS	
Support Band	<input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 (U.S. Bands) <input checked="" type="checkbox"/> GSM 900 <input checked="" type="checkbox"/> DCS 1800 (Non-U.S. Bands)
GPRS & EGPRS Type	Class B
GPRS & EGPRS Class	Class 12(1Tx+4Rx, 2Tx+3Rx, 3Tx+2Rx, 4Tx+1Rx)
TX Frequency Range	GSM 850 : 820-850MHz;; PCS 1900: 1850-1910MHz;
RX Frequency Range	GSM 850 : 869~894MHz; PCS 1900: 1930~1990MHz
Release Version	R99
Type of modulation	GMSK for GSM/GPRS; GMSK & 8-PSK for EGPRS
Antenna Gain	GSM850:0.86dBi; PCS1900: 1.35dBi
Max. Average Power	GSM850: 33.40dBm ;PCS1900: 31.22dBm
WCDMA	
Support Band	<input checked="" type="checkbox"/> UMTS FDD Band II <input checked="" type="checkbox"/> UMTS FDD Band V <input checked="" type="checkbox"/> UMTS FDD Band IV (U.S. Bands) <input type="checkbox"/> UMTS FDD Band I <input type="checkbox"/> UMTS FDD Band VIII (Non-U.S. Bands)
HS Type	HSPA(HSUPA/HSDPA)
TX Frequency Range	WCDMA FDD Band II: 1850-1910MHz; WCDMA FDD Band V: 820-850MHz; FDD Band IV: 1712.4-1752.6MHz;
RX Frequency Range	WCDMA FDD Band II: 1930-1990MHz; WCDMA FDD Band V: 869-894MHz; FDD Band IV: 2112.4-5152.6MHz;
Release Version	Rel-6
Type of modulation	HSDPA:QPSK/16QAM; HSUPA:BPSK; WCDMA:QPSK
Antenna Gain	WCDMA850:0.87dBi; WCDMA1900:1.34dBi; WCDMA 1700:1.27dBi
Max. Average Power	Band II: 22.57dBm; Band IV: 23.68dBm; Band V: 22.46dBm

**EUT Description( Continue)**


<b>LTE</b>	
Support Band	<input checked="" type="checkbox"/> FDD Band 2 <input checked="" type="checkbox"/> FDD Band 4 <input checked="" type="checkbox"/> FDD Band 5 <input checked="" type="checkbox"/> FDD Band 7 <input checked="" type="checkbox"/> FDD Band 12 <input checked="" type="checkbox"/> FDD Band 17 <input type="checkbox"/> FDD Band 25 <input type="checkbox"/> FDD Band 26 <input type="checkbox"/> TDD Band 41 (U.S. Bands) <input type="checkbox"/> FDD Band 1 <input type="checkbox"/> FDD Band 3 <input type="checkbox"/> FDD Band 7 <input type="checkbox"/> FDD Band 8 <input type="checkbox"/> FDD Band 20 <input type="checkbox"/> TDD Band 28 <input type="checkbox"/> TDD Band 38 <input type="checkbox"/> FDD Band 40 <input type="checkbox"/> FDD Band 42 <input type="checkbox"/> FDD Band 43 (Non-U.S. Bands)
TX Frequency Range	Band 2:1850-1910MHz; Band 4:1710-1755MHz;Band 5:824-849MHz; Band 7:2500-2570MHz; Band 12:699-716MHz; Band 17: 704-716MHz;
RX Frequency Range	Band 2:1930-1990MHz; Band 4:2110-2155MHz; Band 5:869-894MHz; Band 7:2620-2690MHz; Band 12: 729-746 MHz; Band 17: 734-746 MHz;
Release Version	Rel-8
Type of modulation	QPSK, 16QAM
Antenna Gain	Band 2: 1.38dBi; Band 4: 1.28dBi; Band 5:0.84dBi; Band 7: 1.21dBi; Band 12:0.32dBi; Band 17:0.38dBi
Max. Average Power	Band 2: 24.30dBm; Band 4: 23.04dBm; Band 5: 23.81dBm; Band 7: 22.89dBm; Band 12: 22.62dBm; Band 17: 23.56dBm;
<b>Bluetooth</b>	
Operation Frequency	2402~2480MHz
Antenna Gain	1.73dBi
Bluetooth Version	V4.2
Type of modulation	<b>BR/EDR:</b> GFSK, $\Pi/4$ -DQPSK, 8-DPSK; <b>BLE:</b> GFSK
EIRP	<b>BR/EDR:</b> 1.496dBm; <b>BLE:</b> 1.529dBm
<b>WIFI</b>	
WIFI Specification	<input type="checkbox"/> 802.11a <input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(20) <input checked="" type="checkbox"/> 802.11n(40)
Operation Frequency	2412~2462MHz
Avg. Burst Power	11b:10.09dBm,11g: 9.88dBm,11n(20): 10.04dBm,11n(40): 9.74dBm
Antenna Gain	1.74dBi
<b>Accessories</b>	
Battery	Brand name: CUBOT Model No. : NOTE 7 Voltage and Capacitance: 3.8 V & 3100mAh
Earphone	Brand name: N/A Model No. : N/A

- Note:1.CMU200 can measure the average power and Peak power at the same time  
 2.The sample used for testing is end product.  
 3. The test sample has no any deviation to the test method of standard mentioned in page 1.

Product	Type
	<input checked="" type="checkbox"/> Production unit <input type="checkbox"/> Identical Prototype

### 3. SAR MEASUREMENT SYSTEM

#### 3.1. The DASY5 system used for performing compliance tests consists of following items



- A standard high precision 6-axis robot with controller, teach pendant and software.
- Data acquisition electronics (DAE) which attached to the robot arm extension. The DAE consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock
- A dosimetric probe equipped with an optical surface detector system.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital Communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- A Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- Phantoms, device holders and other accessories according to the targeted measurement.

### 3.2. DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE-1528 etc.) Under ISO17025. The calibration data are in Appendix D.

#### Isotropic E-Field Probe Specification

<b>Model</b>	EX3DV4-SN:3953	
<b>Manufacture</b>	SPEAG	
<b>frequency</b>	0.7GHz-6GHz Linearity: $\pm 0.9\%$ (k=2)	
<b>Dynamic Range</b>	0.01W/Kg-100W/Kg Linearity: $\pm 0.9\%$ (k=2)	
<b>Dimensions</b>	Overall length: 337mm Tip diameter: 2.5mm Typical distance from probe tip to dipole centers: 1mm	
<b>Application</b>	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.	

### 3.3. Data Acquisition Electronics description

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

#### DAE4

<b>Input Impedance</b>	200M $\Omega$	
<b>The Inputs</b>	Symmetrical and floating	
<b>Common mode rejection</b>	above 80 dB	

### 3.4. Robot

The DASY system uses the high precision robots (DASY5:TX60) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller



### 3.5. Light Beam Unit

The light beam switch allows automatic “tooling” of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position. e, the same position will be reached with another aligned probe within 0



### 3.6. Device Holder

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon=3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



### 3.7. Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chip-disk (DASY5: 128MB), RAM (DASY5: 128MB).

The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DAYS I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



### 3.8. PHANTOM SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:


- Left head
- Right head
- Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

### ELI4 Phantom

- Flat phantom a fiberglass shell flat phantom with 2mm+/- 0.2 mm shell thickness. It has only one measurement area for Flat phantom



## 4. SAR MEASUREMENT PROCEDURE

### 4.1. Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element(dv) of given mass density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/Kg)

SAR can be obtained using either of the following equations:

$$SAR = \frac{\sigma E^2}{\rho}$$

$$SAR = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

Where

SAR	is the specific absorption rate in watts per kilogram;
E	is the r.m.s. value of the electric field strength in the tissue in volts per meter;
σ	is the conductivity of the tissue in siemens per metre;
ρ	is the density of the tissue in kilograms per cubic metre;
c <sub>h</sub>	is the heat capacity of the tissue in joules per kilogram and Kelvin;

$\left. \frac{dT}{dt} \right|_{t=0}$  is the initial time derivative of temperature in the tissue in kelvins per second

## 4.2. SAR Measurement Procedure

### Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface is 2.7mm This distance cannot be smaller than the distance os sensor calibration points to probe tip as `defined in the probe properties,

### Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in db) is specified in the standards for compliance testing. For example, a 2db range is required in IEEE Standard 1528, whereby 3db is a requirement when compliance is assessed in accordance with the ARIB standard (Japan) If one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximum are detected, the number of Zoom Scan has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100MHz to 6GHz

	$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1$ mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$	$\leq 2$ GHz: $\leq 15$ mm 2 – 3 GHz: $\leq 12$ mm	3 – 4 GHz: $\leq 12$ mm 4 – 6 GHz: $\leq 10$ mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

### Step 3: Zoom Scan

Zoom Scan are used to assess the peak spatial SAR value within a cubic average volume containing 1g abd 10g of simulated tissue. The Zoom Scan measures points(refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1g and 10g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB865664 d01 SAR Measurement 100MHz to 6GHz

Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm
<p>Note: <math>\delta</math> is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is <math>\leq 1.4</math> W/kg, <math>\leq 8</math> mm, <math>\leq 7</math> mm and <math>\leq 5</math> mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>			

Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the same settings. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

### 4.3. RF Exposure Conditions


Test Configuration and setting:

The EUT is a model of GSM/WCDMA Portable Mobile Station (MS). It supports GSM/GPRS/EGPRS, WCDMA/HSPA, BT, WIFI, and support hot spot mode.

For WWAN SAR testing, the device was controlled by using a base station emulator. Communication between the device and the emulator were established by air link. The distance between the EUT and the antenna is larger than 50cm, and the output power radiated from the emulator antenna is at least 30db smaller than the output power of EUT.

For WLAN testing, the EUT is configured with the WLAN continuous TX tool through engineering command.

#### Antenna Location: (the back view)



For WWAN mode:

Test Configurations	Antenna to edges/surface	SAR required	Note
Head			
Left Touch		Yes	--
Left Tilt		Yes	--
Right Touch		Yes	--
Right Tilt		Yes	--
Body			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Hotspot			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Edge 1 (Top)	128mm	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225 D06 Hotspot SAR
Edge 2 (Right)	1mm	Yes	--
Edge 3 (Bottom)	1mm	Yes	--
Edge 4 (Left)	1mm	Yes	--

For WLAN mode:

Test Configurations	Antenna to edges/surface	SAR required	Note
Head			
Left Touch		Yes	--
Left Tilt		Yes	--
Right Touch		Yes	--
Right Tilt		Yes	--
Body			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Hotspot			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Edge 1 (Top)	1mm	Yes	--
Edge 2 (Right)	47mm	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225 D06 Hotspot SAR
Edge 3 (Bottom)	119mm	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225 D06 Hotspot SAR
Edge 4 (Left)	1mm	Yes	--

## 5. TISSUE SIMULATING LIQUID

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15cm. For head SAR testing the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 10% are listed in 6.2

### 5.1. The composition of the tissue simulating liquid

Ingredient (% Weight) Frequency (MHz)	Water	Nacl	Polysorbate 20	DGBE	1,2 Propanediol	Triton X-100
750 Head	35	2	0.0	0.0	63	0.0
835 Head	50.36	1.25	48.39	0.0	0.0	0.0
1750 Head	52.64	0.36	0.0	47	0.0	0.0
1900 Head	54.9	0.18	0.0	44.92	0.0	0.0
2450 Head	71.88	0.16	0.0	7.99	0.0	19.97
2600 Head	55.242	0.306	0	44.452	0	0

## 5.2. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1 have been incorporated in the following table. The body tissue dielectric parameters recommended by the IEC 62209-2 have been incorporated in the following table.

Target Frequency (MHz)	head		body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
300	45.3	0.87	45.3	0.87
450	43.5	0.87	43.5	0.87
<b>750</b>	<b>41.9</b>	<b>0.89</b>	<b>41.9</b>	<b>0.89</b>
<b>835</b>	<b>41.5</b>	<b>0.90</b>	<b>41.5</b>	<b>0.90</b>
900	41.5	0.97	41.5	0.97
915	41.5	1.01	41.5	1.01
1450	40.5	1.20	40.5	1.20
1610	40.3	1.29	40.3	1.29
<b>1750</b>	<b>40.1</b>	<b>1.37</b>	<b>40.1</b>	<b>1.37</b>
<b>1800 – 2000</b>	<b>40.0</b>	<b>1.40</b>	<b>40.0</b>	<b>1.40</b>
<b>2450</b>	<b>39.2</b>	<b>1.80</b>	<b>39.2</b>	<b>1.80</b>
<b>2600</b>	<b>39.0</b>	<b>1.96</b>	<b>39.0</b>	<b>1.96</b>
3000	38.5	2.40	38.5	2.40

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000$  kg/m<sup>3</sup>)

### 5.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY 5 Dielectric Probe Kit and R&S Network Analyzer ZVL6.

Tissue Stimulant Measurement for 750MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r$ 41.9 (37.71-46.09)	$\delta$ [s/m] 0.89(0.801-0.979)		
	707.5	44.62	0.85	21.1	Aug. 08.2020
	710	44.62	0.87		
	750	40.52	0.88		

Tissue Stimulant Measurement for 835MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r$ 41.5 (37.35-45.65)	$\delta$ [s/m] 0.90(0.81-0.99)		
	835	42.52	0.91	20.1	Aug. 01.2020
	836.6	41.15	0.92		

Tissue Stimulant Measurement for 835MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r$ 41.5 (37.35-45.65)	$\delta$ [s/m] 0.90(0.81-0.99)		
	835	40.21	0.92	21.0	Aug. 04.2020
	836.5	39.05	0.94		

Tissue Stimulant Measurement for 1750MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r$ 40.1 (36.09-44.11)	$\delta$ [s/m] 1.37(1.233-1.507)		
	1712.5	41.65	1.31	21.2	Aug. 06.2020
	1720	41.32	1.35		
	1732.5	40.22	1.37		
	1745	39.51	1.38		
	1750	38.75	1.39		
	1752.5	37.32	1.41		

Tissue Stimulant Measurement for 1900MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r 40.00(36.00-44.00)$	$\delta [s/m] 1.40(1.26-1.54)$		
Head	1850.2	42.98	1.29	20.4	Aug. 03.2020
	1852.4	41.32	1.32		
	1880	40.06	1.36		
	1900	38.12	1.38		
	1907.6	37.62	1.41		
	1909.8	36.89	1.43		

Tissue Stimulant Measurement for 1900MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r 40.00(36.00-44.00)$	$\delta [s/m] 1.40(1.26-1.54)$		
Head	1860	41.25	1.31	21.3	Aug. 10.2020
	1880	40.92	1.35		
	1900	38.63	1.37		

Tissue Stimulant Measurement for 2450MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r 39.2(35.28-43.12)$	$\delta [s/m] 1.80(1.62-1.98)$		
Head	2437	39.87	1.78	20.8	Aug. 07.2020
	2450	38.63	1.81		

Tissue Stimulant Measurement for 2600MHz					
Head	Fr. (MHz)	Dielectric Parameters ( $\pm 10\%$ )		Tissue Temp [°C]	Test time
		$\epsilon_r 39(35.1-42.9)$	$\delta [s/m] 1.96(1.764-2.156)$		
Head	2535	40.65	1.83	20.8	Aug. 05.2020
	2600	39.74	1.86		


## 6. SAR SYSTEM CHECK PROCEDURE

### 6.1. SAR System Check Procedures

SAR system check is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.



Each DASY system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.



## 6.2. SAR System Check

### 6.2.1. Dipoles



Frequency	L (mm)	h (mm)	d (mm)
750MHz	176	100	6.35
835MHz	161.0	89.8	3.6
1800MHz	71.6	41.7	3.6
1900MHz	68	39.5	3.6
2450MHz	51.5	30.4	3.6
2600MHz	48.5	28.8	3.6

## 6.2.2. System Check Result

System Performance Check at 750MHz&835MHz &1800MHz &1900MHz &2450MHz&2600MHz								
Validation Kit: SN47/14 DIP 0G750-340& SN29/15 DIP 0G835-383& SN46/11 DIP 1G800-186& SN 46/11 DIP 1G900-187& D2450V2-SN:968& SN 47/14 DIP 2G600-342								
Frequency [MHz]	Target Value(W/Kg)		Reference Result ( $\pm 10\%$ )		Tested Value(W/Kg)		Tissue Temp. [°C]	Test time
	1g	10g	1g	10g	1g	10g		
750	8.31	5.45	7.479-9.141	4.905-5.995	8.59	5.66	21.1	Aug. 08.2020
835	9.85	6.27	8.865-10.835	5.643 -6.897	9.75	6.36	20.1	Aug. 01.2020
835	9.85	6.27	8.865-10.835	5.643-6.897	9.76	6.09	21.0	Aug. 04.2020
1800	39.07	20.29	35.163-42.977	18.261-22.319	37.09	19.97	21.2	Aug. 06.2020
1900	40.25	20.50	36.225-44.275	18.45-22.55	39.94	20.76	20.4	Aug. 03.2020
1900	40.25	20.50	36.225-44.275	18.45-22.55	39.46	20.29	21.3	Aug. 10.2020
2450	53.6	25.0	48.24-58.96	22.50-27.50	53.41	23.93	20.8	Aug. 07.2020
2600	56.86	24.84	51.174-62.546	22.356-27.324	53.89	24.57	20.8	Aug. 05.2020

Note:



(1) We use a CW signal of 18dBm for system check, and then all SAR values are normalized to 1W forward power. The result must be within  $\pm 10\%$  of target value.

## 7. EUT TEST POSITION

This EUT was tested in **Right Cheek, Right Tilted, Left Cheek, Left Tilted, Body back, Body front and 4 edges.**

### 7.1. Define Two Imaginary Lines on the Handset

- (1) The vertical centerline passes through two points on the front side of the handset: the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the handset.
- (2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



## 7.2. Cheek Position

- (1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (2) To move the device towards the phantom with the ear piece aligned with the the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost





## 7.3. Tilt Position

- (1) To position the device in the “cheek” position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.



#### 7.4. Body Worn Position

- (1) To position the EUT parallel to the phantom surface.
- (2) To adjust the EUT parallel to the flat phantom.
- (3) To adjust the distance between the EUT surface and the flat phantom to **10mm**.



## 8. SAR EXPOSURE LIMITS

### Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit (W/kg)
Spatial Peak SAR (1g cube tissue for brain or body)	1.60
Spatial Average SAR (Whole body)	0.08
Spatial Peak SAR (Limbs)	4.0

## 9. TEST FACILITY

<b>Test Site</b>	Attestation of Global Compliance (Shenzhen) Co., Ltd
<b>Location</b>	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
<b>Designation Number</b>	CN1259
<b>FCC Test Firm Registration Number</b>	975832
<b>A2LA Cert. No.</b>	5054.02
<b>Description</b>	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

## 10. TEST EQUIPMENT LIST

Equipment description	Manufacturer/ Model	Identification No.	Current calibration date	Next calibration date
Stäubli Robot	Stäubli-TX60	F13/5Q2UD1/A/01	N/A	N/A
Robot Controller	Stäubli-CS8	139522	N/A	N/A
E-Field Probe	Speag- EX3DV4	SN:3953	Jul. 29,2020	Jul. 28,2021
SAM Twin Phantom	Speag-SAM	1790	N/A	N/A
Device Holder	Speag-SD 000 H01 KA	SD 000 H01 KA	N/A	N/A
DAE4	Speag-SD 000 D04 BM	1398	Apr. 23,2020	Apr. 22,2021
SAR Software	Speag-DASY5	DASY52.8	N/A	N/A
Liquid	SATIMO	-	N/A	N/A
Radio Communication Tester	R&S-CMU200	069Y7-158-13-712	Mar. 17,2020	Mar. 16,2021
Comm Tester	R&S- CMW500	S/N120909	Aug. 19,2019	Aug. 18,2020
Dipole	SATIMO SID750	SN47/14 DIP 0G750-340	Apr. 26,2019	Apr. 25,2022
Dipole	SATIMO SID835	SN 29/15 DIP 0G850-383	Apr. 26,2019	Apr. 25,2022
Dipole	SATIMO SID1800	SN46/11 DIP 1G800-186	Apr. 26,2019	Apr. 25,2022
Dipole	SATIMO SID1900	SN 46/11 DIP 1G900-187	Apr. 26,2019	Apr. 25,2022
Dipole	D2450V2	SN968	July 31,2018	July 30,2021
Dipole	SATIMO SID2600	SN 47/14 DIP 2G600-342	Apr. 26,2019	Apr. 25,2022
Signal Generator	Agilent-E4438C	US41461365	Oct. 08,2019	Oct. 07,2020
Vector Analyzer	Agilent / E4440A	US41421290	Sep. 09,2019	Sep. 08,2020
Network Analyzer	Rhode & Schwarz ZVL6	SN101443	Oct. 08,2019	Oct. 07,2020
Attenuator	Warison /WATT-6SR1211	S/N:WRJ34AYM2F1	June 10,2020	June 09,2021
Attenuator	Mini-circuits / VAT-10+	31405	June 10,2020	June 09,2021
Amplifier	AS0104-55_55	1004793	June 11,2020	June 10,2021
Directional Couple	Werlatone/ C5571-10	SN99463	May 15,2020	May 14,2022
Directional Couple	Werlatone/ C6026-10	SN99482	May 15,2020	May 14,2022
Power Sensor	NRP-Z21	1137.6000.02	Sep. 09,2019	Sep. 08,2020
Power Sensor	NRP-Z23	US38261498	Feb. 18,2020	Feb. 17,2021
Power Viewer	R&S	V2.3.1.0	N/A	N/A

Note: Per KDB 865664 Dipole SAR Validation, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss is within 20% of calibrated measurement;
4. Impedance is within 5Ω of calibrated measurement.

## 11. MEASUREMENT UNCERTAINTY

DASY Uncertainty- EX3DV4 Measurement uncertainty for Dipole averaged over 1 gram / 10 gram.									
a	b	c	d	e f(d,k)	f	g	h cx <sub>f</sub> /e	i cx <sub>g</sub> /e	k
Uncertainty Component	Sec.	Tol (± %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g U <sub>i</sub> (±%)	10g U <sub>i</sub> (±%)	v <sub>i</sub>
<b>Measurement System</b>									
Probe calibration	E.2.1	6.65	N	1	1	1	6.65	6.65	∞
Axial Isotropy	E.2.2	0.6	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.24	0.24	∞
Hemispherical Isotropy	E.2.2	1.6	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.65	0.65	∞
Boundary effect	E.2.3	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	0.45	R	$\sqrt{3}$	1	1	0.26	0.26	∞
System detection limits	E.2.4	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	E.2.5	3.3	R	$\sqrt{3}$	1	1	1.91	1.91	∞
Readout Electronics	E.2.6	0.15	N	1	1	1	0.15	0.15	∞
Response Time	E.2.7	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	E.2.8	1.7	R	$\sqrt{3}$	1	1	0.98	0.98	∞
RF ambient conditions-Noise	E.6.1	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	E.6.1	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	E.6.2	0.4	R	$\sqrt{3}$	1	1	0.23	0.23	∞
Probe positioning with respect to phantom shell	E.6.3	6.7	R	$\sqrt{3}$	1	1	3.87	3.87	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
<b>Test sample Related</b>									
Test sample positioning	E.4.2	2.9	N	1	1	1	2.90	2.90	∞
Device holder uncertainty	E.4.1	3.6	N	1	1	1	3.60	3.60	∞
Output power variation—SAR drift measurement	E.2.9	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	E.6.5	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
<b>Phantom and tissue parameters</b>									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	6.6	R	$\sqrt{3}$	1	1	3.81	3.81	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity measurement	E.3.3	5	N	1	0.23	0.26	1.15	1.30	M
Liquid conductivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty			RSS				11.79	11.63	
Expanded Uncertainty (95% Confidence interval)			K=2				23.59	23.26	

DASY Uncertainty- EX3DV4									
System Check uncertainty for Dipole averaged over 1 gram / 10 gram.									
a	b	c	d	e f(d,k)	f	g	h cxf/e	i cxg/e	k
Uncertainty Component	Sec.	Tol (± %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (±%)	10g Ui (±%)	vi
<b>Measurement System</b>									
Probe calibration drift	E.2.1	0.5	N	1	1	1	0.5	0.5	∞
Axial Isotropy	E.2.2	0.6	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Hemispherical Isotropy	E.2.2	1.6	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	E.2.3	1	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Linearity	E.2.4	0.45	R	$\sqrt{3}$	0	0	0.00	0.00	∞
System detection limits	E.2.4	1	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Modulation response	E.2.5	3.3	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	E.2.6	0.15	N	1	0	0	0.00	0.00	∞
Response Time	E.2.7	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	E.2.8	1.7	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-reflections	E.6.1	3	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Probe positioner mechanical tolerance	E.6.2	0.4	R	$\sqrt{3}$	1	1	0.37	0.37	∞
Probe positioning with respect to phantom shell	E.6.3	6.7	R	$\sqrt{3}$	1	1	3.87	3.87	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
<b>System check source (dipole)</b>									
Deviation of experimental dipoles	E.6.4	2.0	N	1	1	1	2.00	2.00	∞
Input power and SAR drift measurement	8,6.6.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid distance	8,E.6.6	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
<b>Phantom and tissue parameters</b>									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	6.6	R	$\sqrt{3}$	1	1	3.81	3.81	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity measurement	E.3.3	5	N	1	0.23	0.26	1.15	1.30	M
Liquid conductivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty			RSS				7.34	7.07	
Expanded Uncertainty (95% Confidence interval)			K=2				14.67	14.14	

DASY Uncertainty- EX3DV4									
System Validation uncertainty for Dipole averaged over 1 gram / 10 gram.									
a	b	c	d	e f(d,k)	f	g	h cx <sub>f</sub> /e	i cx <sub>g</sub> /e	k
Uncertainty Component	Sec.	Tol (±%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g U <sub>i</sub> (±%)	10g U <sub>i</sub> (±%)	v <sub>i</sub>
<b>Measurement System</b>									
Probe calibration	E.2.1	6.65	N	1	1	1	6.65	6.65	∞
Axial Isotropy	E.2.2	0.6	R	$\sqrt{3}$	1	1	0.35	0.35	∞
Hemispherical Isotropy	E.2.2	1.6	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	E.2.3	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	0.45	R	$\sqrt{3}$	1	1	0.26	0.26	∞
System detection limits	E.2.4	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	E.2.5	3.3	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	E.2.6	0.15	N	1	1	1	0.15	0.15	∞
Response Time	E.2.7	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	E.2.8	1.7	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	E.6.1	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	E.6.2	0.4	R	$\sqrt{3}$	1	1	0.23	0.23	∞
Probe positioning with respect to phantom shell	E.6.3	6.7	R	$\sqrt{3}$	1	1	3.87	3.87	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
<b>System check source (dipole)</b>									
Deviation of experimental dipole from numerical dipole	E.6.4	5.0	N	1	1	1	5.00	5.00	∞
Input power and SAR drift measurement	8,6.6.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid distance	8,E.6.6	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
<b>Phantom and tissue parameters</b>									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	6.6	R	$\sqrt{3}$	1	1	3.81	3.81	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity measurement	E.3.3	5	N	1	0.23	0.26	1.15	1.30	M
Liquid conductivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty			RSS				11.45	11.28	
Expanded Uncertainty (95% Confidence interval)			K=2				22.89	22.55	

## 12. CONDUCTED POWER MEASUREMENT GSM BAND

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <1>				
GSM 850	824.2	33.35	-9	24.35
	836.6	<b>33.40</b>	-9	24.40
	848.8	33.40	-9	24.4
GPRS 850 (1 Slot)	824.2	33.36	-9	24.36
	836.6	33.31	-9	24.31
	848.8	33.32	-9	24.32
GPRS 850 (2 Slot)	824.2	30.45	-6	24.45
	836.6	30.12	-6	24.12
	848.8	30.65	-6	24.65
GPRS 850 (3 Slot)	824.2	28.95	-4.26	24.69
	836.6	28.87	-4.26	24.61
	848.8	28.96	-4.26	<b>24.70</b>
GPRS 850 (4 Slot)	824.2	27.42	-3	24.42
	836.6	27.53	-3	24.53
	848.8	27.38	-3	24.38
EGPRS 850 (1 Slot)	824.2	26.17	-9	17.17
	836.6	25.81	-9	16.81
	848.8	25.77	-9	16.77
EGPRS 850 (2 Slot)	824.2	24.61	-6	18.61
	836.6	24.75	-6	18.75
	848.8	24.69	-6	18.69
EGPRS 850 (3 Slot)	824.2	22.11	-4.26	17.85
	836.6	22.32	-4.26	18.06
	848.8	22.42	-4.26	18.16
EGPRS 850 (4 Slot)	824.2	20.15	-3	17.15
	836.6	20.35	-3	17.35
	848.8	20.47	-3	17.47

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <2>				
GSM 850	824.2	31.62	-9	22.62
	836.6	31.94	-9	22.94
	848.8	31.83	-9	22.83
GPRS 850 (1 Slot)	824.2	31.55	-9	22.55
	836.6	31.82	-9	22.82
	848.8	31.61	-9	22.61
GPRS 850 (2 Slot)	824.2	30.22	-6	24.22
	836.6	30.06	-6	24.06
	848.8	30.55	-6	24.55
GPRS 850 (3 Slot)	824.2	28.82	-4.26	24.56
	836.6	28.73	-4.26	24.47
	848.8	28.75	-4.26	24.49
GPRS 850 (4 Slot)	824.2	27.22	-3	24.22
	836.6	27.33	-3	24.33
	848.8	27.15	-3	24.15

**GSM BAND CONTINUE**

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <1>				
PCS1900	1850.2	31.21	-9	21.57
	1880	31.04	-9	21.52
	1909.8	30.90	-9	21.36
GPRS1900 (1 Slot)	1850.2	<b>31.22</b>	-9	21.55
	1880	31.04	-9	21.46
	1909.8	30.90	-9	21.33
GPRS1900 (2 Slot)	1850.2	29.55	-6	22.42
	1880	29.46	-6	<b>22.63</b>
	1909.8	29.58	-6	22.47
GPRS1900 (3 Slot)	1850.2	27.43	-4.26	22.17
	1880	27.35	-4.26	22.32
	1909.8	27.51	-4.26	21.95
GPRS1900 (4 Slot)	1850.2	25.25	-3	21.33
	1880	25.37	-3	21.25
	1909.8	25.14	-3	21.19
EGPRS1900 (1 Slot)	1850.2	27.48	-9	18.48
	1880	27.79	-9	18.79
	1909.8	27.26	-9	18.26
EGPRS1900 (2 Slot)	1850.2	25.32	-6	19.32
	1880	25.18	-6	19.18
	1909.8	25.35	-6	19.35
EGPRS1900 (3 Slot)	1850.2	23.11	-4.26	18.85
	1880	23.09	-4.26	18.83
	1909.8	23.21	-4.26	18.95
EGPRS1900 (4 Slot)	1850.2	21.98	-3	18.98
	1880	21.77	-3	18.77
	1909.8	21.69	-3	18.69

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <2>				
PCS1900	1850.2	30.01	-9	21.01
	1880	30.05	-9	21.05
	1909.8	30.07	-9	21.07
GPRS1900 (1 Slot)	1850.2	30.12	-9	21.12
	1880	30.08	-9	21.08
	1909.8	30.09	-9	21.09
GPRS1900 (2 Slot)	1850.2	29.36	-6	23.36
	1880	29.28	-6	23.28
	1909.8	29.39	-6	23.39
GPRS1900 (3 Slot)	1850.2	27.35	-4.26	23.09
	1880	27.26	-4.26	23.00
	1909.8	27.45	-4.26	23.19
GPRS1900 (4 Slot)	1850.2	25.18	-3	22.18
	1880	25.26	-3	22.26
	1909.8	25.05	-3	22.05

Note 1:

The Frame Power (Source-based time-averaged Power) is scaled the maximum burst average power based on time slots. The calculated methods are show as following:

Frame Power = Max burst power (1 Up Slot) – 9 dB

Frame Power = Max burst power (2 Up Slot) – 6 dB

Frame Power = Max burst power (3 Up Slot) – 4.26 dB

Frame Power = Max burst power (4 Up Slot) – 3 dB

**UMTS BAND**

**HSDPA Setup Configuration:**

- The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- The RF path losses were compensated into the measurements.
- A call was established between EUT and Based Station with following setting:
  - (1) Set Gain Factors( $\beta_c$  and  $\beta_d$ ) parameters set according to each
  - (2) Set RMC 12.2Kbps+HSDPA mode.
  - (3) Set Cell Power=-86dBm
  - (4) Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
  - (5) Select HSDPA Uplink Parameters
  - (6) Set Delta ACK, Delta NACK and Delta CQI=8
  - (7) Set Ack - Nack Repetition Factor to 3
  - (8) Set CQI Feedback Cycle (k) to 4ms
  - (9) Set CQI Repetition Factor to 2
  - (10) Power Ctrl Mode=All Up bits
- The transmitted maximum output power was recorded.

Table C.10.2.4:  $\beta$  values for transmitter characteristics tests with HS-DPCCH

Sub-test	$\beta_c$ (Note5)	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15(Note 4)	15/15(Note 4)	64	12/15(Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1:  $\Delta ACK, \Delta NACK$  and  $\Delta CQI = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1Shenzhen Huaferui Technology Co., Ltd.,  $\Delta ACK$  and  $\Delta NACK = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ , and  $\Delta CQI = 24/15$  with  $\beta_{hs} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $hs/c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $c/d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $c = 11/15$  and  $d = 15/15$ .

**HSUPA Setup Configuration:**

- The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- The RF path losses were compensated into the measurements.
- A call was established between EUT and Base Station with following setting \* :
  - (1) Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
  - (2) Set the Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
  - (3) Set Cell Power = -86 dBm
  - (4) Set Channel Type = 12.2k + HSPA
  - (5) Set UE Target Power
  - (6) Power Ctrl Mode= Alternating bits
  - (7) Set and observe the E-TFCI
  - (8) Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- The transmitted maximum output power was recorded.

Table C.11.1.3:  $\beta$  values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note 1)	$\beta_{ec}$	$\beta_{ed}$ (Note 4) (Note 5)	$\beta_{ed}$ (SF)	$\beta_{ed}$ (Code s)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TF CI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}$ : 47/15 $\beta_{ed2}$ : 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4,  $\Delta ACK$ ,  $\Delta NACK$  and  $\Delta CQI = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ . For sub-test 5,  $\Delta ACK$ ,  $\Delta NACK$  and  $\Delta CQI = 5/15$  with  $\beta_{hs} = 5/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $hs/c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $c/d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $c = 10/15$  and  $d = 15/15$ .

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5:  $\beta_{ed}$  cannot be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

**UMTS BAND II**

<b>Mode</b>	<b>Frequency (MHz)</b>	<b>Avg. Burst Power (dBm)</b>
WCDMA 1900 RMC	1852.4	22.32
	1880	<b>22.57</b>
	1907.6	22.07
WCDMA 1900 AMR	1852.4	22.25
	1880	22.32
	1907.6	22.25
HSDPA Subtest 1	1852.4	21.19
	1880	21.62
	1907.6	21.16
HSDPA Subtest 2	1852.4	20.48
	1880	20.86
	1907.6	20.40
HSDPA Subtest 3	1852.4	20.47
	1880	20.80
	1907.6	20.33
HSDPA Subtest 4	1852.4	20.44
	1880	20.83
	1907.6	20.34
HSUPA Subtest 1	1852.4	19.24
	1880	19.42
	1907.6	18.97
HSUPA Subtest 2	1852.4	19.23
	1880	19.48
	1907.6	19.01
HSUPA Subtest 3	1852.4	20.15
	1880	20.38
	1907.6	19.93
HSUPA Subtest 4	1852.4	18.78
	1880	19.03
	1907.6	18.55
HSUPA Subtest 5	1852.4	20.59
	1880	20.77
	1907.6	18.93

**UMTS BAND IV**

<b>Mode</b>	<b>Frequency (MHz)</b>	<b>Avg. Burst Power (dBm)</b>
WCDMA 1700 RMC	1712.5	<b>23.68</b>
	1732.5	23.62
	1752.5	23.60
WCDMA 1700 AMR	1712.5	23.12
	1732.5	23.25
	1752.5	23.19
HSDPA Subtest 1	1712.5	22.36
	1732.5	21.70
	1752.5	21.70
HSDPA Subtest 2	1712.5	21.04
	1732.5	20.92
	1752.5	20.98
HSDPA Subtest 3	1712.5	21.16
	1732.5	20.91
	1752.5	21.05
HSDPA Subtest 4	1712.5	21.09
	1732.5	20.87
	1752.5	20.97
HSUPA Subtest 1	1712.5	19.64
	1732.5	19.49
	1752.5	19.50
HSUPA Subtest 2	1712.5	19.64
	1732.5	19.49
	1752.5	19.43
HSUPA Subtest 3	1712.5	20.66
	1732.5	20.50
	1752.5	20.38
HSUPA Subtest 4	1712.5	19.18
	1732.5	19.04
	1752.5	19.11
HSUPA Subtest 5	1712.5	21.02
	1732.5	20.91
	1752.5	20.85

**UMTS BAND V**

<b>Mode</b>	<b>Frequency (MHz)</b>	<b>Avg. Burst Power (dBm)</b>
WCDMA 850 RMC	826.4	21.19
	836.6	22.26
	846.6	<b>22.46</b>
WCDMA 850 AMR	826.4	22.05
	836.6	22.14
	846.6	22.09
HSDPA Subtest 1	826.4	20.22
	836.6	21.33
	846.6	21.43
HSDPA Subtest 2	826.4	19.49
	836.6	20.60
	846.6	20.72
HSDPA Subtest 3	826.4	19.40
	836.6	20.57
	846.6	20.69
HSDPA Subtest 4	826.4	19.36
	836.6	20.49
	846.6	20.64
HSUPA Subtest 1	826.4	18.49
	836.6	19.56
	846.6	19.67
HSUPA Subtest 2	826.4	18.51
	836.6	19.58
	846.6	19.61
HSUPA Subtest 3	826.4	19.55
	836.6	20.60
	846.6	20.58
HSUPA Subtest 4	826.4	17.96
	836.6	19.05
	846.6	19.22
HSUPA Subtest 5	826.4	18.71
	836.6	19.86
	846.6	19.91

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_d/\beta_{d'}=12/15$ , $\beta_{hs}/\beta_c=24/15$ .For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX\_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

**LTE Band**

Conducted Power of LTE Band 2(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					18607	18900	19193	
1.4MHz	QPSK	1	0	0	24.17	24.15	24.10	
			3	0	24.16	24.06	24.10	
			5	0	24.18	24.12	24.12	
		3	0	0	<b>24.30</b>	24.04	24.17	
			2	0	24.26	24.00	24.18	
			3	0	24.09	23.93	24.12	
	6	0	1	23.15	23.03	23.19		
	16QAM	1	0	1	23.26	23.31	23.01	
			3	1	23.31	23.19	23.05	
			5	1	23.26	23.32	22.98	
		3	0	1	23.10	22.97	23.02	
			2	1	23.12	22.99	23.02	
			3	1	22.98	22.91	22.95	
		6	0	2	22.25	21.92	22.21	
		Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel
						18615	18900	19185
3MHz	QPSK	1	0	0	24.03	24.13	24.14	
			7	0	23.59	23.74	24.07	
			14	0	23.52	23.79	24.02	
		8	0	1	22.77	22.84	23.29	
			4	1	22.77	22.84	23.31	
			7	1	22.50	22.73	23.28	
	15	0	1	22.66	22.79	23.21		
	16QAM	1	0	1	23.15	23.21	23.04	
			7	1	22.69	22.87	23.06	
			14	1	22.68	22.95	23.02	
		8	0	2	21.84	21.87	22.32	
			4	2	21.86	21.91	22.33	
			7	2	21.61	21.81	22.27	
		15	0	2	21.68	21.74	22.16	

Conducted Power of LTE Band 2(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					18625	18900	19175	
5MHz	QPSK	1	0	0	23.84	24.15	24.26	
			13	0	22.96	23.27	23.61	
			24	0	23.08	23.53	23.83	
		12	0	1	22.20	22.40	22.76	
			6	1	22.19	22.38	22.76	
			13	1	21.78	22.13	22.66	
		25	0	1	21.99	22.30	22.75	
		16QAM	1	0	1	22.77	23.23	23.24
				13	1	21.92	22.39	22.67
	24			1	22.12	22.70	22.96	
	12		0	2	21.21	21.47	21.84	
			6	2	21.24	21.50	21.87	
			13	2	20.83	21.24	21.82	
	25	0	2	21.04	21.27	21.82		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					18650	18900	19150	
10MHz	QPSK	1	0	0	22.93	23.44	23.77	
			25	0	22.62	23.00	23.66	
			49	0	22.96	22.61	23.15	
		25	0	1	21.75	22.33	22.78	
			13	1	21.74	22.29	22.77	
			25	1	21.77	21.86	22.52	
		50	0	1	21.80	22.17	22.68	
		16QAM	1	0	1	22.01	22.59	22.61
				25	1	21.79	22.23	22.55
	49			1	22.19	21.81	22.14	
	25		0	2	20.76	21.36	21.81	
			13	2	20.78	21.42	21.83	
			25	2	20.80	21.01	21.61	
	50	0	2	20.79	21.23	21.69		

Conducted Power of LTE Band 2(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					18675	18900	19125	
15MHz	QPSK	1	0	0	23.03	23.95	24.24	
			38	0	23.04	23.05	23.69	
			74	0	23.75	22.93	23.26	
		36	0	1	22.12	22.20	22.73	
			18	1	22.11	22.18	22.74	
			39	1	22.11	22.16	22.73	
		75	0	1	22.11	22.17	22.72	
		16QAM	1	0	1	22.15	23.18	23.13
				38	1	22.21	22.33	22.60
	74			1	23.00	22.23	22.26	
	36		0	2	22.11	22.16	22.73	
			18	2	22.11	22.16	22.73	
			39	2	22.11	22.15	22.73	
	75	0	2	21.11	21.19	21.74		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					18700	18900	19100	
20MHz	QPSK	1	0	0	23.04	23.97	23.78	
			50	0	23.55	22.95	23.61	
			99	0	23.77	23.01	22.96	
		50	0	1	21.74	22.42	23.03	
			25	1	21.74	22.39	23.04	
			50	1	22.80	21.74	22.43	
		100	0	1	22.35	22.14	22.79	
		16QAM	1	0	1	21.95	23.04	22.89
				50	1	22.54	22.09	22.77
	99			1	22.82	22.20	22.17	
	50		0	2	20.74	21.46	22.13	
			25	2	20.76	21.48	22.16	
			50	2	21.84	20.81	21.56	
	100	0	2	21.32	21.16	21.80		

Conducted Power of LTE Band 4(dBm)							
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					19957	20175	20393
1.4MHz	QPSK	1	0	0	22.64	21.90	22.65
			3	0	22.37	21.75	22.19
			5	0	22.59	21.85	22.19
		3	0	0	22.32	21.97	22.32
			2	0	22.31	21.97	22.30
			3	0	22.34	21.79	22.09
	6	0	1	22.34	21.88	22.22	
	16QAM	1	0	1	22.57	21.84	22.61
			3	1	22.46	21.72	22.28
			5	1	22.68	21.77	22.25
		3	0	1	22.27	21.82	22.24
			2	1	22.26	21.83	22.25
			3	1	22.27	21.65	22.01
		6	0	2	22.26	21.92	22.28
Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel
					19965	20175	20385
3MHz	QPSK	1	0	0	22.59	22.07	22.92
			7	0	22.51	21.77	22.56
			14	0	22.75	21.83	22.26
		8	0	1	22.48	21.98	22.69
			4	1	22.47	21.98	22.68
			7	1	22.56	21.82	22.29
	15	0	1	22.51	21.94	22.41	
	16QAM	1	0	1	22.68	22.28	22.77
			7	1	22.63	21.98	22.35
			14	1	22.86	22.01	22.06
		8	0	2	22.55	22.02	22.68
			4	2	22.54	22.03	22.68
			7	2	22.64	21.92	22.31
		15	0	2	22.55	21.91	22.36

Conducted Power of LTE Band 4(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					19975	20175	20375	
5MHz	QPSK	1	0	0	22.51	22.04	<b>23.04</b>	
			13	0	22.18	21.39	22.31	
			24	0	22.77	21.63	22.14	
		12	0	1	22.11	21.57	22.43	
			6	1	22.09	21.58	22.43	
			13	1	22.30	21.35	21.94	
		25	0	1	22.18	21.44	22.15	
		16QAM	1	0	1	22.45	22.26	22.93
				13	1	22.15	21.64	22.18
	24			1	22.74	21.88	22.04	
	12		0	2	22.14	21.67	22.48	
			6	2	22.14	21.69	22.47	
			13	2	22.33	21.46	21.99	
	25	0	2	22.21	21.45	22.19		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					20000	20175	20350	
10MHz	QPSK	1	0	0	21.86	21.58	22.10	
			25	0	22.32	21.29	22.31	
			49	0	21.98	20.90	21.36	
		25	0	1	22.22	21.58	22.24	
			13	1	22.20	21.59	22.22	
			25	1	22.30	21.19	21.93	
		50	0	1	22.30	21.39	22.08	
		16QAM	1	0	1	21.99	21.78	21.88
				25	1	22.46	21.54	22.10
	49			1	22.13	21.12	21.19	
	25		0	2	22.20	21.66	22.27	
			13	2	22.19	21.67	22.27	
			25	2	22.25	21.29	21.98	
	50		0	2	22.32	21.43	22.10	

Conducted Power of LTE Band 4(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					20025	20175	20325	
15MHz	QPSK	1	0	0	22.08	22.29	21.71	
			38	0	22.31	21.33	22.23	
			74	0	21.93	21.26	21.72	
		36	0	1	22.39	21.52	21.97	
			18	1	22.38	21.52	21.95	
			39	1	22.38	21.51	21.95	
		75	0	1	22.37	21.52	21.90	
		16QAM	1	0	1	22.26	22.54	21.49
				38	1	22.47	21.67	22.05
	74			1	22.10	21.63	21.52	
	36		0	2	22.38	21.53	21.94	
			18	2	22.39	21.52	21.93	
			39	2	22.38	21.52	21.92	
	75	0	2	22.33	21.56	21.93		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					20050	20175	20300	
20MHz	QPSK	1	0	0	22.27	22.51	22.35	
			50	0	22.43	21.31	21.84	
			99	0	21.27	21.46	21.60	
		50	0	1	22.52	21.91	21.43	
			25	1	22.49	21.93	21.41	
			50	1	21.81	21.21	21.85	
		100	0	1	22.24	21.57	21.62	
		16QAM	1	0	1	22.26	22.57	21.42
				50	1	22.39	21.50	21.89
	99			1	21.26	21.70	21.64	
	50		0	2	22.50	21.96	21.48	
			25	2	22.48	21.98	21.46	
			50	2	21.82	21.28	21.90	
	100	0	2	22.22	21.62	21.65		

Conducted Power of LTE Band 5(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					20407	20525	20643	
1.4MHz	QPSK	1	0	0	23.56	23.56	23.71	
			3	0	23.54	23.55	23.71	
			5	0	23.53	23.57	23.72	
		3	0	0	23.64	23.60	<b>23.81</b>	
			2	0	23.65	23.59	23.80	
			3	0	23.62	23.60	23.76	
		6	0	1	22.56	22.56	22.72	
		16QAM	1	0	1	22.68	22.69	22.65
				3	1	22.72	22.76	22.68
	5			1	22.67	22.76	22.62	
	3		0	1	22.52	22.55	22.65	
			2	1	22.52	22.55	22.65	
			3	1	22.49	22.55	22.59	
	6	0	2	21.64	21.44	21.73		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					20415	20525	20635	
3MHz	QPSK	1	0	0	23.54	23.52	23.69	
			7	0	23.54	23.55	23.72	
			14	0	23.51	23.52	23.69	
		8	0	1	22.60	22.60	22.81	
			4	1	22.60	22.60	22.82	
			7	1	22.58	22.61	22.82	
		15	0	1	22.58	22.62	22.77	
		16QAM	1	0	1	22.69	22.68	22.59
				7	1	22.70	22.72	22.65
	14			1	22.68	22.66	22.61	
	8		0	2	21.69	21.58	21.79	
			4	2	21.68	21.57	21.77	
			7	2	21.67	21.62	21.79	
	15	0	2	21.64	21.53	21.68		

Conducted Power of LTE Band 5(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					20425	20525	20625	
5MHz	QPSK	1	0	0	23.67	23.64	23.77	
			13	0	23.67	23.63	23.77	
			24	0	23.59	23.61	23.75	
		12	0	1	22.63	22.66	22.78	
			6	1	22.63	22.66	22.77	
			13	1	22.64	22.66	22.81	
		25	0	1	22.59	22.62	22.75	
		16QAM	1	0	1	22.65	22.88	22.80
				13	1	22.65	22.86	22.82
	24			1	22.60	22.83	22.80	
	12		0	2	21.68	21.69	21.80	
			6	2	21.68	21.69	21.79	
			13	2	21.69	21.68	21.82	
	25	0	2	21.65	21.58	21.77		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
20450						20525	20600	
10MHz	QPSK	1	0	0	22.05	22.64	23.71	
			25	0	23.43	22.54	22.23	
			49	0	23.53	23.13	22.35	
		25	0	1	22.26	21.84	22.41	
			13	1	22.09	21.37	22.72	
			25	1	21.47	21.77	22.78	
		50	0	1	21.10	21.61	21.59	
		16QAM	1	0	1	21.45	21.93	21.41
				25	1	21.25	22.93	21.35
	49			1	21.81	22.98	21.90	
	25		0	2	20.71	22.60	20.94	
			13	2	20.49	22.90	20.73	
			25	2	21.12	22.82	20.39	
	50		0	2	20.98	21.60	21.64	

Conducted Power of LTE Band 7 (dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					20775	21100	21425	
5MHz	QPSK	1	0	0	<b>22.89</b>	22.62	22.50	
			12	0	22.11	22.04	21.86	
			24	0	22.57	22.47	22.23	
		12	0	1	21.16	21.14	20.86	
			6	1	21.15	21.15	20.87	
			13	1	21.02	21.07	20.83	
		25	0	1	21.04	21.12	20.89	
		16QAM	1	0	1	21.71	21.71	21.37
				12	1	21.04	21.17	20.81
	24			1	21.52	21.65	21.29	
	12		0	2	20.21	20.20	20.02	
			6	2	20.24	20.24	20.05	
			13	2	20.12	20.18	19.97	
	25	0	2	20.11	20.06	19.93		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					20800	21100	21400	
10MHz	QPSK	1	0	0	21.88	21.90	19.94	
			24	0	21.70	21.87	21.89	
			49	0	21.82	21.52	21.51	
		25	0	1	20.77	20.98	21.08	
			12	1	20.77	20.98	21.09	
			25	1	20.81	20.86	20.79	
		50	0	1	20.87	20.94	20.95	
		16QAM	1	0	1	20.99	22.19	21.05
				24	1	20.91	21.03	20.85
	49			1	20.98	21.08	20.45	
	25		0	2	19.84	20.77	20.13	
			12	2	19.88	19.99	20.18	
			25	2	19.87	20.01	19.97	
	50	0	2	19.92	19.93	20.02		

**Conducted Power of LTE Band 7 (dBm)**

Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					20825	21100	21375	
15MHz	QPSK	1	0	0	21.94	22.02	22.43	
			37	0	21.83	21.79	21.93	
			74	0	22.44	21.61	21.68	
		37	0	1	20.97	20.73	21.05	
			16	1	20.96	20.73	21.04	
			35	1	20.96	20.73	21.04	
	75	0	1	20.95	20.74	21.04		
	16QAM	1	0	1	21.01	21.24	21.38	
			37	1	20.95	21.08	20.85	
			74	1	21.64	21.00	20.64	
		37	0	2	20.96	20.73	21.04	
			16	2	20.95	20.73	21.03	
			35	2	20.95	20.74	21.03	
		75	0	2	19.89	19.81	20.07	
Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
						20850	21100	21350
20MHz	QPSK	1	0	0	21.96	22.23	22.50	
			49	0	22.09	21.81	22.06	
			99	0	22.55	21.86	21.61	
		50	0	1	20.67	20.93	21.48	
			25	1	20.65	20.92	21.50	
			49	1	21.37	20.73	20.92	
	100	0	1	21.14	20.84	21.26		
	16QAM	1	0	1	20.88	21.34	21.54	
			49	1	21.03	20.99	21.22	
			99	1	21.62	21.09	20.83	
		50	0	2	19.72	19.94	20.56	
			25	2	19.75	19.97	20.60	
			49	2	20.48	19.79	20.10	
		100	0	2	20.17	19.83	20.33	

Conducted Power of LTE Band 12(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					23017	23095	23173	
1.4MHz	QPSK	1	0	0	22.34	22.40	22.50	
			3	0	22.42	22.38	22.53	
			5	0	22.41	22.40	22.53	
		3	0	0	22.50	22.50	22.62	
			2	0	22.50	22.49	<b>22.62</b>	
			3	0	22.51	22.49	22.60	
		6	0	1	22.41	22.40	22.50	
		16QAM	1	0	1	22.45	22.48	22.38
				3	1	22.58	22.52	22.44
	5			1	22.52	22.50	22.40	
	3		0	1	22.37	22.38	22.41	
			2	1	22.37	22.38	22.41	
			3	1	22.38	22.37	22.36	
	6	0	2	22.43	22.25	22.49		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					23025	23095	23165	
3MHz	QPSK	1	0	0	22.23	22.39	22.47	
			7	0	22.38	22.38	22.52	
			14	0	22.32	22.35	22.52	
		8	0	1	22.45	22.47	22.57	
			4	1	22.46	22.46	22.57	
			7	1	22.44	22.44	22.60	
		15	0	1	22.41	22.43	22.54	
		16QAM	1	0	1	22.40	22.50	22.32
				7	1	22.54	22.48	22.41
	14			1	22.46	22.42	22.41	
	8		0	2	22.47	22.43	22.55	
			4	2	22.47	22.43	22.55	
			7	2	22.46	22.44	22.59	
	15	0	2	22.41	22.33	22.45		

Conducted Power of LTE Band 12(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					23035	23095	23155	
5MHz	QPSK	1	0	0	22.46	22.50	22.54	
			13	0	22.53	22.52	22.57	
			24	0	22.48	22.41	22.57	
		12	0	1	22.53	22.51	22.55	
			6	1	22.53	22.52	22.55	
			13	1	22.52	22.46	22.58	
		25	0	1	22.49	22.43	22.51	
		16QAM	1	0	1	22.43	22.55	22.51
				13	1	22.49	22.56	22.55
	24			1	22.46	22.56	22.55	
	12		0	2	22.52	22.52	22.57	
			6	2	22.51	22.53	22.57	
			13	2	22.52	22.48	22.58	
	25	0	2	22.47	22.39	22.52		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					23060	23095	23130	
10MHz	QPSK	1	0	0	21.40	22.18	22.45	
			25	0	21.17	22.49	21.76	
			49	0	21.69	22.11	21.15	
		25	0	1	22.15	21.83	21.92	
			13	1	22.39	21.35	21.78	
			25	1	21.48	21.78	21.52	
		50	0	1	21.12	22.06	21.46	
		16QAM	1	0	1	22.17	21.27	21.08
				25	1	22.31	21.53	21.22
	49			1	22.25	21.53	22.06	
	25		0	2	21.44	21.88	22.34	
			13	2	22.17	21.39	22.19	
			25	2	21.86	21.92	22.56	
	50		0	2	22.23	21.16	21.16	

Conducted Power of LTE Band 17(dBm)							
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					23755	23790	23825
5MHz	QPSK	1	0	0	23.53	23.47	23.51
			13	0	23.51	23.50	23.55
			24	0	23.44	23.47	<b>23.56</b>
		12	0	1	22.55	22.49	22.56
			6	1	22.55	22.50	22.56
			13	1	22.50	22.50	22.61
	25	0	1	22.48	22.46	22.53	
	16QAM	1	0	1	22.80	22.53	22.54
			13	1	22.73	22.55	22.59
			24	1	22.70	22.53	22.61
		12	0	2	21.67	21.60	21.62
			6	2	21.67	21.60	21.62
			13	2	21.60	21.61	21.64
		25	0	2	21.52	21.56	21.61
Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel
					23780	23790	23800
10MHz	QPSK	1	0	0	23.07	22.83	21.49
			25	0	23.33	22.98	22.08
			49	0	22.55	23.15	21.96
		25	0	1	21.41	21.71	20.38
			13	1	21.71	22.29	20.56
			25	1	21.00	22.55	21.52
	50	0	1	21.13	22.53	21.41	
	16QAM	1	0	1	23.42	21.70	22.09
			25	1	22.96	22.68	21.94
			49	1	22.84	23.19	22.49
		25	0	2	21.24	22.41	20.82
			13	2	21.12	22.73	21.19
			25	2	22.06	22.79	21.39
		50	0	2	21.55	21.86	21.40

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3.3-1 of the 3GPP TS36.101.

**Table 6.2.3.3-1 Maximum Power Reduction (MPR) for Power class3**

Modulation	Maximum Power Reduction (MPR) for Power[RB]						MPR(dB)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
QPSK	>5	>4	>8	>12	>16	>18	≤1
16QAM	≤5	≤4	≤8	≤12	≤16	≤18	≤1
16QAM	>5	>4	>8	>12	>16	>18	≤2

The allowed A-MPR values specified below in Table 6.2.4.3-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS\_01".3

**Table 6.2.4.3-1: Additional Maximum Power Reduction (A-MPR) / Spectrum Emission requirements**

Network Signaling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks ( $N_{RB}$ )	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.2-1	1.4,3,5,10,15,20	Table 5.4.2-1	N/A
NS_03	6.6.2.2.3.1	2,4,10, 23, 25,35,36	3	>5	$\leq 1$
			5	>6	$\leq 1$
			10	>6	$\leq 1$
			15	>8	$\leq 1$
			20	>10	$\leq 1$
NS_04	6.6.2.2.3.2	41	5	>6	$\leq 1$
			10, 15, 20	Table 6.2.4.3-4	
NS_05	6.6.3.3.3.1	1	10,15,20	$\geq 50$	$\leq 1$
NS_06	6.6.2.2.3.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.4.2-1	N/A
NS_07	6.6.2.2.3.3 6.6.3.3.3.2	13	10	Table 6.2.4.3-2	Table 6.2.4.3-2
NS_08	6.6.3.3.3.3	19	10, 15	> 44	$\leq 3$
NS_09	6.6.3.3.3.4	21	10, 15	> 40	$\leq 1$
				> 55	$\leq 2$
NS_10		20	15, 20	Table 6.2.4.3-3	Table 6.2.4.3-3
NS_11	6.6.2.2.1 6.6.3.3.13	231	1.4, 3, 5, 10,15,20	Table 6.2.4.3-5	Table 6.2.4.3-5
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4.3-6	Table 6.2.4.3-6
NS_13	6.6.3.3.6	26	5	Table 6.2.4.3-7	Table 6.2.4.3-7
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4.3-8	Table 6.2.4.3-8
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4.3-9 Table 6.2.4.3-10	Table 6.2.4.3-9, Table 6.2.4.3-10
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4.3-11, Table 6.2.4.3-12, Table 6.2.4.3-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.4.2-1	N/A
	6.6.3.3.11	28	5	$\geq 2$	$\leq 1$
NS_18			10, 15, 20	$\geq 1$	$\leq 4$
NS_19			10, 15, 20	Table 6.2.4.3-15	Table 6.2.4.3-15
NS_20			5, 10, 15, 20	Table 6.2.4.3-14	Table 6.2.4.3-14
...					
NS_20	-	-	-	-	-

**WIFI**

Mode	Data Rate (Mbps)	Channel	Frequency(MHz)	Avg. Burst Power(dBm)
802.11b	1	01	2412	<b>10.09</b>
		06	2437	9.91
		11	2462	9.73
802.11g	6	01	2412	9.42
		06	2437	9.88
		11	2462	9.76
802.11n(20)	6.5	01	2412	9.73
		06	2437	10.04
		11	2462	9.83
802.11n(40)	13.5	03	2422	9.70
		06	2437	9.74
		09	2452	9.64

**Bluetooth\_V4.0(BR/EDR)**

Modulation	Channel	Frequency(MHz)	Peak Power (dBm)
GFSK	0	2402	0.012
	39	2441	-0.634
	78	2480	<b>1.496</b>
$\pi/4$ -DQPSK	0	2402	-0.638
	39	2441	-1.263
	78	2480	0.825
8-DPSK	0	2402	-0.562
	39	2441	-1.068
	78	2480	0.913

**Bluetooth\_V4.0(BLE)**

Modulation	Channel	Frequency(MHz)	Peak Power (dBm)
GFSK	0	2402	-0.039
	19	2440	-0.591
	39	2480	<b>1.529</b>

## 13. TEST RESULTS

### 13.1. SAR Test Results Summary

#### 13.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE 1528-2013, Body-worn and 4 Edges SAR was performed with the device 10mm from the phantom.

#### 13.1.2. Operation Mode

1. Per KDB 447498 D01 v06 ,for each exposure position, if the highest 1-g SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional.
2. Per KDB 865664 D01 v01r04,for each frequency band, if the measured SAR is  $\geq 0.8$ W/Kg, testing for repeated SAR measurement is required , that the highest measured SAR is only to be tested. When the SAR results are near the limit, the following procedures are required for each device to verify these types of SAR measurement related variation concerns by repeating the highest measured SAR configuration in each frequency band.
  - (1) When the original highest measured SAR is  $\geq 0.8$ W/Kg, repeat that measurement once.
  - (2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $>1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/Kg.
  - (3) Perform a third repeated measurement only if the original, first and second repeated measurement is  $\geq 1.5$  W/Kg and ratio of largest to smallest SAR for the original, first and second measurement is  $\geq 1.20$ .
3. Body-worn exposure conditions are intended to voice call operations, therefore GSM voice call mode is selected to be test.
4. Per KDB 648474 D04 v01r03,when the reported SAR for a body-worn accessory measured without a headset connected to the handset is  $\leq 1.2$ W/Kg, SAR testing with a headset connected is not required.
5. Per KDB 248227 D01v02r02,for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$ W/kg.
6. Per KDB 941225 D06 V02r01, When the same wireless mode transmission configurations for voice and data are required for SAR measurements, the more conservative configuration with a smaller separation distance should be tested for the overlapping SAR configurations.
7. Maximum Scaling SAR in order to calculate the Maximum SAR values to test under the standard Peak Power, Calculation method is as follows:  
Maximum Scaling SAR =tested SAR (Max.)  $\times$  [maximum turn-up power (mw)/ maximum measurement output power(mw) ]
8. Proximity sensor, just for avoiding the wrong operation in the phone screen when call, and has no influence on output power or SAR result
9. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1RB allocation using the RB offset and required test channel combination with highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
10. Per KDB 941125 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
11. Per KDB 941125 D05v02r03. For QPSK with 100% RB allocation. SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and

1RB allocation and the highest reported SAR is  $>1.45$  W/Kg, the remaining required test channels must also be tested.

12. Per KDB 941125 D05v02r03. 16QAM output power for each RB allocation configuration is not 1/2 dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$ W/Kg, Per KDB 941225 D05v02r02, 16QAM SAR testing is not required.
13. Per KDB 941125 D05v02r03. Smaller bandwidth output power for each RB allocation configuration is  $>$ not 1/2 dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$ W/Kg. Per KDB 941125 D05v02r03, smaller bandwidth SAR testing is not required.

### 13.1.3. Test Result

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%):47.1				
Product: Smart Phone									
Test Mode: GSM850 with GMSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<math>\pm 0.2</math> dB)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
<b>SIM 1 Card</b>									
Left Cheek	voice	190	836.6	0.02	0.308	33.50	33.40	0.315	1.6
Left Tilt	voice	190	836.6	-0.10	0.234	33.50	33.40	0.239	1.6
Right Cheek	voice	190	836.6	0.07	<b>0.334</b>	33.50	33.40	<b>0.342</b>	1.6
Right Tilt	voice	190	836.6	-0.03	0.199	33.50	33.40	0.204	1.6
Body back	voice	190	836.6	0.10	<b>0.506</b>	33.50	33.40	<b>0.518</b>	1.6
Body front	voice	190	836.6	-0.04	0.346	33.50	33.40	0.354	1.6
Body back	GPRS-3 slot	190	836.6	0.07	0.686	29.00	28.87	0.707	1.6
Body front	GPRS-3 slot	190	836.6	-0.10	0.527	29.00	28.87	0.543	1.6
Edge 2(Right)	GPRS-3 slot	190	836.6	0.02	0.415	29.00	28.87	0.428	1.6
Edge 3(Bottom)	GPRS-3 slot	190	836.6	0.12	0.250	29.00	28.87	0.258	1.6
Edge 4(Left)	GPRS-3 slot	190	836.6	-0.11	<b>0.702</b>	29.00	28.87	<b>0.723</b>	1.6

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 49.2				
Product: Smart Phone									
Test Mode: PCS1900 with GMSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2 dB)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
<b>SIM 1 Card</b>									
Left Cheek	voice	661	1880.0	0.13	<b>0.193</b>	31.30	31.04	<b>0.205</b>	1.6
Left Tilt	voice	661	1880.0	0.01	0.094	31.30	31.04	0.100	1.6
Right Cheek	voice	661	1880.0	0.06	0.177	31.30	31.04	0.188	1.6
Right Tilt	voice	661	1880.0	-0.04	0.126	31.30	31.04	0.134	1.6
Body back	voice	661	1880.0	0.05	<b>0.455</b>	31.30	31.04	<b>0.483</b>	1.6
Body front	voice	661	1880.0	0.01	0.363	31.30	31.04	0.385	1.6
Body back	GPRS-2 slot	661	1880.0	0.07	0.686	29.60	29.46	0.708	1.6
Body front	GPRS-2 slot	661	1880.0	0.09	0.570	29.60	29.46	0.589	1.6
Edge 2(Right)	GPRS-2 slot	661	1880.0	-0.14	0.204	29.60	29.46	0.211	1.6
Edge 3(Bottom)	GPRS-2 slot	512	1850.2	-0.05	0.797	29.60	29.55	0.806	1.6
Edge 3(Bottom)	GPRS-2 slot	661	1880.0	-0.09	1.01	29.60	29.46	1.043	1.6
Edge 3(Bottom)	GPRS-2 slot	810	1909.8	-0.15	<b>1.07</b>	29.60	29.58	<b>1.075</b>	1.6
Edge 4(Left)	GPRS-2 slot	661	1880.0	-0.08	0.129	29.60	29.46	0.133	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 49.2				
Product: Smart Phone									
Test Mode: WCDMA Band II with QPSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<math>\pm 0.2</math> dB)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
Left Cheek	RMC 12.2kbps	9400	1880	0.01	<b>0.178</b>	22.60	22.57	<b>0.179</b>	1.6
Left Tilt	RMC 12.2kbps	9400	1880	0.12	0.095	22.60	22.57	0.096	1.6
Right Cheek	RMC 12.2kbps	9400	1880	0.17	0.171	22.60	22.57	0.172	1.6
Right Tilt	RMC 12.2kbps	9400	1880	-0.01	0.135	22.60	22.57	0.136	1.6
Body back	RMC 12.2kbps	9400	1880	0.17	0.640	22.60	22.57	0.644	1.6
Body front	RMC 12.2kbps	9400	1880	0.14	0.353	22.60	22.57	0.355	1.6
Edge 2(Right)	RMC 12.2kbps	9400	1880	0.14	0.123	22.60	22.57	0.124	1.6
Edge 3(Bottom)	RMC 12.2kbps	9262	1852.4	0.07	0.807	22.60	22.32	0.861	1.6
Edge 3(Bottom)	RMC 12.2kbps	9400	1880	-0.03	0.916	22.60	22.57	0.922	1.6
Edge 3(Bottom)	RMC 12.2kbps	9538	1907.6	0.09	<b>0.974</b>	22.60	22.07	<b>1.100</b>	1.6
Edge 4(Left)	RMC 12.2kbps	9400	1880	-0.12	0.103	22.60	22.57	0.104	1.6

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 52.1				
Product: Smart Phone									
Test Mode: WCDMA Band IV with QPSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<math>\pm 0.2</math> dB)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
Left Cheek	RMC 12.2kbps	8662	1732.5	0.12	0.231	23.70	23.62	0.235	1.6
Left Tilt	RMC 12.2kbps	8662	1732.5	-0.07	0.121	23.70	23.62	0.123	1.6
Right Cheek	RMC 12.2kbps	8662	1732.5	-0.13	<b>0.287</b>	23.70	23.62	<b>0.292</b>	1.6
Right Tilt	RMC 12.2kbps	8662	1732.5	-0.05	0.180	23.70	23.62	0.183	1.6
Body back	RMC 12.2kbps	8662	1732.5	0.05	0.661	23.70	23.62	0.673	1.6
Body front	RMC 12.2kbps	8662	1732.5	-0.00	0.540	23.70	23.62	0.550	1.6
Edge 2(Right)	RMC 12.2kbps	8662	1732.5	0.18	0.194	23.70	23.62	0.198	1.6
Edge 3(Bottom)	RMC 12.2kbps	8562	1712.5	-0.05	0.945	23.70	23.68	0.949	1.6
Edge 3(Bottom)	RMC 12.2kbps	8662	1732.5	-0.09	<b>1.05</b>	23.70	23.62	<b>1.070</b>	1.6
Edge 3(Bottom)	RMC 12.2kbps	8763	1752.5	-0.15	0.828	23.70	23.60	0.847	1.6
Edge 4(Left)	RMC 12.2kbps	8662	1732.5	0.00	0.118	23.70	23.62	0.120	1.6

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 47.1				
Product: Smart Phone									
Test Mode: WCDMA Band V with QPSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2 dB)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
Left Cheek	RMC 12.2kbps	4183	836.6	0.11	0.245	22.50	22.26	0.259	1.6
Left Tilt	RMC 12.2kbps	4183	836.6	-0.14	0.208	22.50	22.26	0.220	1.6
Right Cheek	RMC 12.2kbps	4183	836.6	0.11	<b>0.265</b>	22.50	22.26	<b>0.280</b>	1.6
Right Tilt	RMC 12.2kbps	4183	836.6	0.03	0.176	22.50	22.26	0.186	1.6
Body back	RMC 12.2kbps	4183	836.6	0.02	<b>0.412</b>	22.50	22.26	<b>0.435</b>	1.6
Body front	RMC 12.2kbps	4183	836.6	-0.14	0.274	22.50	22.26	0.290	1.6
Edge 2(Right)	RMC 12.2kbps	4183	836.6	0.07	0.227	22.50	22.26	0.240	1.6
Edge 3(Bottom)	RMC 12.2kbps	4183	836.6	-0.18	0.141	22.50	22.26	0.149	1.6
Edge 4(Left)	RMC 12.2kbps	4183	836.6	0.14	0.385	22.50	22.26	0.407	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 52.6						
Product: Smart Phone												
Test Mode: LTE Band 2												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<±0.2 dB)	SAR (1g) (W/kg)	Max. Tune up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
20	QPSK	Left Cheek	1	0	18900	1880	0.01	<b>0.229</b>	24.30	23.97	<b>0.247</b>	1.6
		Left Tilt	1	0	18900	1880	-0.05	0.098	24.30	23.97	0.106	1.6
		Right Cheek	1	0	18900	1880	0.04	0.215	24.30	23.97	0.232	1.6
		Right Tilt	1	0	18900	1880	-0.09	0.133	24.30	23.97	0.143	1.6
		Body back	1	0	18900	1880	-0.12	0.773	24.30	23.97	0.834	1.6
		Body front	1	0	18900	1880	-0.16	0.406	24.30	23.97	0.438	1.6
		Edge 2(Right)	1	0	18900	1880	-0.13	0.201	24.30	23.97	0.217	1.6
		Edge 3(Bottom)	1	0	18700	1860	-0.03	0.872	24.30	23.04	<b>1.166</b>	1.6
		Edge 3(Bottom)	1	0	18900	1880	-0.16	<b>0.888</b>	24.30	23.97	0.958	1.6
		Edge 3(Bottom)	1	0	19100	1900	-0.13	0.818	24.30	23.78	0.922	1.6
		Edge 4(Left)	1	0	18900	1880	-0.09	0.133	24.30	23.97	0.143	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 52.1						
Product: Smart Phone												
Test Mode: LTE Band 4												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<±0.2 dB)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
20	QPSK	Left Cheek	1	0	20175	1732.5	0.16	<b>0.303</b>	23.04	22.51	<b>0.342</b>	1.6
		Left Tilt	1	0	20175	1732.5	-0.14	0.139	23.04	22.51	0.157	1.6
		Right Cheek	1	0	20175	1732.5	0.14	0.271	23.04	22.51	0.306	1.6
		Right Tilt	1	0	20175	1732.5	0.04	0.186	23.04	22.51	0.210	1.6
		Body back	1	0	20175	1732.5	0.02	0.622	23.04	22.51	0.703	1.6
		Body front	1	0	20175	1732.5	0.09	0.595	23.04	22.51	0.672	1.6
		Edge 2(Right)	1	0	20175	1732.5	-0.19	0.235	23.04	22.51	0.266	1.6
		Edge 3(Bottom)	1	0	20050	1720	-0.12	0.813	23.04	22.27	0.971	1.6
		Edge 3(Bottom)	1	0	20175	1732.5	-0.10	0.865	23.04	22.51	0.977	1.6
		Edge 3(Bottom)	1	0	20300	1745	-0.10	<b>0.961</b>	23.04	22.35	<b>1.126</b>	1.6
		Edge 4(Left)	1	0	20175	1732.5	0.10	0.133	23.04	22.51	0.150	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 46.5						
Product: Smart Phone												
Test Mode: LTE Band 5												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<±0.2 dB)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
10	QPSK	Left Cheek	1	0	20525	836.5	-0.10	0.305	23.90	22.64	0.408	1.6
		Left Tilt	1	0	20525	836.5	-0.11	0.218	23.90	22.64	0.291	1.6
		Right Cheek	1	0	20525	836.5	0.14	<b>0.335</b>	23.90	22.64	<b>0.448</b>	1.6
		Right Tilt	1	0	20525	836.5	0.05	0.229	23.90	22.64	0.306	1.6
		Body back	1	0	20525	836.5	0.06	<b>0.508</b>	23.90	22.64	<b>0.679</b>	1.6
		Body front	1	0	20525	836.5	-0.07	0.345	23.90	22.64	0.461	1.6
		Edge 2(Right)	1	0	20525	836.5	-0.02	0.253	23.90	22.64	0.338	1.6
		Edge 3(Bottom)	1	0	20525	836.5	-0.15	0.017	23.90	22.64	0.023	1.6
		Edge 4(Left)	1	0	20525	836.5	-0.01	0.454	23.90	22.64	0.607	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 49.3						
Product: Smart Phone												
Test Mode: LTE Band 7												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<math>\pm 0.2</math> dB)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
20	QPSK	Left Cheek	1	0	21100	2535	-0.13	0.225	22.90	22.23	0.263	1.6
		Left Tilt	1	0	21100	2535	0.05	0.204	22.90	22.23	0.238	1.6
		Right Cheek	1	0	21100	2535	0.14	<b>0.381</b>	22.90	22.23	<b>0.445</b>	1.6
		Right Tilt	1	0	21100	2535	0.10	0.111	22.90	22.23	0.130	1.6
		Body back	1	0	21100	2535	-0.09	0.354	22.90	22.23	0.413	1.6
		Body front	1	0	21100	2535	0.01	0.220	22.90	22.23	0.257	1.6
		Edge 2(Right)	1	0	21100	2535	0.18	0.151	22.90	22.23	0.176	1.6
		Edge 3(Bottom)	1	0	21100	2535	0.07	<b>0.459</b>	22.90	22.23	<b>0.536</b>	1.6
		Edge 4(Left)	1	0	21100	2535	-0.14	0.069	22.90	22.23	0.081	1.6

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 47.2						
Product: Smart Phone												
Test Mode: LTE Band 12												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<math>\pm 0.2</math> dB)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
10	QPSK	Left Cheek	1	0	23095	707.5	0.11	0.172	22.70	22.18	0.194	1.6
		Left Tilt	1	0	23095	707.5	0.09	0.139	22.70	22.18	0.157	1.6
		Right Cheek	1	0	23095	707.5	0.19	<b>0.194</b>	22.70	22.18	<b>0.219</b>	1.6
		Right Tilt	1	0	23095	707.5	0.01	0.142	22.70	22.18	0.160	1.6
		Body back	1	0	23095	707.5	-0.09	<b>0.359</b>	22.70	22.18	<b>0.405</b>	1.6
		Body front	1	0	23095	707.5	-0.01	0.194	22.70	22.18	0.219	1.6
		Edge 2(Right)	1	0	23095	707.5	-0.07	0.157	22.70	22.18	0.177	1.6
		Edge 3(Bottom)	1	0	23095	707.5	0.12	0.083	22.70	22.18	0.094	1.6
		Edge 4(Left)	1	0	23095	707.5	-0.03	0.189	22.70	22.18	0.213	1.6

Note:

- When the 1-g Reported SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 47.2						
Product: Smart Phone												
Test Mode: LTE Band 17												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<math>\leq \pm 0.2 \text{ dB}</math>)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
10	QPSK	Left Cheek	1	0	23790	710	0.14	0.195	23.60	22.83	0.233	1.6
		Left Tilt	1	0	23790	710	0.04	0.137	23.60	22.83	0.164	1.6
		Right Cheek	1	0	23790	710	0.15	<b>0.219</b>	23.60	22.83	<b>0.261</b>	1.6
		Right Tilt	1	0	23790	710	0.09	0.146	23.60	22.83	0.174	1.6
		Body back	1	0	23790	710	-0.04	<b>0.476</b>	23.60	22.83	<b>0.568</b>	1.6
		Body front	1	0	23790	710	0.06	0.258	23.60	22.83	0.308	1.6
		Edge 2(Right)	1	0	23790	710	0.06	0.195	23.60	22.83	0.233	1.6
		Edge 3(Bottom)	1	0	23790	710	0.12	0.076	23.60	22.83	0.091	1.6
		Edge 4(Left)	1	0	23790	710	0.09	0.251	23.60	22.83	0.300	1.6

Note:

- When the 1-g Reported SAR is  $\leq 0.8 \text{ W/kg}$ , testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 48.4				
Product: Smart Phone									
Test Mode:802.11b									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2 dB)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
Left Cheek	DTS	6	2437	0.04	0.175	10.10	9.91	0.183	1.6
Left Tilt	DTS	6	2437	0.11	0.157	10.10	9.91	0.164	1.6
Right Cheek	DTS	6	2437	0.14	<b>0.347</b>	10.10	9.91	<b>0.363</b>	1.6
Right Tilt	DTS	6	2437	0.11	0.236	10.10	9.91	0.247	1.6
Body back	DTS	6	2437	-0.04	0.128	10.10	9.91	0.134	1.6
Body front	DTS	6	2437	0.09	0.090	10.10	9.91	0.094	1.6
Edge 1 (Top)	DTS	6	2437	-0.01	0.047	10.10	9.91	0.049	1.6
Edge 4(Left)	DTS	6	2437	0.13	<b>0.132</b>	10.10	9.91	<b>0.138</b>	1.6

Note:

- According to KDB248227, SAR is not required for 802.11n HT20/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a/b channels.
- All of above "DTS" means data transmitters.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

Repeated SAR										
Product: Smart Phone										
Test Mode: PCS1900& WCDMA Band II& WCDMA Band IV										
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2 dB)	Once SAR (1g) (W/kg)	Power Drift (<±5%)	Twice SAR (1g) (W/kg)	Power Drift (<±0.2 dB)	Third SAR (1g) (W/kg)	Limit (W/kg)
Edge 3(Bottom)	GPRS-2 slot	810	1909.8	0.11	1.08	--	--	--	--	1.6
Edge 3(Bottom)	RMC 12.2kbps	9538	1907.6	0.13	0.969	--	--	--	--	1.6
Edge 3(Bottom)	RMC 12.2kbps	8662	1732.5	0.05	1.02	--	--	--	--	1.6

Repeated SAR											
Product: Smart Phone											
Test Mode: LTE Band 2& LTE Band 4											
Position	Test Mode		Ch.	Fr. (MHz)	Power Drift (<±0.2 dB)	Once SAR (1g) (W/kg)	Power Drift (<±5%)	Twice SAR (1g) (W/kg)	Power Drift (<±0.2 dB)	Third SAR (1g) (W/kg)	Limit (W/kg)
	UL RB Allocation	UL RB START									
Edge 3(Bottom)	1	0	18900	1880	0.03	0.864		--	--	--	1.6
Edge 3(Bottom)	1	0	20300	1745	-0.11	0.958		--	--	--	1.6

**Simultaneous Multi-band Transmission Evaluation:**  
**Application Simultaneous Transmission information:**

NO	Simultaneous state	Portable Handset		
		Head	Body-worn	Hotspot
1	GSM(voice)+ WLAN 2.4GHz (data)	Yes	Yes	-
2	GSM(voice)+ Bluetooth(data)	-	Yes	-
3	GSM (Data) + WLAN 2.4GHz (data)	-	Yes	Yes
4	GSM (Data) + Bluetooth(data)	-	Yes	Yes
5	WCDMA+ WLAN 2.4GHz (data)	Yes	Yes	Yes
6	WCDMA+ Bluetooth(data)	-	Yes	Yes
7	LTE + WLAN 2.4GHz (data)	Yes	Yes	Yes
8	LTE + Bluetooth(data)	--	Yes	Yes

NOTE:

1. WIFI and BT share the same antenna, and cannot transmit simultaneously.
2. Simultaneous with every transmitter must be the same test position.
3. KDB 447498 D01, BT SAR is excluded as below table.
4. KDB 447498 D01, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user; which is 0mm for head SAR and 10mm for body-worn SAR.
5. According to KDB 447498 D01 4.3.1, Standalone SAR test exclusion is as follow:  
For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:  

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR<sup>30</sup>, where
  - f(GHz) is the RF channel transmit frequency in GHz
  - Power and distance are rounded to the nearest mW and mm before calculation<sup>31</sup>
  - The result is rounded to one decimal place for comparison
  - The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below
The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.
6. If the test separation distance is  $< 5$ mm, 5mm is used for excluded SAR calculation.
7. According to KDB 447498 D01 4.3.2, simultaneous transmission SAR test exclusion is as follow:
  - (1) Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.
  - (2) Any transmitters and antennas should be considered when calculating simultaneous mode.
  - (3) For mobile phone and PC, it's the sum of all transmitters and antennas at the same mode with same position in each applicable exposure condition
  - (4) When the standalone SAR test exclusion of section 4.3.2 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to det
$$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$$
for test separation distances  $\leq 50$  mm;  
where  $x = 7.5$  for 1-g SAR, and  $x = 18.75$  for 10-g SAR.

8. When the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion. The ratio is determined by  $(SAR1 + SAR2)1.5/R_i$ , rounded to two decimal digits, and must be  $\leq 0.04$  for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

Estimated SAR		Max Power including Tune-up Tolerance		Separation Distance (mm)	Estimated SAR (W/kg)
		dBm	mW		
<b>BT</b>	Head	2	1.585	0	0.067
	Body	2	1.585	10	0.033

**Sum of the SAR for GSM 850 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		GSM 850	Wi-Fi DTS Band	Bluetooth		
Head (voice)	Left Touch	0.315	0.183		0.498	No
	Left Tilt	0.239	0.164		0.403	No
	Right Touch	0.342	0.363		0.705	No
	Right Tilt	0.204	0.247		0.451	No
Body-worn (voice)	Rear	0.518	0.134		0.652	No
		0.518		0.033	0.551	No
	Front	0.354	0.094		0.448	No
		0.354		0.033	0.387	No
Body-worn (Data)	Rear	0.707		0.033	0.740	No
		0.707	0.134		0.841	No
	Front	0.543		0.033	0.576	No
		0.543	0.094		0.637	No
Body-worn (Hotspot)	Edge 1	/	0.049		0.049	No
	Edge 2	0.428	/		0.428	No
	Edge 3	0.258	/		0.258	No
	Edge 4	0.723	0.138		0.861	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.428		0.033	0.461	No
	Edge 3	0.258		0.033	0.291	No
	Edge 4	0.723		0.033	0.756	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is “The SAR to Peak Location Separation Ratio “

**Sum of the SAR for GSM 1900 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		GSM 1900	Wi-Fi DTS Band	Bluetooth		
Head (voice)	Left Touch	0.205	0.183		0.388	No
	Left Tilt	0.100	0.164		0.264	No
	Right Touch	0.188	0.363		0.551	No
	Right Tilt	0.134	0.247		0.381	No
Body-worn (voice)	Rear	0.483	0.134		0.617	No
		0.483		0.033	0.516	No
	Front	0.385	0.094		0.479	No
		0.385		0.033	0.418	No
Body-worn (Data)	Rear	0.708		0.033	0.741	No
		0.708	0.134		0.842	No
	Front	0.589		0.033	0.622	No
		0.589	0.094		0.683	No
Body-worn (Hotspot)	Edge 1	/	0.049		0.049	No
	Edge 2	0.211	/		0.211	No
	Edge 3	1.075	/		1.075	No
	Edge 4	0.133	0.138		0.271	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.211		0.033	0.244	No
	Edge 3	1.075		0.033	1.108	No
	Edge 4	0.133		0.033	0.166	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for WCDMA Band II & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		WCDMA Band II	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.179	0.183		0.362	No
	Left Tilt	0.096	0.164		0.260	No
	Right Touch	0.172	0.363		0.535	No
	Right Tilt	0.136	0.247		0.383	No
Hotspot	Rear	0.644	0.134		0.778	No
	Front	0.355	0.094		0.449	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.124	/		0.124	No
	Edge 3	1.100	/		1.100	No
	Edge 4	0.104	0.138		0.242	No
	Rear	0.644		0.033	0.677	No
	Front	0.355		0.033	0.388	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.124		0.033	0.157	No
	Edge 3	1.100		0.033	1.133	No
	Edge 4	0.104		0.033	0.137	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for WCDMA Band IV & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		WCDMA Band IV	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.235	0.183		0.418	No
	Left Tilt	0.123	0.164		0.287	No
	Right Touch	0.292	0.363		0.655	No
	Right Tilt	0.183	0.247		0.430	No
Hotspot	Rear	0.673	0.134		0.807	No
	Front	0.550	0.094		0.644	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.198	/		0.198	No
	Edge 3	1.070	/		1.070	No
	Edge 4	0.120	0.138		0.258	No
	Rear	0.673		0.033	0.706	No
	Front	0.550		0.033	0.583	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.198		0.033	0.231	No
	Edge 3	1.070		0.033	1.103	No
	Edge 4	0.120		0.033	0.153	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for WCDMA Band V & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		WCDMA Band V	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.259	0.183		0.442	No
	Left Tilt	0.220	0.164		0.384	No
	Right Touch	0.280	0.363		0.643	No
	Right Tilt	0.186	0.247		0.433	No
Hotspot	Rear	0.435	0.134		0.569	No
	Front	0.290	0.094		0.384	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.240	/		0.240	No
	Edge 3	0.149	/		0.149	No
	Edge 4	0.407	0.138		0.545	No
	Rear	0.435		0.033	0.468	No
	Front	0.290		0.033	0.323	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.240		0.033	0.273	No
	Edge 3	0.149		0.033	0.182	No
	Edge 4	0.407		0.033	0.440	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for LTE Band 2 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 2	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.247	0.183		0.430	No
	Left Tilt	0.106	0.164		0.270	No
	Right Touch	0.232	0.363		0.595	No
	Right Tilt	0.143	0.247		0.390	No
Body-worn	Rear	0.834	0.134		0.968	No
	Front	0.438	0.094		0.532	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.217	/		0.217	No
	Edge 3	1.166	/		1.166	No
	Edge 4	0.143	0.138		0.281	No
	Rear	0.834		0.033	0.867	No
	Front	0.438		0.033	0.471	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.217		0.033	0.250	No
	Edge 3	1.166		0.033	<b>1.199</b>	No
	Edge 4	0.143		0.033	0.176	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for LTE Band 4 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 4	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.342	0.183		0.525	No
	Left Tilt	0.157	0.164		0.321	No
	Right Touch	0.306	0.363		0.669	No
	Right Tilt	0.210	0.247		0.457	No
Body-worn	Rear	0.703	0.134		0.837	No
	Front	0.672	0.094		0.766	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.266	/		0.266	No
	Edge 3	1.126	/		1.126	No
	Edge 4	0.150	0.138		0.288	No
	Rear	0.703		0.033	0.736	No
	Front	0.672		0.033	0.705	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.266		0.033	0.299	No
	Edge 3	1.126		0.033	1.159	No
	Edge 4	0.150		0.033	0.183	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for LTE Band 5 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 5	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.408	0.183		0.591	No
	Left Tilt	0.291	0.164		0.455	No
	Right Touch	0.448	0.363		0.811	No
	Right Tilt	0.306	0.247		0.553	No
Body-worn	Rear	0.679	0.134		0.813	No
	Front	0.461	0.094		0.555	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.338	/		0.338	No
	Edge 3	0.023	/		0.023	No
	Edge 4	0.607	0.138		0.745	No
	Rear	0.679		0.033	0.712	No
	Front	0.461		0.033	0.494	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.338		0.033	0.371	No
	Edge 3	0.023		0.033	0.056	No
	Edge 4	0.607		0.033	0.640	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for LTE Band 7 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 7	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.263	0.183		0.446	No
	Left Tilt	0.238	0.164		0.402	No
	Right Touch	0.445	0.363		0.808	No
	Right Tilt	0.130	0.247		0.377	No
Body-worn	Rear	0.413	0.134		0.547	No
	Front	0.257	0.094		0.351	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.176	/		0.176	No
	Edge 3	0.536	/		0.536	No
	Edge 4	0.081	0.138		0.219	No
	Rear	0.413		0.033	0.446	No
	Front	0.257		0.033	0.290	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.176		0.033	0.209	No
	Edge 3	0.536		0.033	0.569	No
	Edge 4	0.081		0.033	0.114	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for LTE Band 12 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 12	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.194	0.183		0.377	No
	Left Tilt	0.157	0.164		0.321	No
	Right Touch	0.219	0.363		0.582	No
	Right Tilt	0.160	0.247		0.407	No
Body-worn	Rear	0.405	0.134		0.539	No
	Front	0.219	0.094		0.313	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.177	/		0.177	No
	Edge 3	0.094	/		0.094	No
	Edge 4	0.213	0.138		0.351	No
	Rear	0.405		0.033	0.438	No
	Front	0.219		0.033	0.252	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.177		0.033	0.210	No
	Edge 3	0.094		0.033	0.127	No
	Edge 4	0.213		0.033	0.246	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

**Sum of the SAR for LTE Band 17 & Wi-Fi & BT:**

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 17	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.233	0.183		0.416	No
	Left Tilt	0.164	0.164		0.328	No
	Right Touch	0.261	0.363		0.624	No
	Right Tilt	0.174	0.247		0.421	No
Body-worn	Rear	0.568	0.134		0.702	No
	Front	0.308	0.094		0.402	No
	Edge 1	/	0.049		0.049	No
	Edge 2	0.233	/		0.233	No
	Edge 3	0.091	/		0.091	No
	Edge 4	0.300	0.138		0.438	No
	Rear	0.568		0.033	0.601	No
	Front	0.308		0.033	0.341	No
	Edge 1	/		0.033	0.033	No
	Edge 2	0.233		0.033	0.266	No
	Edge 3	0.091		0.033	0.124	No
	Edge 4	0.300		0.033	0.333	No

**Note:**

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

## APPENDIX A. SAR SYSTEM CHECK DATA

Test Laboratory: AGC Lab

Date: Aug. 08.2020

System Check Head 750MHz

DUT: Dipole 750 MHz Type: SID 750

Communication System: CW; Communication System Band: D750 (750.0 MHz); Duty Cycle: 1:1;  
Frequency: 750 MHz; Medium parameters used:  $f = 750\text{MHz}$ ;  $\sigma = 0.88\text{ mho/m}$ ;  $\epsilon_r = 40.52$ ;  $\rho = 1000\text{ kg/m}^3$  ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature ( $^{\circ}\text{C}$ ): 21.4, Liquid temperature ( $^{\circ}\text{C}$ ): 21.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.53, 10.53, 10.53); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 750MHz/Area Scan (9x14x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (measured) = 0.647 W/kg


**Configuration/System Check Head 750MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  
 $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 22.091 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.958 W/kg

**SAR(1 g) = 0.542 W/kg; SAR(10 g) = 0.357 W/kg**

Maximum value of SAR (measured) = 0.651 W/kg



**Test Laboratory: AGC Lab**  
**System Check Head 835 MHz**  
**DUT: Dipole 835 MHz Type: SID 835**

**Date: Aug. 01.2020**

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;  
Frequency: 835 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma=0.91$  mho/m;  $\epsilon_r =42.52$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature (°C):20.3, Liquid temperature (°C): 20.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 835MHz/Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.826 W/kg


**Configuration/System Check Head 835MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.987 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.999 W/kg

**SAR(1 g) = 0.615 W/kg; SAR(10 g) = 0.401 W/kg**

Maximum value of SAR (measured) = 0.829 W/kg



**Test Laboratory: AGC Lab**  
**System Check Head 835 MHz**  
**DUT: Dipole 835 MHz Type: SID 835**

**Date: Aug. 04.2020**

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;  
Frequency: 835 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma=0.92$  mho/m;  $\epsilon_r =40.21$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature (°C): 21.2, Liquid temperature (°C): 21.0

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 835MHz/Area Scan (9x14x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.729 W/kg


**Configuration/System Check Head 835MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.918 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.977 W/kg

**SAR(1 g) = 0.616 W/kg; SAR(10 g) = 0.384 W/kg**

Maximum value of SAR (measured) = 0.740 W/kg



**Test Laboratory: AGC Lab**  
**System Check Head 1750MHz**  
**DUT: Dipole 1800 MHz; Type: SID 1800**

**Date: Aug. 06.2020**

Communication System: CW; Communication System Band: D1700 (1750.0 MHz); Duty Cycle: 1:1;  
Frequency: 1750 MHz; Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 38.75$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.61, 8.61, 8.61); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 1750MHz/Area Scan (7x10x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 2.82 W/kg


**Configuration/System Check Head 1750MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 46.367 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 4.36 W/kg

**SAR(1 g) = 2.34 W/kg; SAR(10 g) = 1.26 W/kg**

Maximum value of SAR (measured) = 2.84 W/kg



**Test Laboratory: AGC Lab**  
**System Check Head 1900MHz**  
**DUT: Dipole 1900 MHz; Type: SID 1900**

**Date: Aug. 03.2020**

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1;  
Frequency: 1900 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma=1.38$  mho/m;  $\epsilon_r =38.12$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 1900MHz/Area Scan (7x10x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 2.85 W/kg


**Configuration/System Check Head 1900MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 43.315 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 4.64 W/kg

**SAR(1 g) = 2.52 W/kg; SAR(10 g) = 1.31 W/kg**

Maximum value of SAR (measured) = 3.13 W/kg



**Test Laboratory: AGC Lab**  
**System Check Head 1900MHz**  
**DUT: Dipole 1900 MHz; Type: SID 1900**

**Date: Aug. 10.2020**

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1;  
Frequency: 1900 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma=1.37$  mho/m;  $\epsilon_r =38.63$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature (°C): 21.5, Liquid temperature (°C): 21.3

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 1900MHz/Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 3.06 W/kg


**Configuration/System Check Head 1900MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 47.684 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 4.45 W/kg

**SAR(1 g) = 2.49 W/kg; SAR(10 g) = 1.28 W/kg**

Maximum value of SAR (measured) = 3.02 W/kg



**Test Laboratory: AGC Lab**  
**System Check Head 2450 MHz**  
**DUT: Dipole 2450 MHz Type: D2450V2**

**Date: Aug. 07.2020**

Communication System CW; Communication System Band: D2450 (2450.0 MHz); Duty Cycle: 1:1;  
Frequency: 2450 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.81$  mho/m;  $\epsilon_r = 38.63$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature (°C): 21.1, Liquid temperature (°C): 20.8

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(7.66, 7.66, 7.66); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 2450Hz/Area Scan (5x8x1):**Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 5.23 W/kg


**Configuration/System Check Head 2450Hz/Zoom Scan (5x5x5)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 45.392 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 7.08 W/kg

**SAR(1 g) = 3.37 W/kg; SAR(10 g) = 1.51 W/kg**

Maximum value of SAR (measured) = 5.13 W/kg



**Test Laboratory: AGC Lab**  
**System Check Head 2600 MHz**  
**DUT: Dipole 2600 MHz; Type: SID 2600**

**Date: Aug. 05.2020**

Communication System: CW; Communication System Band: D2600 (2600.0 MHz); Duty Cycle: 1:1;  
Frequency: 2600 MHz; Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.86$  mho/m;  $\epsilon_r = 39.74$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=18dBm  
Ambient temperature (°C): 21.1, Liquid temperature (°C): 20.8

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(7.45, 7.45, 7.45); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check Head 2600Hz/Area Scan (5x8x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 5.07 W/kg


**Configuration/System Check Head 2600Hz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 53.604 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 7.17 W/kg

**SAR(1 g) = 3.4 W/kg; SAR(10 g) = 1.55 W/kg**

Maximum value of SAR (measured) = 5.21 W/kg



## APPENDIX B. SAR MEASUREMENT DATA

Test Laboratory: AGC Lab

Date: Aug. 01.2020

GSM 850 Mid-Touch-Right <SIM 1>

DUT: Smart Phone; Type: NOTE 7


Communication System: Generic GSM; Communication System Band: GSM 850; Duty Cycle: 1:8.3;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.92$  mho/m;  $\epsilon_r = 41.15$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 20.3, Liquid temperature (°C): 20.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**RIGHT HEAD/R-C/Area Scan (7x12x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.366 W/kg

**RIGHT HEAD/R-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.514 V/m; Power Drift = 0.07 dB  
Peak SAR (extrapolated) = 0.407 W/kg  
**SAR(1 g) = 0.334 W/kg; SAR(10 g) = 0.255 W/kg**  
Maximum value of SAR (measured) = 0.365 W/kg



Test Laboratory: AGC Lab  
GSM 850 Mid- Body- Back(MS)<SIM 1>  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 01.2020


Communication System: Generic GSM; Communication System Band: GSM 850; Duty Cycle: 1:8.3;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma=0.92$  mho/m;  $\epsilon_r = 41.15$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.3, Liquid temperature (°C): 20.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002Shenzhen Huaforui Technology Co., Ltd.;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/BACK/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.544 W/kg

**BODY/BACK/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 24.646 V/m; Power Drift = 0.10 dB  
Peak SAR (extrapolated) = 0.644 W/kg  
**SAR(1 g) = 0.506 W/kg; SAR(10 g) = 0.385 W/kg**  
Maximum value of SAR (measured) = 0.555 W/kg



Test Laboratory: AGC Lab  
GPRS 850 Mid- Edge 4(3up) < SIM 1>  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 01.2020

Communication System: GPRS-3 Slot; Communication System Band: GSM 850; Duty Cycle: 1:2.7;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.92$  mho/m;  $\epsilon_r = 41.15$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.3, Liquid temperature (°C): 20.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002Shenzhen Huafurui Technology Co., Ltd.;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/4/Area Scan (6x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.795 W/kg


**BODY/4/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm


Reference Value = 28.358 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.979 W/kg

**SAR(1 g) = 0.702 W/kg; SAR(10 g) = 0.488 W/kg**

Maximum value of SAR (measured) = 0.794 W/kg





Test Laboratory: AGC Lab  
PCS 1900 Mid-Touch-Left <SIM 1>  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 03.2020


Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 40.06$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**LEFT HEAD/L-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.207 W/kg

**LEFT HEAD/L-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 5.275 V/m; Power Drift = 0.13 dB  
Peak SAR (extrapolated) = 0.292 W/kg  
**SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.126 W/kg**  
Maximum value of SAR (measured) = 0.223 W/kg



Test Laboratory: AGC Lab  
PCS 1900 Mid-Body- Back(MS)<SIM 1>  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 03.2020


Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 40.06$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/BACK/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.523 W/kg

**BODY/BACK/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 13.059 V/m; Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 0.807 W/kg  
**SAR(1 g) = 0.455 W/kg; SAR(10 g) = 0.277 W/kg**  
Maximum value of SAR (measured) = 0.554 W/kg



Test Laboratory: AGC Lab  
GPRS 1900 High-Edge 3 (2up) < SIM 1>  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 03.2020

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900; Duty Cycle: 1:4.2;  
Frequency: 1909.8 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 36.89$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/3-H/Area Scan (6x10x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 1.33 W/kg


**BODY/3-H/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 26.339 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 1.98 W/kg

**SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.551 W/kg**

Maximum value of SAR (measured) = 1.36 W/kg





**Test Laboratory: AGC Lab**  
**WCDMA Band II Mid-Touch-Left**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 03.2020**


Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 40.06$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**LEFT HEAD/L-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.202 W/kg

**LEFT HEAD/L-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 4.815 V/m; Power Drift = 0.01 dB  
Peak SAR (extrapolated) = 0.275 W/kg  
**SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.115 W/kg**  
Maximum value of SAR (measured) = 0.204 W/kg



Test Laboratory: AGC Lab  
WCDMA Band II High-Edge 3  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 03.2020


Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1;  
Frequency: 1907.6 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma=1.41$ mho/m;  $\epsilon_r =37.62$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4


DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY 3/3-H/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.856 W/kg

**BODY 3/3-H/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 27.279 V/m; Power Drift = 0.09 dB  
Peak SAR (extrapolated) = 1.83 W/kg  
**SAR(1 g) = 0.974 W/kg; SAR(10 g) = 0.501 W/kg**  
Maximum value of SAR (measured) = 1.22 W/kg





**Test Laboratory: AGC Lab**  
**WCDMA Band IV Mid-Touch-Right**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 06.2020**

Communication System: UMTS; Communication System Band: BAND IV UTRA/FDD; Duty Cycle: 1:1;  
Frequency: 1732.5 MHz; Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 40.22$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.61, 8.61, 8.61); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**RIGHT HEAD/R-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.383 W/kg


**RIGHT HEAD/R-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 7.569 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.410 W/kg

**SAR(1 g) = 0.287 W/kg; SAR(10 g) = 0.190 W/kg**

Maximum value of SAR (measured) = 0.331 W/kg



Test Laboratory: AGC Lab  
WCDMA Band IV Mid- Edge 3  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 06.2020

Communication System: UMTS; Communication System Band: BAND IV UTRA/FDD; Duty Cycle: 1:1;  
Frequency: 1732.5 MHz; Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 40.22$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.61, 8.61, 8.61); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/3/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 1.23 W/kg


**BODY/3/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 21.114 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.96 W/kg

**SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.534 W/kg**

Maximum value of SAR (measured) = 1.33 W/kg





**Test Laboratory: AGC Lab**  
**WCDMA Band V Mid- Touch-Right**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 01.2020**

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD; Duty Cycle: 1:1;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.92$  mho/m;  $\epsilon_r = 41.15$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 20.3, Liquid temperature (°C): 20.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**RIGHT HEAD/R-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.292 W/kg


**RIGHT HEAD/R-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 7.298 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.324 W/kg

**SAR(1 g) = 0.265 W/kg; SAR(10 g) = 0.203 W/kg**

Maximum value of SAR (measured) = 0.290 W/kg



Test Laboratory: AGC Lab  
WCDMA Band V Mid-Body-Towards Grounds  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 01.2020


Communication System: UMTS; Communication System Band: BAND V UTRA/FDD;Duty Cycle:1:1;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz; $\sigma=0.92$  mho/m;  $\epsilon_r = 41.15$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.3, Liquid temperature (°C): 20.1


DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/BACK/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.433 W/kg

**BODY/BACK/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 22.324 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 0.529 W/kg  
**SAR(1 g) = 0.412 W/kg; SAR(10 g) = 0.311 W/kg**  
Maximum value of SAR (measured) = 0.456 W/kg





Test Laboratory: AGC Lab  
LTE Band 2 Mid-Touch-Left <SIM 1>  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 10.2020

Communication System: LTE; Communication System Band: LTE Band 2; Duty Cycle: 1:1;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 40.92$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21.5, Liquid temperature (°C): 21.3

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**LEFT HEAD/L-C/Area Scan (7x12x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.259 W/kg


**LEFT HEAD/L-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.410 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.351 W/kg

**SAR(1 g) = 0.229 W/kg; SAR(10 g) = 0.148 W/kg**

Maximum value of SAR (measured) = 0.262 W/kg



**Test Laboratory: AGC Lab**  
**LTE Band 2 Mid- Edge 3 (1 RB#0)**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 10.2020**


Communication System: LTE; Communication System Band: LTE Band 2; Duty Cycle: 1:1;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 40.92$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.5, Liquid temperature (°C): 21.3


DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/3/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 1.07 W/kg

**BODY/3/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 26.427 V/m; Power Drift = -0.16 dB  
Peak SAR (extrapolated) = 1.63 W/kg  
**SAR(1 g) = 0.888 W/kg; SAR(10 g) = 0.462 W/kg**  
Maximum value of SAR (measured) = 1.06 W/kg





**Test Laboratory: AGC Lab**  
**LTE Band 4 Mid-Touch-Left (1 RB#0)**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 06.2020**


Communication System: LTE; Communication System Band: LTE Band 4; Duty Cycle:1:1;  
Frequency:1732.5 MHz; Medium parameters used:  $f=1750$  MHz;  $\sigma=1.37$  mho/m;  $\epsilon_r=40.22$ ;  $\rho=1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.61, 8.61, 8.61); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**LEFT HEAD/L-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.329 W/kg

**LEFT HEAD/L-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 6.759 V/m; Power Drift = 0.16 dB  
Peak SAR (extrapolated) = 0.458 W/kg  
**SAR(1 g) = 0.303 W/kg; SAR(10 g) = 0.197 W/kg**  
Maximum value of SAR (measured) = 0.350 W/kg



**Test Laboratory: AGC Lab**  
**LTE Band 4 High- Edge 3 (1 RB#0)**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 06.2020**

Communication System: LTE; Communication System Band: LTE Band 4; Duty Cycle:1:1;  
Frequency:1745 MHz; Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 39.51$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.61, 8.61, 8.61); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/3-H/Area Scan (6x10x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 1.166 W/kg


**BODY/3-H/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 24.152 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.79 W/kg

**SAR(1 g) = 0.961 W/kg; SAR(10 g) = 0.494 W/kg**

Maximum value of SAR (measured) = 1.23 W/kg





Test Laboratory: AGC Lab  
LTE Band 5 Mid-Touch- Right (1 RB#0)  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 04.2020

Communication System: LTE; Communication System Band: LTE Band 5; Duty Cycle:1:1;  
Frequency: 836.5 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma=0.94$  mho/m;  $\epsilon_r =39.05$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.2, Liquid temperature (°C): 21.0

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**RIGHT HEAD/R-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.326 W/kg


**RIGHT HEAD/R-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 6.839 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.409 W/kg

**SAR(1 g) = 0.335 W/kg; SAR(10 g) = 0.257 W/kg**

Maximum value of SAR (measured) = 0.366 W/kg



Test Laboratory: AGC Lab  
LTE Band 5 Mid-Body-Back (1 RB#0)  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 04.2020

Communication System: LTE; Communication System Band: LTE Band 5; Duty Cycle:1:1;  
Frequency:836.5 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma=0.94$ mho/m;  $\epsilon_r =39.05$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.2, Liquid temperature (°C): 21.0

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.13, 10.13, 10.13); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/BACK/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.541 W/kg


**BODY/BACK/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm


Reference Value = 25.044 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.641 W/kg

**SAR(1 g) = 0.508 W/kg; SAR(10 g) = 0.387 W/kg**

Maximum value of SAR (measured) = 0.556 W/kg





**Test Laboratory: AGC Lab**  
**LTE Band 7 Mid-Touch- Right (1RB#0)**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 05.2020**

Communication System: LTE; Communication System Band: LTE Band 7; Duty Cycle:1:1;  
Frequency: 2535MHz; Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.83$  mho/m;  $\epsilon_r = 40.65$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.1, Liquid temperature (°C): 20.8

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(7.45, 7.45, 7.45); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**RIGHT HEAD/R-C/Area Scan (10x17x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (measured) = 0.453 W/kg


**RIGHT HEAD/R-C/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.643 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.699 W/kg

**SAR(1 g) = 0.381 W/kg; SAR(10 g) = 0.214 W/kg**

Maximum value of SAR (measured) = 0.470 W/kg



Test Laboratory: AGC Lab  
LTE Band 7 Mid-Edge3 (1RB#0)  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 05.2020

Communication System: LTE; Communication System Band: LTE Band 7; Duty Cycle:1:1;  
Frequency: 2535MHz; Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.83$  mho/m;  $\epsilon_r = 40.65$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.1, Liquid temperature (°C): 20.8

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(7.45, 7.45, 7.45); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/3/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.446 W/kg


**BODY/3/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 14.834 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.05 W/kg

**SAR(1 g) = 0.459 W/kg; SAR(10 g) = 0.218 W/kg**

Maximum value of SAR (measured) = 0.590 W/kg





**Test Laboratory: AGC Lab**  
**LTE Band 12 Mid-Touch- Right (1 RB#0)**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 08.2020**

Communication System: LTE; Communication System Band: LTE Band 12; Duty Cycle:1:1;  
Frequency: 707.5 MHz; Medium parameters used:  $f = 750$  MHz;  $\sigma=0.85$  mho/m;  $\epsilon_r =44.62$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.53, 10.53, 10.53); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**RIGHT HEAD/R-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.209 W/kg

**RIGHT HEAD/R-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 5.644 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.232 W/kg

**SAR(1 g) = 0.194 W/kg; SAR(10 g) = 0.154 W/kg**

Maximum value of SAR (measured) = 0.209 W/kg



**Test Laboratory: AGC Lab**  
**LTE Band 12 Mid-Body-Back (1 RB#0)**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 08.2020**

Communication System: LTE; Communication System Band: LTE Band 12; Duty Cycle:1:1;  
Frequency: 707.5 MHz; Medium parameters used:  $f = 750$  MHz;  $\sigma=0.85$  mho/m;  $\epsilon_r =44.62$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.53, 10.53, 10.53); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/BACK/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.383 W/kg


**BODY/BACK/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 21.337 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.463 W/kg

**SAR(1 g) = 0.359 W/kg; SAR(10 g) = 0.274 W/kg**

Maximum value of SAR (measured) = 0.394 W/kg





Test Laboratory: AGC Lab  
LTE Band 17 Mid-Touch- Right (1 RB#0)  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 08.2020


Communication System: LTE; Communication System Band: LTE Band 17; Duty Cycle:1:1;  
Frequency: 710 MHz; Medium parameters used:  $f = 750$  MHz;  $\sigma=0.87$  mho/m;  $\epsilon_r =42.37$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.1

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.53, 10.53, 10.53); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**RIGHT HEAD/R-C/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.236 W/kg

**RIGHT HEAD/R-C/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 5.681 V/m; Power Drift = 0.15 dB  
Peak SAR (extrapolated) = 0.266 W/kg  
**SAR(1 g) = 0.219 W/kg; SAR(10 g) = 0.173 W/kg**  
Maximum value of SAR (measured) = 0.237 W/kg



Test Laboratory: AGC Lab  
LTE Band 17 Mid-Body-Back (1 RB#0)  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 08.2020


Communication System: LTE; Communication System Band: LTE Band 17; Duty Cycle:1:1;  
Frequency: 710 MHz; Medium parameters used:  $f = 750$  MHz;  $\sigma=0.87$  mho/m;  $\epsilon_r =42.37$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.1


DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(10.53, 10.53, 10.53); Calibrated: Jul. 29,2020;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/BACK/Area Scan (7x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.517 W/kg

**BODY/BACK/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 23.167 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 0.600 W/kg  
**SAR(1 g) = 0.476 W/kg; SAR(10 g) = 0.367 W/kg**  
Maximum value of SAR (measured) = 0.522 W/kg





## WIFI MODE

Test Laboratory: AGC Lab

Date: Aug. 07.2020

802.11b Mid- Touch-Right

DUT: Smart Phone; Type: NOTE 7

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 39.87$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.1, Liquid temperature (°C): 20.8

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(7.66, 7.66, 7.66); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**RIGHT HEAD/R-C/Area Scan (10x17x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm

Maximum value of SAR (measured) = 0.426 W/kg


**RIGHT HEAD/R-C/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 7.174 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.639 W/kg

**SAR(1 g) = 0.347 W/kg; SAR(10 g) = 0.194 W/kg**

Maximum value of SAR (measured) = 0.432 W/kg





Test Laboratory: AGC Lab  
802.11b Mid- Edge 4 (DTS)  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 07.2020

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 39.87$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.1, Liquid temperature (°C): 20.8

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(7.66, 7.66, 7.66); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/4/Area Scan (6x12x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.147 W/kg

**BODY/4/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm  
Reference Value = 8.037 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.273 W/kg

**SAR(1 g) = 0.132 W/kg; SAR(10 g) = 0.077 W/kg**

Maximum value of SAR (measured) = 0.162 W/kg



### Repeated SAR

Test Laboratory: AGC Lab  
GPRS 1900 High-Edge 3 (2up) < SIM 1 >  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 03.2020

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900; Duty Cycle: 1:4.2;  
Frequency: 1909.8 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 36.89$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4

#### DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/3-H-REPEATED/Area Scan (6x10x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 0.940 W/kg

**BODY/3-H-REPEATED/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 27.544 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 2.05 W/kg

**SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.554 W/kg**

Maximum value of SAR (measured) = 1.35 W/kg



**Test Laboratory: AGC Lab**  
**WCDMA Band II High-Edge 3**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 03.2020**

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1;  
Frequency: 1907.6 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma=1.41$  mho/m;  $\epsilon_r =37.62$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):20.7, Liquid temperature (°C): 20.4

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/3-H-REPEATED/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.871 W/kg

**BODY/3-H-REPEATED/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 27.172 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.83 W/kg

**SAR(1 g) = 0.969 W/kg; SAR(10 g) = 0.499 W/kg**

Maximum value of SAR (measured) = 1.23 W/kg



**Test Laboratory: AGC Lab**  
**WCDMA Band IV Mid- Edge 3**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 06.2020**

Communication System: UMTS; Communication System Band: BAND IV UTRA/FDD; Duty Cycle: 1:1;  
Frequency: 1732.5 MHz; Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 40.22$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.61, 8.61, 8.61); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/3-REPEATED/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 1.19 W/kg


**BODY/3-REPEATED/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.035 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.87 W/kg

**SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.529 W/kg**

Maximum value of SAR (measured) = 1.325 W/kg



Test Laboratory: AGC Lab  
LTE Band 2 Mid- Edge 3 (1 RB#0)  
DUT: Smart Phone; Type: NOTE 7

Date: Aug. 10.2020


Communication System: LTE; Communication System Band: LTE Band 2; Duty Cycle: 1:1;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 40.92$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.5, Liquid temperature (°C): 21.3

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.32, 8.32, 8.32); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/3-REPEATED/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 1.049 W/kg

**BODY/3-REPEATED/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 22.972 V/m; Power Drift = 0.03 dB  
Peak SAR (extrapolated) = 1.63 W/kg  
**SAR(1 g) = 0.864 W/kg; SAR(10 g) = 0.445 W/kg**  
Maximum value of SAR (measured) = 1.10 W/kg



**Test Laboratory: AGC Lab**  
**LTE Band 4 High- Edge 3 (1 RB#0)**  
**DUT: Smart Phone; Type: NOTE 7**

**Date: Aug. 06.2020**


Communication System: LTE; Communication System Band: LTE Band 4; Duty Cycle:1:1;  
Frequency:1745 MHz; Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 39.51$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

- Probe: EX3DV4 – SN:3953; ConvF(8.61, 8.61, 8.61); Calibrated: Jul. 29,2020;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 SN1398; Calibrated: Apr. 23,2020
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


**BODY/3-H-REPEATED/Area Scan (6x10x1):** Measurement grid:  $dx=15$ mm,  $dy=15$ mm  
Maximum value of SAR (measured) = 1.185 W/kg

**BODY/3-H-REPEATED/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm  
Reference Value = 24.166 V/m; Power Drift = -0.11 dB  
Peak SAR (extrapolated) = 1.79 W/kg  
**SAR(1 g) = 0.958 W/kg; SAR(10 g) = 0.493 W/kg**  
Maximum value of SAR (measured) = 1.23 W/kg




## APPENDIX C. TEST SETUP PHOTOGRAPHS


LEFT- CHEEK TOUCH




LEFT-TILT 15°



RIGHT- CHEEK TOUCH



RIGHT-TILT 15°



Body Back 10mm



Body Front 10mm



Edge 1(Top) 10mm




Edge 2(Right) 10mm



Edge 3(Bottom) 10mm





Edge 4(Left) 10mm



### DEPTH OF THE LIQUID IN THE PHANTOM—ZOOM IN

Note : The position used in the measurement were according to IEEE 1528-2013





## **APPENDIX D. CALIBRATION DATA**

Refer to Attached files.