

---

# Safety Test Report

---

Report No.: AGC00552200705ES01

**PRODUCT DESIGNATION** : Smartphone  
**BRAND NAME** : CUBOT  
**MODEL NAME** : J8  
**APPLICANT** : Shenzhen Huafurui Technology Co., Ltd.  
**DATE OF ISSUE** : Sept. 03, 2020  
**STANDARD(S)** : EN 62368-1:2014+A11:2017  
**REPORT VERSION** : V1.0

**Attestation of Global Compliance(Shenzhen) Co., Ltd.**



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>




| <b>TEST REPORT</b><br><b>EN 62368-1</b><br><b>Audio/video, information and communication technology equipment</b><br><b>Part 1: Safety requirements</b> |   |
|---|---|
| Report No. ....   | AGC00552200705ES01  |
| Tested by (+ signature) .....   | Bengi Liu <span style="float: right;"><i>Bengi Liu</i></span>   |
| Reviewed by (+ signature) .....   | Byron Wang <span style="float: right;"><i>Byron Wang</i></span>   |
| Approved by (+ signature) .....   | Matte He<br>(Authorized Officer) <span style="float: right;"><i>Matte He</i></span>   |
| Date of issue .....   | Sept. 03, 2020  |
| Contents.....   | Total 62 pages  |
| <b>Testing laboratory</b>   |   |
| Name.....   | Attestation of Global Compliance (Shenzhen) Co., Ltd.   |
| Address.....  | 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao 'an District, Shenzhen, Guangdong, China   |
| Testing location.....   | Same as above.  |
| <b>Applicant</b>  |   |
| Name.....   | Shenzhen Huafurui Technology Co., Ltd.  |
| Address.....  | Unit 1401 &1402, 14/F, Jinqi zhigu mansion (No. 4 building of Chongwen Garden), Crossing of the Liuxian street and Tangling road, Taoyuan street, Nanshan district, Shenzhen,P.R. China |
| <b>Manufacturer</b>   |   |
| Name.....   | Shenzhen Huafurui Technology Co., Ltd.  |
| Address.....  | Unit 1401 &1402, 14/F, Jinqi zhigu mansion (No. 4 building of Chongwen Garden), Crossing of the Liuxian street and Tangling road, Taoyuan street, Nanshan district, Shenzhen,P.R. China |
| <b>Factory</b>  |   |
| Name.....   | Shenzhen Huafurui Technology Co., Ltd.  |
| Address.....  | Unit 1401 &1402, 14/F, Jinqi zhigu mansion (No. 4 building of Chongwen Garden), Crossing of the Liuxian street and Tangling road, Taoyuan street, Nanshan district, Shenzhen,P.R. China |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|   |   |
|---|---|
| <b>Test specification</b>                 |   |
| Standard .....                            | EN 62368-1:2014+A11:2017  |
| Test procedure .....                      | Type test   |
| Procedure deviation.....                  | N/A   |
| Non-standard test method.....             | N/A   |
| <b>Test Report Form/blank test report</b> |   |
| Test Report Form No.....                  | AGC62368A2  |
| TRF originator.....                       | AGC   |
| Master TRF .....                          | 2018-09   |
| <b>Test item</b>                          |   |
| Product designation.....                  | Smartphone  |
| Brand name .....                          | CUBOT   |
| Test model .....                          | J8  |
| Series model .....                        | N/A   |
| Rating(s).....                            | 5V= 1A  |
| <b>Test item particulars</b>              |   |
| Classification of use by .....            | <input checked="" type="checkbox"/> Ordinary person<br><input type="checkbox"/> Instructed person<br><input type="checkbox"/> Skilled person<br><input checked="" type="checkbox"/> Children likely to be present   |
| Supply Connection .....                   | <input type="checkbox"/> AC Mains <input type="checkbox"/> DC Mains<br><input checked="" type="checkbox"/> External Circuit - not Mains connected<br>- <input checked="" type="checkbox"/> ES1 <input type="checkbox"/> ES2 <input type="checkbox"/> ES3  |
| Supply % Tolerance .....                  | <input type="checkbox"/> +10%/-10%<br><input type="checkbox"/> +20%/-15%<br><input type="checkbox"/> + ____% / - ____%<br><input checked="" type="checkbox"/> None  |
| Supply Connection – Type .....            | <input type="checkbox"/> pluggable equipment type A -<br><input type="checkbox"/> non-detachable supply cord<br><input type="checkbox"/> appliance coupler<br><input type="checkbox"/> direct plug-in<br><input type="checkbox"/> mating connector<br><input type="checkbox"/> pluggable equipment type B -<br><input type="checkbox"/> non-detachable supply cord<br><input type="checkbox"/> appliance coupler<br><input type="checkbox"/> permanent connection<br><input type="checkbox"/> mating connector <input checked="" type="checkbox"/> other: not mains connected |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|  |   |
|--|---|
| Considered current rating of protective device as part of building or equipment installation ..... | N/A<br>Installation location: <input type="checkbox"/> building; <input type="checkbox"/> equipment   |
| Equipment mobility .....   | <input type="checkbox"/> movable <input checked="" type="checkbox"/> hand-held <input checked="" type="checkbox"/> transportable<br><input type="checkbox"/> stationary <input type="checkbox"/> for building-in <input type="checkbox"/> direct plug-in <input type="checkbox"/> rack-mounting <input type="checkbox"/> wall-mounted |
| Over voltage category (OVC) .....  | <input type="checkbox"/> OVC I <input type="checkbox"/> OVC II <input type="checkbox"/> OVC III<br><input type="checkbox"/> OVC IV <input checked="" type="checkbox"/> other: <u>not mains connected</u>  |
| Class of equipment .....   | <input type="checkbox"/> Class I <input type="checkbox"/> Class II <input checked="" type="checkbox"/> Class III  |
| Access location .....  | <input type="checkbox"/> restricted access location <input checked="" type="checkbox"/> N/A   |
| Pollution degree (PD) .....  | <input type="checkbox"/> PD 1 <input checked="" type="checkbox"/> PD 2 <input type="checkbox"/> PD 3  |
| Manufacturer's specified maximum operating ambient.....  | 40°C  |
| IP protection class .....  | <input checked="" type="checkbox"/> IPX0 <input type="checkbox"/> IP__  |
| Power Systems .....  | <input type="checkbox"/> TN <input type="checkbox"/> TT <input type="checkbox"/> IT - ____ V <sub>L-L</sub>   |
| Altitude during operation (m) .....  | <input checked="" type="checkbox"/> 2000 m or less <input type="checkbox"/> ____ m  |
| Altitude of test laboratory (m) .....  | <input checked="" type="checkbox"/> 2000 m or less <input type="checkbox"/> ____ m  |
| Mass of equipment (kg) .....   | <input checked="" type="checkbox"/> <1 kg   |

**Test case verdicts**

Test case does not apply to the test object ..... : N (/A)  
 Test item does meet the requirement ..... : P(ass)  
 Test item does not meet the requirement..... : F(ail)

**Testing**

Date of receipt of test item..... : Jul. 29, 2020  
 Date of performance of test..... : Aug. 05, 2020 - Aug. 28, 2020

**Attachments**

Attachment A ..... : Photos of product

**General remarks**

This report shall not be reproduced except in full without the written approval of the testing laboratory.  
 The test results presented in this report relate only to the item tested.  
 "(See remark #)" refers to a remark appended to the report.  
 "(See appended table)" refers to a table appended to the report.  
 Throughout this report a comma is used as the decimal separator.

Report Revise Record:

| Report Version | Revise Time | Issued Date    | Valid Version | Notes           |
|----------------|-------------|----------------|---------------|-----------------|
| V1.0           | /           | Sept. 03, 2020 | Valid         | Initial release |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



**General product information**

The product supplied by Li-ion battery, and charge from PC approved Travel Charger with Micro-B connection and is considered moveable and Class III (supplied by SELV). The HW Version and SW Version of EUT as following:

HW Version : TE641\_MAIN\_PCB\_V1.0  
SW Version : CUBOT\_J8\_A043C\_V03\_20200817


Instructions and equipment marking related to safety is applied in the language that is acceptable in the country in which the equipment is to be sold.

The product was submitted and tested for use at the manufacturer’s recommended ambient temperature (Tma) of 40°C.

**Summary of testing**

The test item passed.

**Copy of marking plates**



**Remark:**

- 1) The CE marking and WEEE symbol (if any) should be at least 5mm and 7mm respectively in height.
- 2) The markings and instructions are the minimum requirements required by safety standard. For final production samples, the additional markings which do not give rise to misunderstanding may be added.
- 3) As declared by the applicant, the importer (and manufacturer, if it is different)’s name, registered trade name or mark and the postal address will be marked on the products before being place on the market.
- 4) Marking on the packaging or in a document accompanying the electrical equipment is only acceptable if it is not possible to place such markings on the product.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| <b>ENERGY SOURCE IDENTIFICATION AND CLASSIFICATION TABLE:</b>   |                                   |
|---|-----------------------------------|
| (Note 1: Identify the following six (6) energy source forms based on the origin of the energy.)<br>(Note 2: The identified classification e.g., ES2, TS1, should be with respect to its ability to cause pain or injury on the body or its ability to ignite a combustible material. Any energy source can be declared Class 3 as a worse case classification e.g. PS3, ES3.) |                                   |
| <b>Electrically-caused injury (Clause 5):</b><br>(Note: Identify type of source, list sub-assembly or circuit designation and corresponding energy source classification)<br>Example: +5 V dc input   |                                   |
|   | ES1                               |
| Source of electrical energy   | Corresponding classification (ES) |
| Internal circuitry  | ES1                               |
| <b>Electrically-caused fire (Clause 6):</b><br>(Note: List sub-assembly or circuit designation and corresponding energy source classification)<br>Example: Battery pack (maximum 85 watts):   |                                   |
|   | PS2                               |
| Source of power or PIS  | Corresponding classification (PS) |
| Adapter output  | PS1                               |
| Internal circuitry  | PS2                               |
| Battery cell  | PS2                               |
| Battery pack  | PS2                               |
| <b>Injury caused by hazardous substances (Clause 7)</b><br>(Note: Specify hazardous chemicals, whether produces ozone or other chemical construction not addressed as part of the component evaluation.)<br>Example: Liquid in filled component   |                                   |
|   | Glycol                            |
| Source of hazardous substances  | Corresponding chemical            |
| Battery pack  | Complied with annex M             |
| <b>Mechanically-caused injury (Clause 8)</b><br>(Note: List moving part(s), fan, special installations, etc. & corresponding MS classification based on Table 35.)<br>Example: Wall mount unit  |                                   |
|   | MS2                               |
| Source of kinetic/mechanical energy   | Corresponding classification (MS) |
| Edges and corners   | MS1                               |
| Equipment mass  | MS1                               |
| <b>Thermal burn injury (Clause 9)</b><br>(Note: Identify the surface or support, and corresponding energy source classification based on type of part, location, operating temperature and contact time in Table 38.)<br>Example: Hand-held scanner – thermoplastic enclosure   |                                   |
|   | TS1                               |
| Source of thermal energy  | Corresponding classification (TS) |
| All accessible parts  | TS1                               |
| <b>Radiation (Clause 10)</b><br>(Note: List the types of radiation present in the product and the corresponding energy source classification.)<br>Example: DVD – Class 1 Laser Product  |                                   |
|   | RS1                               |
| Type of radiation   | Corresponding classification (RS) |
| LED   | RS1                               |
| Acoustic  | RS2                               |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| OVERVIEW OF EMPLOYED SAFEGUARDS                         |   |  |  |                           |
|---|---|--|--|---------------------------|
| Clause  | Possible Hazard   |  |  |                           |
| 5.1   | Electrically-caused injury  |  |  |                           |
| Body Part<br>(e.g. Ordinary)                            | Energy Source<br>(ES3: Primary Filter circuit)  | Safeguards   |  |                           |
|   |   | Basic  | Supplementary  | Reinforced<br>(Enclosure) |
| Ordinary person   | ES1: All circuits   | N/A  | N/A  | N/A                       |
| 6.1   | Electrically-caused fire  |  |  |                           |
| Material part<br>(e.g. mouse enclosure)                 | Energy Source<br>(PS2: 100 Watt circuit)  | Safeguards   |  |                           |
|   |   | Basic  | Supplementary  | Reinforced                |
| All internal combustible material and plastic enclosure | PS1: Adapter output   | N/A  | N/A  | N/A                       |
| All internal combustible material and plastic enclosure | PS2: Adapter output<br>PS2: Internal circuits<br>PS2: Battery cell<br>PS2: Battery pack | 1. No ignition occurred.<br>2. No parts exceeding 90% of its spontaneous ignition temperature. | 1. PCB is complied with V-0 material;<br>2. all other components: at least V-2 except for mounted on min. V-1 material or small parts of combustible material<br>3.V-0 enclosure provided. | N/A                       |
| 7.1   | Injury caused by hazardous substances   |  |  |                           |
| Body Part<br>(e.g., skilled)                            | Energy Source<br>(hazardous material)   | Safeguards   |  |                           |
|   |   | Basic  | Supplementary  | Reinforced                |
| Ordinary person   | Complied with annex M   | N/A  | N/A  | N/A                       |
| 8.1   | Mechanically-caused injury  |  |  |                           |
| Body Part<br>(e.g. Ordinary)                            | Energy Source<br>(MS3:High Pressure Lamp)   | Safeguards   |  |                           |
|   |   | Basic  | Supplementary  | Reinforced<br>(Enclosure) |
| Ordinary person   | MS1: Edges and corners  | N/A  | N/A  | N/A                       |
| Ordinary person   | MS1: Equipment mass   | N/A  | N/A  | N/A                       |
| 9.1   | Thermal Burn  |  |  |                           |
| Body Part<br>(e.g., Ordinary)                           | Energy Source<br>(TS2)  | Safeguards   |  |                           |
|   |   | Basic  | Supplementary  | Reinforced                |
| Ordinary person   | TS1: Accessible plastic enclosure   | N/A  | N/A  | N/A                       |
| 10.1  | Radiation   |  |  |                           |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| Body Part<br>(e.g., Ordinary)   | Energy Source<br>(Output from audio port) | Safeguards  |               |            |
|---|---|---|---------------|------------|
|   |   | Basic   | Supplementary | Reinforced |
| Ordinary person   | RS1: LED                                  | N/A   | N/A           | N/A        |
| Ordinary person   | RS2: Acoustic                             | Instructional safeguard: 1.<br><br>Symbol :<br>2. "high sound pressure" or equivalent wording; 3. "hearing damage risk" or equivalent wording; 4. "do not listen at high volume levels for long periods" or equivalent wording | N/A           | N/A        |
| <b>Supplementary Information:</b><br>(1) See attached energy source diagram for additional details.<br>(2) "N" – Normal Condition; "A" – Abnormal Condition; "S" Single Fault |   |   |               |            |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |  |         |
|------------|---|--|---------|
| Clause     | Requirement – Test  | Result - Remark  | Verdict |
| <b>4</b>   | <b>GENERAL REQUIREMENTS</b>                                     |  | P       |
| 4.1.1      | Acceptance of materials, components and subassemblies           | See appended table 4.1.2   | P       |
| 4.1.2      | Use of components   | Components which are certified to IEC and/or national standards are used correctly within their ratings. Components not covered by IEC standards are tested under the conditions present in the equipment. | P       |
| 4.1.3      | Equipment design and construction                               | No accessible part which could cause injury  | P       |
| 4.1.15     | Markings and instructions.....:                                 | (See Annex F)  | P       |
| 4.4.4      | Safeguard robustness  | See below  | P       |
| 4.4.4.2    | Steady force tests.....:  | (See Annex T.4)  | P       |
| 4.4.4.3    | Drop tests.....:  | (See Annex T.7)  | P       |
| 4.4.4.4    | Impact tests.....:  |  | N       |
| 4.4.4.5    | Internal accessible safeguard enclosure and barrier tests.....: |  | N       |
| 4.4.4.6    | Glass Impact tests.....:  |  | N       |
| 4.4.4.7    | Thermoplastic material tests.....:                              | (See Annex T.8)  | P       |
| 4.4.4.8    | Air comprising a safeguard.....:                                |  | N       |
| 4.4.4.9    | Accessibility and safeguard effectiveness                       | No damaged   | P       |
| 4.5        | Explosion   | No explosion occurs during normal/abnormal operation and single fault conditions   | P       |
| 4.6        | Fixing of conductors  |  | N       |
| 4.6.1      | Fix conductors not to defeat a safeguard                        |  | N       |
| 4.6.2      | 10 N force test applied to.....:                                |  | N       |
| 4.7        | Equipment for direct insertion into mains socket - outlets      |  | N       |
| 4.7.2      | Mains plug part complies with the relevant standard.....:       |  | N       |
| 4.7.3      | Torque (Nm).....:   |  | N       |
| 4.8        | Products containing coin/button cell batteries                  | No coin/button batteries used.   | N       |
| 4.8.2      | Instructional safeguard   |  | N       |


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |                 |         |
|------------|--|-----------------|---------|
| Clause     | Requirement – Test   | Result - Remark | Verdict |
| 4.8.3      | Battery Compartment Construction                                       |                 | N       |
|            | Means to reduce the possibility of children removing the battery ..... |                 | —       |
| 4.8.4      | Battery Compartment Mechanical Tests .....                             |                 | N       |
| 4.8.5      | Battery Accessibility  |                 | N       |
| 4.9        | Likelihood of fire or shock due to entry of conductive object .....    | (See Annex P)   | P       |

|          |   |  |   |
|----------|---|--|---|
| <b>5</b> | <b>ELECTRICALLY-CAUSED INJURY</b>   |  | P |
| 5.2.1    | Electrical energy source classifications .....  | (See appended table 5.2)               | P |
| 5.2.2    | ES1, ES2 and ES3 limits   | ES1                                    | P |
| 5.2.2.2  | Steady-state voltage and current.....   | See appended table 5.2)                | P |
| 5.2.2.3  | Capacitance limits .....  |  | N |
| 5.2.2.4  | Single pulse limits.....  | No such single pulses with the EUT     | N |
| 5.2.2.5  | Limits for repetitive pulses.....   | No such repetitive pulses with the EUT | N |
| 5.2.2.6  | Ringing signals .....   | No such ringing signals with the EUT   | N |
| 5.2.2.7  | Audio signals .....   |  | N |
| 5.3      | Protection against electrical energy sources  | ES1                                    | N |
| 5.3.1    | General Requirements for accessible parts to ordinary, instructed and skilled persons | See above.                             | N |
| 5.3.2.1  | Accessibility to electrical energy sources and safeguards                             |  | N |
| 5.3.2.2  | Contact requirements  |  | N |
|          | a) Test with test probe from Annex V .....  |  | N |
|          | b) Electric strength test potential (V).....  |  | N |
|          | c) Air gap (mm) .....   |  | N |
| 5.3.2.4  | Terminals for connecting stripped wire  |  | N |
| 5.4      | Insulation materials and requirements   |  | N |
| 5.4.1.2  | Properties of insulating material   |  | N |
| 5.4.1.3  | Humidity conditioning.....  |  | N |
| 5.4.1.4  | Maximum operating temperature for insulating materials .....                          |  | N |
| 5.4.1.5  | Pollution degree.....   |  | — |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result - Remark | Verdict |
| 5.4.1.5.2  | Test for pollution degree 1 environment and for an insulating compound      |                 | N       |
| 5.4.1.5.3  | Thermal cycling   |                 | N       |
| 5.4.1.6    | Insulation in transformers with varying dimensions                          |                 | N       |
| 5.4.1.7    | Insulation in circuits generating starting pulses                           |                 | N       |
| 5.4.1.8    | Determination of working voltage  |                 | N       |
| 5.4.1.9    | Insulating surfaces   |                 | N       |
| 5.4.1.10   | Thermoplastic parts on which conductive metallic parts are directly mounted |                 | N       |
| 5.4.1.10.2 | Vicat softening temperature .....   |                 | N       |
| 5.4.1.10.3 | Ball pressure .....   |                 | N       |
| 5.4.2      | Clearances  |                 | N       |
| 5.4.2.2    | Determining clearance using peak working voltage                            |                 | N       |
| 5.4.2.3    | Determining clearance using required withstand voltage .....                |                 | N       |
|            | a) a.c. mains transient voltage .....                                       |                 | —       |
|            | b) d.c. mains transient voltage .....                                       |                 | —       |
|            | c) external circuit transient voltage .....                                 |                 | —       |
|            | d) transient voltage determined by measurement...                           |                 | —       |
| 5.4.2.4    | Determining the adequacy of a clearance using an electric strength test     |                 | N       |
| 5.4.2.5    | Multiplication factors for clearances and test voltages .....               |                 | N       |
| 5.4.3      | Creepage distances .....  |                 | N       |
| 5.4.3.1    | General   |                 | N       |
| 5.4.3.3    | Material Group .....  |                 | —       |
| 5.4.4      | Solid insulation  |                 | N       |
| 5.4.4.2    | Minimum distance through insulation .....                                   |                 | N       |
| 5.4.4.3    | Insulation compound forming solid insulation                                |                 | N       |
| 5.4.4.4    | Solid insulation in semiconductor devices                                   |                 | N       |
| 5.4.4.5    | Cemented joints   |                 | N       |
| 5.4.4.6    | Thin sheet material   |                 | N       |
| 5.4.4.6.1  | General requirements  |                 | N       |
| 5.4.4.6.2  | Separable thin sheet material   |                 | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |                 |         |
|------------|--|-----------------|---------|
| Clause     | Requirement – Test   | Result - Remark | Verdict |
|            | Number of layers (pcs) .....   |                 | N       |
| 5.4.4.6.3  | Non-separable thin sheet material                                    |                 | N       |
| 5.4.4.6.4  | Standard test procedure for non-separable thin sheet material .....  |                 | N       |
| 5.4.4.6.5  | Mandrel test   |                 | N       |
| 5.4.4.7    | Solid insulation in wound components                                 |                 | N       |
| 5.4.4.9    | Solid insulation at frequencies >30 kHz .....                        |                 | N       |
| 5.4.5      | Antenna terminal insulation  |                 | N       |
| 5.4.5.1    | General  |                 | N       |
| 5.4.5.2    | Voltage surge test   |                 | N       |
|            | Insulation resistance (MΩ).....                                      |                 | —       |
| 5.4.6      | Insulation of internal wire as part of supplementary safeguard ..... |                 | N       |
| 5.4.7      | Tests for semiconductor components and for cemented joints           |                 | N       |
| 5.4.8      | Humidity conditioning  |                 | N       |
|            | Relative humidity (%).....   |                 | —       |
|            | Temperature (°C) .....   |                 | —       |
|            | Duration (h) .....   |                 | —       |
| 5.4.9      | Electric strength test .....   |                 | N       |
| 5.4.9.1    | Test procedure for a solid insulation type test                      |                 | N       |
| 5.4.9.2    | Test procedure for routine tests                                     |                 | N       |
| 5.4.10     | Protection against transient voltages between external circuit       |                 | N       |
| 5.4.10.1   | Parts and circuits separated from external circuits                  |                 | N       |
| 5.4.10.2   | Test methods   |                 | N       |
| 5.4.10.2.1 | General  |                 | N       |
| 5.4.10.2.2 | Impulse test .....   |                 | N       |
| 5.4.10.2.3 | Steady-state test.....   |                 | N       |
| 5.4.11     | Insulation between external circuits and earthed circuitry.....      |                 | N       |
| 5.4.11.1   | Exceptions to separation between external circuits and earth         |                 | N       |
| 5.4.11.2   | Requirements   |                 | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result - Remark | Verdict |
|            | Rated operating voltage $U_{op}$ (V).....:  |                 | —       |
|            | Nominal voltage $U_{peak}$ (V).....:  |                 | —       |
|            | Max increase due to variation $U_{sp}$ .....  |                 | —       |
|            | Max increase due to ageing $\Delta U_{sa}$ .....                                      |                 | —       |
|            | $U_{op} = U_{peak} + \Delta U_{sp} + \Delta U_{sa}$ .....                             |                 | —       |
| 5.5        | Components as safeguards  |                 | N       |
| 5.5.1      | General   |                 | N       |
| 5.5.2      | Capacitors and RC units   |                 | N       |
| 5.5.2.1    | General requirement   |                 | N       |
| 5.5.2.2    | Safeguards against capacitor discharge after disconnection of a connector.....:       |                 | N       |
| 5.5.3      | Transformers  |                 | N       |
| 5.5.4      | Optocouplers  |                 | N       |
| 5.5.5      | Relays  |                 | N       |
| 5.5.6      | Resistors   |                 | N       |
| 5.5.7      | SPD's   |                 | N       |
| 5.5.7.1    | Use of an SPD connected to reliable earthing  |                 | N       |
| 5.5.7.2    | Use of an SPD between mains and protective earth                                      |                 | N       |
| 5.5.8      | Insulation between the mains and external circuit consisting of a coaxial cable.....: |                 | N       |
| 5.6        | Protective conductor  |                 | N       |
| 5.6.2      | Requirement for protective conductors   |                 | N       |
| 5.6.2.1    | General requirements  |                 | N       |
| 5.6.2.2    | Colour of insulation  |                 | N       |
| 5.6.3      | Requirement for protective earthing conductors  |                 | N       |
|            | Protective earthing conductor size ( $mm^2$ ) .....                                   |                 | —       |
| 5.6.4      | Requirement for protective bonding conductors   |                 | N       |
| 5.6.4.1    | Protective bonding conductors   |                 | N       |
|            | Protective bonding conductor size ( $mm^2$ ). .....                                   |                 | —       |
|            | Protective current rating (A) .....   |                 | —       |
| 5.6.4.3    | Current limiting and overcurrent protective devices                                   |                 | N       |
| 5.6.5      | Terminals for protective conductors   |                 | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |                 |         |
|------------|--|-----------------|---------|
| Clause     | Requirement – Test   | Result - Remark | Verdict |
| 5.6.5.1    | Requirement  |                 | N       |
|            | Conductor size (mm <sup>2</sup> ), nominal thread diameter (mm)..... :                         |                 | N       |
| 5.6.5.2    | Corrosion  |                 | N       |
| 5.6.6      | Resistance of the protective system  |                 | N       |
| 5.6.6.1    | Requirements   |                 | N       |
| 5.6.6.2    | Test Method Resistance (Ω)..... :  |                 | N       |
| 5.6.7      | Reliable earthing  |                 | N       |
| 5.7        | Prospective touch voltage, touch current and protective conductor current                      |                 | N       |
| 5.7.2      | Measuring devices and networks   |                 | N       |
| 5.7.2.1    | Measurement of touch current..... :  |                 | N       |
| 5.7.2.2    | Measurement of prospective touch voltage   |                 | N       |
| 5.7.3      | Equipment set-up, supply connections and earth connections                                     |                 | N       |
|            | System of interconnected equipment (separate connections/single connection) ..... :            |                 | —       |
|            | Multiple connections to mains (one connection at a time/simultaneous connections) ..... :      |                 | —       |
| 5.7.4      | Earthed conductive accessible parts..... :   |                 | N       |
| 5.7.5      | Protective conductor current   |                 | N       |
|            | Supply Voltage (V)..... :  |                 | —       |
|            | Measured current (mA)..... :   |                 | —       |
|            | Instructional Safeguard..... :   |                 | N       |
| 5.7.6      | Prospective touch voltage and touch current due to external circuits                           |                 | N       |
| 5.7.6.1    | Touch current from coaxial cables  |                 | N       |
| 5.7.6.2    | Prospective touch voltage and touch current from external circuits                             |                 | N       |
| 5.7.7      | Summation of touch currents from external circuits   |                 | N       |
|            | a) Equipment with earthed external circuits Measured current (mA)..... :                       |                 | N       |
|            | b) Equipment whose external circuits are not referenced to earth. Measured current (mA)..... : |                 | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |   |         |
|------------|--|---|---------|
| Clause     | Requirement – Test   | Result - Remark   | Verdict |
| <b>6</b>   | <b>ELECTRICALLY- CAUSED FIRE</b>   |   | P       |
| 6.2.2      | Power source circuit classifications   | PS (power source) classification determined by measuring the maximum power in Figures 34 and 35 for load and power source circuits. | P       |
| 6.2.2.1    | General  | See the following details.  | P       |
| 6.2.2.2    | Power measurement for worst-case load fault.....:  | (See appended table 6.2.2)  | P       |
| 6.2.2.3    | Power measurement for worst-case power source fault .....  | (See appended table 6.2.2)  | P       |
| 6.2.2.4    | PS1 .....  | (See appended table 6.2.2)  | P       |
| 6.2.2.5    | PS2 .....  | (See appended table 6.2.2)  | P       |
| 6.2.2.6    | PS3 .....  |   | N       |
| 6.2.3      | Classification of potential ignition sources   |   | P       |
| 6.2.3.1    | Arcing PIS .....   |   | N       |
| 6.2.3.2    | Resistive PIS .....  | (See appended table 6.3.2)  | P       |
| 6.3        | Safeguards against fire under normal operating and abnormal operating conditions   |   | P       |
| 6.3.1 (a)  | No ignition and attainable temperature value less than 90 % defined by ISO 871 or less than 300 °C for unknown materials.....: | (See appended table 5.4.1.5, 6.3.2, 9.0, B.2.6)   | P       |
| 6.3.1 (b)  | Combustible materials outside fire enclosure   | No such materials used.   | N       |
| 6.4        | Safeguards against fire under single fault conditions  |   | P       |
| 6.4.1      | Safeguard Method   | The method of control of fire spread be used.   | P       |
| 6.4.2      | Reduction of the likelihood of ignition under single fault conditions in PS1 circuits  |   | N       |
| 6.4.3      | Reduction of the likelihood of ignition under single fault conditions in PS2 and PS3 circuits                                  |   | N       |
| 6.4.3.1    | General  |   | N       |
| 6.4.3.2    | Supplementary Safeguards   | By equipment plastic fire enclosure.  | N       |
|            | Special conditions if conductors on printed boards are opened or peeled  | No such case happened.  | N       |
| 6.4.3.3    | Single Fault Conditions .....  |   | N       |
|            | Special conditions for temperature limited by fuse   |   | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |   |         |
|------------|---|---|---------|
| Clause     | Requirement – Test  | Result - Remark   | Verdict |
| 6.4.4      | Control of fire spread in PS1 circuits  |   | P       |
| 6.4.5      | Control of fire spread in PS2 circuits  |   | P       |
| 6.4.5.2    | Supplementary safeguards .....  | (See appended tables 4.1.2 and Annex G)<br>PCB rated V-0;<br>Plastic enclosure rated V-0. | P       |
| 6.4.6      | Control of fire spread in PS3 circuit   |   | N       |
| 6.4.7      | Separation of combustible materials from a PIS  | Clause 6.4.8 applied.   | N       |
| 6.4.7.1    | General .....   |   | N       |
| 6.4.7.2    | Separation by distance  |   | N       |
| 6.4.7.3    | Separation by a fire barrier  |   | N       |
| 6.4.8      | Fire enclosures and fire barriers   | Equipment enclosure was evaluated as a fire enclosure.                                    | P       |
| 6.4.8.1    | Fire enclosure and fire barrier material properties   | See the following details.  | P       |
| 6.4.8.2.1  | Requirements for a fire barrier   | No such construction.   | N       |
| 6.4.8.2.2  | Requirements for a fire enclosure   | Equipment fire enclosure was made of min. V-0 material.                                   | P       |
| 6.4.8.3    | Constructional requirements for a fire enclosure and a fire barrier                               | See the following details.  | P       |
| 6.4.8.3.1  | Fire enclosure and fire barrier openings  |   | P       |
| 6.4.8.3.2  | Fire barrier dimensions   | No barrier used.  | N       |
| 6.4.8.3.3  | Top Openings in Fire Enclosure: dimensions (mm) :   |   | N       |
|            | Needle Flame test   |   | N       |
| 6.4.8.3.4  | Bottom Openings in Fire Enclosure, condition met a), b) and/or c) dimensions (mm) .....           |   | N       |
|            | Flammability tests for the bottom of a fire enclosure .....                                       |   | N       |
| 6.4.8.3.5  | Integrity of the fire enclosure, condition met: a), b) or c).....                                 |   | N       |
| 6.4.8.4    | Separation of PIS from fire enclosure and fire barrier distance (mm) or flammability rating ..... | Equipment fire enclosure was made of min. V-0 material.                                   | P       |
| 6.5        | Internal and external wiring  |   | P       |
| 6.5.1      | Requirements  |   | P       |
| 6.5.2      | Cross-sectional area (mm <sup>2</sup> ) .....   | See appended tables 4.1.2   | —       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |   |         |
|------------|---|---|---------|
| Clause     | Requirement – Test  | Result - Remark                             | Verdict |
| 6.5.3      | Requirements for interconnection to building wiring.....:         | No such interconnection to building wiring. | N       |
| 6.6        | Safeguards against fire due to connection to additional equipment |   | N       |
|            | External port limited to PS2 or complies with Clause Q.1          |   | N       |

| 7   | <b>INJURY CAUSED BY HAZARDOUS SUBSTANCES</b>     |  | P |
|-----|--|--|---|
| 7.2 | Reduction of exposure to hazardous substances    | No hazardous chemicals within the equipment.                             | N |
| 7.3 | Ozone exposure                                   | No ozone production within the equipment.                                | N |
| 7.4 | Use of personal safeguards (PPE)                 | No such consideration.   | N |
|     | Personal safeguards and instructions .....       | See above.   | — |
| 7.5 | Use of instructional safeguards and instructions | No chemical-caused injuries, the instruction safeguard was not required. | N |
|     | Instructional safeguard (ISO 7010)..... :        | (See Annex F)  | — |
| 7.6 | Batteries.....:                                  | Complied with Annex M  | P |

| 8     | <b>MECHANICALLY-CAUSED INJURY</b>   |  | P |
|-------|---|--|---|
| 8.1   | General   | See the following details.   | P |
| 8.2   | Mechanical energy source classifications                                    | Edges and corners, classified as MS1<br>Equipment mass < 7 kg, classified as MS1<br>Internal motor classified as MS1 | P |
| 8.3   | Safeguards against mechanical energy sources                                | MS1  | P |
| 8.4   | Safeguards against parts with sharp edges and corners                       | Accessible edges and corners of the equipment are rounded and are classified as MS1.                                 | P |
| 8.4.1 | Safeguards  | See above.   | N |
| 8.5   | Safeguards against moving parts   |  | N |
| 8.5.1 | MS2 or MS3 part required to be accessible for the function of the equipment | See above.   | N |
| 8.5.2 | Instructional Safeguard .....   | See above.   | — |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result - Remark | Verdict |
| 8.5.4      | Special categories of equipment comprising moving parts             |                 | N       |
| 8.5.4.1    | Large data storage equipment  |                 | N       |
| 8.5.4.2    | Equipment having electromechanical device for destruction of media  |                 | N       |
| 8.5.4.2.1  | Safeguards and Safety Interlocks..... :                             |                 | N       |
| 8.5.4.2.2  | Instructional safeguards against moving parts                       |                 | N       |
|            | Instructional Safeguard ..... :                                     |                 | —       |
| 8.5.4.2.3  | Disconnection from the supply                                       |                 | N       |
| 8.5.4.2.4  | Probe type and force (N)..... :                                     |                 | N       |
| 8.5.5      | High Pressure Lamps   |                 | N       |
| 8.5.5.1    | Energy Source Classification  |                 | N       |
| 8.5.5.2    | High Pressure Lamp Explosion Test ..... :                           |                 | N       |
| 8.6        | Stability   | < 7 kg          | N       |
| 8.6.1      | Product classification  |                 | N       |
|            | Instructional Safeguard ..... :                                     |                 | —       |
| 8.6.2      | Static stability  |                 | N       |
| 8.6.2.2    | Static stability test   |                 | N       |
|            | Applied Force ..... :   |                 | —       |
| 8.6.2.3    | Downward Force Test   |                 | N       |
| 8.6.3      | Relocation stability test   |                 | N       |
|            | Unit configuration during 10° tilt ..... :                          |                 | —       |
| 8.6.4      | Glass slide test  |                 | N       |
| 8.6.5      | Horizontal force test (Applied Force) ..... :                       |                 | N       |
|            | Position of feet or movable parts ..... :                           |                 | —       |
| 8.7        | Equipment mounted to wall or ceiling                                |                 | N       |
| 8.7.1      | Mounting Means (Length of screws (mm) and mounting surface) ..... : |                 | N       |
| 8.7.2      | Direction and applied force ..... :                                 |                 | N       |
| 8.8        | Handles strength  |                 | N       |
| 8.8.1      | Classification  |                 | N       |
| 8.8.2      | Applied Force ..... :   |                 | N       |
| 8.9        | Wheels or casters attachment requirements                           |                 | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |   |         |
|------------|--|---|---------|
| Clause     | Requirement – Test                                 | Result - Remark                         | Verdict |
| 8.9.1      | Classification                                     |   | N       |
| 8.9.2      | Applied force..... :                               |   | —       |
| 8.10       | Carts, stands and similar carriers                 | No such device provided within the EUT. | N       |
| 8.10.1     | General  |   | N       |
| 8.10.2     | Marking and instructions                           |   | N       |
|            | Instructional Safeguard ..... :                    |   | —       |
| 8.10.3     | Cart, stand or carrier loading test and compliance |   | N       |
|            | Applied force..... :                               |   | —       |
| 8.10.4     | Cart, stand or carrier impact test                 |   | N       |
| 8.10.5     | Mechanical stability                               |   | N       |
|            | Applied horizontal force (N)..... :                |   | —       |
| 8.10.6     | Thermoplastic temperature stability (°C) ..... :   |   | N       |
| 8.11       | Mounting means for rack mounted equipment          |   | N       |
| 8.11.1     | General  |   | N       |
| 8.11.2     | Product Classification                             |   | N       |
| 8.11.3     | Mechanical strength test, variable N ..... :       |   | N       |
| 8.11.4     | Mechanical strength test 250N, including end stops |   | N       |
| 8.12       | Telescoping or rod antennas ..... :                | No such device provided within the EUT. | N       |
|            | Button/Ball diameter (mm) ..... :                  | See above.                              | —       |

|          |  |  |          |
|----------|--|--|----------|
| <b>9</b> | <b>THERMAL BURN INJURY</b>               |  | <b>P</b> |
| 9.2      | Thermal energy source classifications    | All accessible surfaces are classified as TS1, see appended table 5.4.1.4, 6.3.2, 9.0, B.2.6 | P        |
| 9.3      | Safeguard against thermal energy sources | See above.   | P        |
| 9.4      | Requirements for safeguards              |  | P        |
| 9.4.1    | Equipment safeguard                      | Enclosure temperatures do not exceed TS1 limits.   | P        |
| 9.4.2    | Instructional safeguard ..... :          |  | N        |

|           |  |  |          |
|-----------|--|--|----------|
| <b>10</b> | <b>RADIATION</b>                       |  | <b>P</b> |
| 10.2      | Radiation energy source classification |  | P        |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |   |         |
|------------|--|---|---------|
| Clause     | Requirement – Test   | Result - Remark                                   | Verdict |
| 10.2.1     | General classification   | RS1: LED flashlight<br>RS2: Acoustic output       | P       |
| 10.3       | Protection against laser radiation                               |   | P       |
|            | Laser radiation that exists equipment:                           |   | —       |
|            | Normal, abnormal, single-fault.....:                             |   | N       |
|            | Instructional safeguard .....                                    |   | —       |
|            | Tool .....   |   | —       |
| 10.4       | Protection against visible, infrared, and UV radiation           |   | P       |
| 10.4.1     | General  |   | P       |
| 10.4.1.a)  | RS3 for Ordinary and instructed persons .....                    |   | N       |
| 10.4.1.b)  | RS3 accessible to a skilled person.....:                         |   | N       |
|            | Personal safeguard (PPE) instructional safeguard .....           |   | —       |
| 10.4.1.c)  | Equipment visible, IR, UV does not exceed RS1 .:                 |   | P       |
| 10.4.1.d)  | Normal, abnormal, single-fault conditions .....                  |   | P       |
| 10.4.1.e)  | Enclosure material employed as safeguard is opaque .....         |   | N       |
| 10.4.1.f)  | UV attenuation .....   |   | N       |
| 10.4.1.g)  | Materials resistant to degradation UV .....                      |   | N       |
| 10.4.1.h)  | Enclosure containment of optical radiation.....:                 |   | N       |
| 10.4.1.i)  | Exempt Group under normal operating conditions.....:             | Exempt Group                                      | P       |
| 10.4.2     | Instructional safeguard .....                                    |   | N       |
| 10.5       | Protection against x-radiation                                   | No such x-radiation generated from the equipment. | N       |
| 10.5.1     | X- radiation energy source that exists equipment:                |   | N       |
|            | Normal, abnormal, single fault conditions                        |   | N       |
|            | Equipment safeguards.....:                                       |   | N       |
|            | Instructional safeguard for skilled person.....:                 |   | N       |
| 10.5.3     | Most unfavourable supply voltage to give maximum radiation ..... |   | —       |
|            | Abnormal and single-fault condition .....                        |   | N       |
|            | Maximum radiation (pA/kg).....:                                  |   | N       |
| 10.6       | Protection against acoustic energy sources                       | RS2   | P       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |  |         |
|------------|--|--|---------|
| Clause     | Requirement – Test   | Result - Remark  | Verdict |
| 10.6.1     | General  |  | P       |
| 10.6.2     | Classification   |  | P       |
|            | Acoustic output, dB(A) .....                                     |  | P       |
|            | Output voltage, unweighted r.m.s.....                            | Pre-set condition:<br>Music mode: Left: 5mV, Right: 5mV, limit $\leq 27\text{mV}$ ;<br>FM mode: Left: 6mV, Right: 7mV, limit $\leq 27\text{mV}$ ;<br>Warning information condition:<br>Music mode: Left: 11mV, Right: 11mV, limit $\leq 27\text{mV}$ ;<br>FM mode: Left: 14mV, Right: 14mV, limit $\leq 27\text{mV}$ ;<br>Maximum Volume condition:<br>Music mode: Left: 61mV, Right: 61mV, limit $\leq 150\text{mV}$ ;<br>FM mode: Left: 78mV, Right: 78mV, limit $\leq 150\text{mV}$ ; | N       |
| 10.6.4     | Protection of persons  |  | P       |
|            | Instructional safeguards .....                                   | <br>1. Symbol .....<br>2. "high sound pressure" or equivalent wording; 3. "hearing damage risk" or equivalent wording;<br>4. "do not listen at high volume levels for long periods" or equivalent wording   | P       |
|            | Equipment safeguard prevent ordinary person to RS2 .....         | Automatically return to RS1 level when the power is switched off.  | —       |
|            | Means to actively inform user of increase sound pressure .....   | Warning: hearing damage risk or equivalent wording   | —       |
|            | Equipment safeguard prevent ordinary person to RS2 .....         | After 20h the acoustic output not exceeding RS1  | —       |
| 10.6.5     | Requirements for listening devices (headphones, earphones, etc.) |  | N       |
| 10.6.5.1   | Corded passive listening devices with analog input               |  | N       |


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result - Remark | Verdict |
|            | Input voltage with 94 dB(A) $L_{Aeq}$ acoustic pressure output..... : |                 | —       |
| 10.6.5.2   | Corded listening devices with digital input                           |                 | N       |
|            | Maximum dB(A) ..... :   |                 | —       |
| 10.6.5.3   | Cordless listening device   |                 | N       |
|            | Maximum dB(A) ..... :   |                 | —       |

|          |  |  |   |
|----------|--|--|---|
| <b>B</b> | <b>NORMAL OPERATING CONDITION TESTS, ABNORMAL OPERATING CONDITION TESTS AND SINGLE FAULT CONDITION TESTS</b> |  | P |
| B.2      | Normal Operating Conditions  | See the following details.   | P |
| B.2.1    | General requirements..... :  | (See Test Item Particulars and appended test tables)                   | P |
|          | Audio Amplifiers and equipment with audio amplifiers ..... :   | Normal operation : Max. available output power with 1KHz signal input. | P |
| B.2.3    | Supply voltage and tolerances  | (See appended table B.2.5)   | P |
| B.2.5    | Input test..... :  | (See appended table B.2.5)   | P |
| B.3      | Simulated abnormal operating conditions  |  | P |
| B.3.1    | General requirements..... :  | (See appended table B.3&B.4)   | P |
| B.3.2    | Covering of ventilation openings   | No ventilation openings provided.                                      | N |
| B.3.3    | D.C. mains polarity test   |  | N |
| B.3.4    | Setting of voltage selector ..... :  | No setting of voltage selector within the EUT                          | N |
| B.3.5    | Maximum load at output terminals ..... :   | No such terminals.   | N |
| B.3.6    | Reverse battery polarity   | Impossible reverse polarity by inherent design.                        | P |
| B.3.7    | Abnormal operating conditions as specified in Clause E.2.  |  | P |
| B.3.8    | Safeguards functional during and after abnormal operating conditions   | All safeguards remained effectively.                                   | P |
| B.4      | Simulated single fault conditions  |  | P |
| B.4.2    | Temperature controlling device open or short-circuited ..... :   |  | N |
| B.4.3    | Motor tests  |  | P |
| B.4.3.1  | Motor blocked or rotor locked increasing the internal ambient temperature ..... :                            | (See appended table B.4)   | P |
| B.4.4    | Short circuit of functional insulation   | See the following details.   | P |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |   |         |
|------------|---|---|---------|
| Clause     | Requirement – Test  | Result - Remark   | Verdict |
| B.4.4.1    | Short circuit of clearances for functional insulation                                     | (See appended table B.3 &B.4)   | P       |
| B.4.4.2    | Short circuit of creepage distances for functional insulation                             | (See appended table B.3 &B.4)   | P       |
| B.4.4.3    | Short circuit of functional insulation on coated printed boards                           | No coated printed boards within the EUT   | N       |
| B.4.5      | Short circuit and interruption of electrodes in tubes and semiconductors                  |   | P       |
| B.4.6      | Short circuit or disconnect of passive components   | (See appended table B.3 &B.4)   | P       |
| B.4.7      | Continuous operation of components  | The EUT is continuous operating type and no such components intended for short time operation or intermittent operation | N       |
| B.4.8      | Class 1 and Class 2 energy sources within limits during and after single fault conditions | (See appended table B.3&B.4)  | P       |
| B.4.9      | Battery charging under single fault conditions ... :                                      | Complied with the annex M   | P       |

| <b>C</b> | <b>UV RADIATION</b>                                    |  | N |
|----------|--|--|---|
| C.1      | Protection of materials in equipment from UV radiation | No such UV generated from the equipment. | N |
| C.1.2    | Requirements   |  | N |
| C.1.3    | Test method  |  | N |
| C.2      | UV light conditioning test                             |  | N |
| C.2.1    | Test apparatus   |  | N |
| C.2.2    | Mounting of test samples                               |  | N |
| C.2.3    | Carbon-arc light-exposure apparatus                    |  | N |
| C.2.4    | Xenon-arc light exposure apparatus                     |  | N |

| <b>D</b> | <b>TEST GENERATORS</b>           |                        | N |
|----------|----------------------------------|------------------------|---|
| D.1      | Impulse test generators          | No such consideration. | N |
| D.2      | Antenna interface test generator |                        | N |
| D.3      | Electronic pulse generator       |                        | N |

| <b>E</b> | <b>TEST CONDITIONS FOR EQUIPMENT CONTAINING AUDIO AMPLIFIERS</b> |                            | P |
|----------|--|----------------------------|---|
| E.1      | Audio amplifier normal operating conditions                      |                            | N |
|          | Audio signal voltage (V).....:                                   | (See appended table B.2.5) | — |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test                            | Result - Remark | Verdict |
|            | Rated load impedance (Ω) .....                | 8Ω              | —       |
| E.2        | Audio amplifier abnormal operating conditions |                 | P       |


| F       | EQUIPMENT MARKINGS, INSTRUCTIONS, AND INSTRUCTIONAL SAFEGUARDS |  | P |
|---------|--|--|---|
| F.1     | General requirements   | See the following details.   | P |
|         | Instructions – Language .....                                  | English  | — |
| F.2     | Letter symbols and graphical symbols                           | See the following details.   | P |
| F.2.1   | Letter symbols according to IEC60027-1                         | Letter symbols for quantities and units are complied with IEC 60027-1.           | P |
| F.2.2   | Graphic symbols IEC, ISO or manufacturer specific              | Graphical symbols are complied with IEC 60417, ISO 3864-2, ISO 7000 or ISO 7010. | P |
| F.3     | Equipment markings   |  | P |
| F.3.1   | Equipment marking locations                                    | Equipment marking is located on the exterior surface and is easily visible.      | P |
| F.3.2   | Equipment identification markings                              | See the following details.   | P |
| F.3.2.1 | Manufacturer identification .....                              | See copy of marking plate.   | — |
| F.3.2.2 | Model identification .....                                     | See copy of marking plate.   | — |
| F.3.3   | Equipment rating markings                                      | Provided.  | P |
| F.3.3.1 | Equipment with direct connection to mains                      |  | N |
| F.3.3.2 | Equipment without direct connection to mains                   | See above.   | P |
| F.3.3.3 | Nature of supply voltage .....                                 |  | — |
| F.3.3.4 | Rated voltage .....  | 5V   | — |
| F.3.3.4 | Rated frequency .....  |  | — |
| F.3.3.6 | Rated current or rated power .....                             | 1.0A   | — |
| F.3.3.7 | Equipment with multiple supply connections                     | Only one supply connection.  | N |
| F.3.4   | Voltage setting device   | No such device on the equipment.   | N |
| F.3.5   | Terminals and operating devices                                | See below  | N |
| F.3.5.1 | Mains appliance outlet and socket-outlet markings .....        | No such devices on the equipment.  | N |
| F.3.5.2 | Switch position identification marking .....                   | No such switch on the equipment.   | N |
| F.3.5.3 | Replacement fuse identification and rating markings .....      |  | N |
| F.3.5.4 | Replacement battery identification marking .....               |  | P |
| F.3.5.5 | Terminal marking location                                      |  | N |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |  |         |
|------------|--|--|---------|
| Clause     | Requirement – Test   | Result - Remark  | Verdict |
| F.3.6      | Equipment markings related to equipment classification   | Class III  | N       |
| F.3.6.1    | Class I Equipment  |  | N       |
| F.3.6.1.1  | Protective earthing conductor terminal   |  | N       |
| F.3.6.1.2  | Neutral conductor terminal   |  | N       |
| F.3.6.1.3  | Protective bonding conductor terminals   |  | N       |
| F.3.6.2    | Class II equipment (IEC60417-5172)   |  | N       |
| F.3.6.2.1  | Class II equipment with or without functional earth  |  | N       |
| F.3.6.2.2  | Class II equipment with functional earth terminal marking  |  | N       |
| F.3.7      | Equipment IP rating marking .....  | This equipment is classified as IPX0.  | —       |
| F.3.8      | External power supply output marking   |  | N       |
| F.3.9      | Durability, legibility and permanence of marking   | See the following details.   | P       |
| F.3.10     | Test for permanence of markings  | The label was subjected to the permanence of marking test, 15 sec. for water and 15 sec. for petroleum spirit.<br>After each test, the marking remained legible. | P       |
| F.4        | Instructions   |  | P       |
|            | a) Equipment for use in locations where children not likely to be present - marking                            |  | N       |
|            | b) Instructions given for installation or initial use  | Relevant safety caution texts and installation instruction are available.  | P       |
|            | c) Equipment intended to be fastened in place  |  | N       |
|            | d) Equipment intended for use only in restricted access area   |  | N       |
|            | e) Audio equipment terminals classified as ES3 and other equipment with terminals marked in accordance F.3.6.1 |  | N       |
|            | f) Protective earthing employed as safeguard   |  | N       |
|            | g) Protective earthing conductor current exceeding ES 2 limits   |  | N       |
|            | h) Symbols used on equipment   |  | P       |
|            | i) Permanently connected equipment not provided with all-pole mains switch                                     | The EUT is not a permanently connected equipment   | N       |
|            | j) Replaceable components or modules providing safeguard function  |  | P       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result - Remark | Verdict |
| F.5        | Instructional safeguards  |                 | N       |
|            | Where “instructional safeguard” is referenced in the test report it specifies the required elements, location of marking and/or instruction |                 | N       |

|               |  |   |   |
|---------------|--|---|---|
| <b>G</b>      | <b>COMPONENTS</b>  |   | P |
| <b>G.1</b>    | <b>Switches</b>  |   | N |
| G.1.1         | General requirements   | No such switch as disconnect devices provided within the equipment. | N |
| G.1.2         | Ratings, endurance, spacing, maximum load  |   | N |
| <b>G.2</b>    | <b>Relays</b>  |   | N |
| G.2.1         | General requirements   | No such relay provided within the equipment.                        | N |
| G.2.2         | Overload test  |   | N |
| G.2.3         | Relay controlling connectors supply power  |   | N |
| G.2.4         | Mains relay, modified as stated in G.2   |   | N |
| <b>G.3</b>    | <b>Protection Devices</b>  |   | N |
| G.3.1         | Thermal cut-offs   | No thermal cut-off provided within the equipment.                   | N |
| G.3.1.1a) &b) | Thermal cut-outs separately approved according to IEC 60730 with conditions indicated in a) & b) | See above.  | N |
| G.3.1.1c)     | Thermal cut-outs tested as part of the equipment as indicated in c)                              | See above.  | N |
| G.3.1.2       | Thermal cut-off connections maintained and secure  | See above.  | N |
| G.3.2         | Thermal links  |   | N |
| G.3.2.1a)     | Thermal links separately tested with IEC 60691   | No thermal link provided within the equipment.                      | N |
| G.3.2.1b)     | Thermal links tested as part of the equipment  | See above.  | N |
|               | Aging hours (H) .....  | See above.  | — |
|               | Single Fault Condition .....   | See above.  | — |
|               | Test Voltage (V) and Insulation Resistance (Ω) . :   | See above.  | — |
| G.3.3         | PTC Thermistors  | No PTC thermistor provided within the equipment.                    | N |
| G.3.4         | Overcurrent protection devices   |   | N |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1   |  |                                  |         |
|--------------|--|----------------------------------|---------|
| Clause       | Requirement – Test   | Result - Remark                  | Verdict |
| G.3.5        | Safeguards components not mentioned in G.3.1 to G.3.5                                    |                                  | N       |
| G.3.5.1      | Non-resettable devices suitably rated and marking provided                               | No such component.               | N       |
| G.3.5.2      | Single faults conditions .....   |                                  | N       |
| <b>G.4</b>   | <b>Connectors</b>  |                                  | N       |
| G.4.1        | Spacings   | No such connector within the EUT | N       |
| G.4.2        | Mains connector configuration .....  |                                  | N       |
| G.4.3        | Plug is shaped that insertion into mains socket-outlets or appliance coupler is unlikely |                                  | N       |
| <b>G.5</b>   | <b>Wound Components</b>  |                                  | N       |
| G.5.1        | Wire insulation in wound components.....   | No such component.               | N       |
| G.5.1.2 a)   | Two wires in contact inside wound component, angle between 45° and 90°                   |                                  | N       |
| G.5.1.2 b)   | Construction subject to routine testing  |                                  | N       |
| G.5.2        | Endurance test on wound components   |                                  | N       |
| G.5.2.1      | General test requirements  |                                  | N       |
| G.5.2.2      | Heat run test  |                                  | N       |
|              | Time (s).....  |                                  | —       |
|              | Temperature (°C).....  |                                  | —       |
| G.5.2.3      | Wound Components supplied by mains   |                                  | N       |
| <b>G.5.3</b> | <b>Transformers</b>  |                                  | N       |
| G.5.3.1      | Requirements applied (IEC61204-7, IEC61558-1/-2, and/or IEC62368-1).....                 |                                  | N       |
|              | Position .....   |                                  | —       |
|              | Method of protection .....   |                                  | —       |
| G.5.3.2      | Insulation   |                                  | N       |
|              | Protection from displacement of windings.....  |                                  | —       |
| G.5.3.3      | Overload test .....  |                                  | N       |
| G.5.3.3.1    | Test conditions  |                                  | N       |
| G.5.3.3.2    | Winding Temperatures testing in the unit   |                                  | N       |
| G.5.3.3.3    | Winding Temperatures - Alternative test method   |                                  | N       |
| <b>G.5.4</b> | <b>Motors</b>  |                                  | P       |
| G.5.4.1      | General requirements   | Only DC motor used.              | P       |
|              | Position .....   | Inside enclosure.                | —       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                          |         |
|------------|---|--------------------------|---------|
| Clause     | Requirement – Test  | Result - Remark          | Verdict |
| G.5.4.2    | Test conditions   |                          | N       |
| G.5.4.3    | Running overload test   |                          | N       |
| G.5.4.4    | Locked-rotor overload test  |                          | N       |
|            | Test duration (days) .....  |                          | —       |
| G.5.4.5    | Running overload test for d.c. motors in secondary circuits             |                          | N       |
| G.5.4.5.2  | Tested in the unit  |                          | N       |
|            | Electric strength test (V) .....  |                          | —       |
| G.5.4.5.3  | Tested on the Bench - Alternative test method; test time (h) .....      |                          | N       |
|            | Electric strength test (V) .....  |                          | —       |
| G.5.4.6    | Locked-rotor overload test for d.c. motors in secondary circuits        |                          | P       |
| G.5.4.6.2  | Tested in the unit  |                          | P       |
|            | Maximum Temperature .....   | (See appended table B.4) | P       |
|            | Electric strength test (V) .....  |                          | N       |
| G.5.4.6.3  | Tested on the bench - Alternative test method; test time (h).....       |                          | N       |
|            | Electric strength test (V) .....  |                          | N       |
| G.5.4.7    | Motors with capacitors  |                          | N       |
| G.5.4.8    | Three-phase motors  |                          | N       |
| G.5.4.9    | Series motors   |                          | N       |
|            | Operating voltage .....   |                          | —       |
| <b>G.6</b> | <b>Wire Insulation</b>  |                          | N       |
| G.6.1      | General   |                          | N       |
| G.6.2      | Solvent-based enamel wiring insulation                                  |                          | N       |
| <b>G.7</b> | <b>Mains supply cords</b>   |                          | N       |
| G.7.1      | General requirements  |                          | N       |
|            | Type .....  |                          | —       |
|            | Rated current (A) .....   |                          | —       |
|            | Cross-sectional area (mm <sup>2</sup> ), (AWG).....                     |                          | —       |
| G.7.2      | Compliance and test method  |                          | N       |
| G.7.3      | Cord anchorages and strain relief for non-detachable power supply cords |                          | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1  |   |  |         |
|-------------|---|--|---------|
| Clause      | Requirement – Test                                  | Result - Remark                                      | Verdict |
| G.7.3.2     | Cord strain relief                                  |  | N       |
| G.7.3.2.1   | Requirements  |  | N       |
|             | Strain relief test force (N).....:                  |  | —       |
| G.7.3.2.2   | Strain relief mechanism failure                     |  |         |
| G.7.3.2.3   | Cord sheath or jacket position, distance (mm).....: |  | —       |
| G.7.3.2.4   | Strain relief comprised of polymeric material       |  | N       |
| G.7.4       | Cord Entry.....:                                    |  | N       |
| G.7.5       | Non-detachable cord bend protection                 |  | N       |
| G.7.5.1     | Requirements  |  | N       |
| G.7.5.2     | Mass (g) .....                                      |  | —       |
|             | Diameter (m).....:                                  |  | —       |
|             | Temperature (°C).....:                              |  | —       |
| G.7.6       | Supply wiring space                                 |  | N       |
| G.7.6.2     | Stranded wire                                       |  | N       |
| G.7.6.2.1   | Test with 8 mm strand                               |  | N       |
| <b>G.8</b>  | <b>Varistors</b>                                    |  | N       |
| G.8.1       | General requirements                                | No VDRs.   | N       |
| G.8.2       | Safeguard against shock                             |  | N       |
| G.8.3       | Safeguard against fire                              |  | N       |
| G.8.3.2     | Varistor overload test.....:                        |  | N       |
| G.8.3.3     | Temporary overvoltage.....:                         | (See appended table B.3)                             | N       |
| <b>G.9</b>  | <b>Integrated Circuit (IC) Current Limiters</b>     |  | N       |
| G.9.1 a)    | Manufacturer defines limit at max. 5A.              | No IC current limiter provided within the equipment. | N       |
| G.9.1 b)    | Limiters do not have manual operator or reset       |  | N       |
| G.9.1 c)    | Supply source does not exceed 250 VA .....          |  | —       |
| G.9.1 d)    | IC limiter output current (max. 5A) .....           |  | —       |
| G.9.1 e)    | Manufacturers' defined drift .....                  |  | —       |
| G.9.2       | Test Program 1                                      |  | N       |
| G.9.3       | Test Program 2                                      |  | N       |
| G.9.4       | Test Program 3                                      |  | N       |
| <b>G.10</b> | <b>Resistors</b>                                    |  | N       |
| G.10.1      | General requirements                                |  | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1  |   |  |         |
|-------------|---|--|---------|
| Clause      | Requirement – Test  | Result - Remark  | Verdict |
| G.10.2      | Resistor test   |  | N       |
| G.10.3      | Test for resistors serving as safeguards between the mains and an external circuit consisting of a coaxial cable      |  | N       |
| G.10.3.1    | General requirements  |  | N       |
| G.10.3.2    | Voltage surge test  |  | N       |
| G.10.3.3    | Impulse test  |  | N       |
| <b>G.11</b> | <b>Capacitor and RC units</b>   |  | N       |
| G.11.1      | General requirements  |  | N       |
| G.11.2      | Conditioning of capacitors and RC units   |  | N       |
| G.11.3      | Rules for selecting capacitors  |  | N       |
| <b>G.12</b> | <b>Optocouplers</b>   |  | N       |
|             | Optocouplers comply with IEC 60747-5-5:2007 Spacing or Electric Strength Test (specify option and test results) ..... |  | N       |
|             | Type test voltage Vini .....  |  | —       |
|             | Routine test voltage, Vini,b .....  |  | —       |
| <b>G.13</b> | <b>Printed boards</b>   |  | P       |
| G.13.1      | General requirements  | See the following details.   | P       |
| G.13.2      | Uncoated printed boards   | The insulation between conductors on the outer surfaces of an uncoated printed board complied with the minimum clearance and creepage requirements | P       |
| G.13.3      | Coated printed boards   | No coated printed board provided within the equipment.   | N       |
| G.13.4      | Insulation between conductors on the same inner surface   |  | N       |
|             | Compliance with cemented joint requirements (Specify construction) .....  |  | —       |
| G.13.5      | Insulation between conductors on different surfaces   |  | N       |
|             | Distance through insulation .....   |  | N       |
|             | Number of insulation layers (pcs) .....   |  | —       |
| G.13.6      | Tests on coated printed boards  |  | N       |
| G.13.6.1    | Sample preparation and preliminary inspection   |  | N       |
| G.13.6.2a)  | Thermal conditioning  |  | N       |


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1  |   |                 |         |
|-------------|---|-----------------|---------|
| Clause      | Requirement – Test  | Result - Remark | Verdict |
| G.13.6.2b)  | Electric strength test  |                 | N       |
| G.13.6.2c)  | Abrasion resistance test  |                 | N       |
| <b>G.14</b> | <b>Coating on components terminals</b>  |                 | N       |
| G.14.1      | Requirements .....  | (See G.13)      | N       |
| <b>G.15</b> | <b>Liquid filled components</b>   |                 | N       |
| G.15.1      | General requirements  |                 | N       |
| G.15.2      | Requirements  |                 | N       |
| G.15.3      | Compliance and test methods   |                 | N       |
| G.15.3.1    | Hydrostatic pressure test   |                 | N       |
| G.15.3.2    | Creep resistance test   |                 | N       |
| G.15.3.3    | Tubing and fittings compatibility test  |                 | N       |
| G.15.3.4    | Vibration test  |                 | N       |
| G.15.3.5    | Thermal cycling test  |                 | N       |
| G.15.3.6    | Force test  |                 | N       |
| G.15.4      | Compliance  |                 | N       |
| <b>G.16</b> | <b>IC including capacitor discharge function (ICX)</b>  |                 | N       |
| a)          | Humidity treatment in accordance with sc5.4.8 – 120 hours   |                 | N       |
| b)          | Impulse test using circuit 2 with $U_c =$ to transient voltage .....  |                 | N       |
| C1)         | Application of ac voltage at 110% of rated voltage for 2.5 minutes  |                 | N       |
| C2)         | Test voltage .....  |                 | —       |
| D1)         | 10,000 cycles on and off using capacitor with smallest capacitance resistor with largest resistance specified by manufacturer |                 | N       |
| D2)         | Capacitance .....   |                 | —       |
| D3)         | Resistance .....  |                 | —       |

| <b>H</b> | <b>CRITERIA FOR TELEPHONE RINGING SIGNALS</b> |  | N |
|----------|---|--|---|
| H.1      | General                                       |  | N |
| H.2      | Method A                                      |  | N |
| H.3      | Method B                                      |  | N |
| H.3.1    | Ringling signal                               |  | N |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result - Remark | Verdict |
| H.3.1.1    | Frequency (Hz) .....  |                 | —       |
| H.3.1.2    | Voltage (V) .....   |                 | —       |
| H.3.1.3    | Cadence; time (s) and voltage (V) .....                                       |                 | —       |
| H.3.1.4    | Single fault current (mA):.....   |                 | —       |
| H.3.2      | Tripping device and monitoring voltage.....                                   |                 | N       |
| H.3.2.1    | Conditions for use of a tripping device or a monitoring voltage complied with |                 | N       |
| H.3.2.2    | Tripping device   |                 | N       |
| H.3.2.3    | Monitoring voltage (V) .....  |                 | —       |

|          |   |  |   |
|----------|---|--|---|
| <b>J</b> | <b>INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION</b> |  | N |
|          | General requirements  |  | N |

|          |   |  |   |
|----------|---|--|---|
| <b>K</b> | <b>SAFETY INTERLOCKS</b>  |  | N |
| K.1      | General requirements  | No safety interlock provided within the equipment. | N |
| K.2      | Components of safety interlock safeguard mechanism .....  | (See Annex G)                                      | N |
| K.3      | Inadvertent change of operating mode  |  | N |
| K.4      | Interlock safeguard override  |  | N |
| K.5      | Fail-safe   |  | N |
|          | Compliance.....   | (See appended table B.4)                           | N |
| K.6      | Mechanically operated safety interlocks   |  | N |
| K.6.1    | Endurance requirement   |  | N |
| K.6.2    | Compliance and Test method .....  |  | N |
| K.7      | Interlock circuit isolation   |  | N |
| K.7.1    | Separation distance for contact gaps & interlock circuit elements (type and circuit location) ..... |  | N |
| K.7.2    | Overload test, Current (A) .....  |  | N |
| K.7.3    | Endurance test  |  | N |
| K.7.4    | Electric strength test .....  | (See appended table 5.4.11)                        | N |

|          |                           |  |   |
|----------|---------------------------|--|---|
| <b>L</b> | <b>DISCONNECT DEVICES</b> |  | N |
| L.1      | General requirements      |  | N |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |                                 |                 |         |
|------------|---------------------------------|-----------------|---------|
| Clause     | Requirement – Test              | Result - Remark | Verdict |
| L.2        | Permanently connected equipment |                 | N       |
| L.3        | Parts that remain energized     |                 | N       |
| L.4        | Single phase equipment          |                 | N       |
| L.5        | Three-phase equipment           |                 | N       |
| L.6        | Switches as disconnect devices  |                 | N       |
| L.7        | Plugs as disconnect devices     |                 | N       |
| L.8        | Multiple power sources          |                 | N       |

| M          | EQUIPMENT CONTAINING BATTERIES AND THEIR PROTECTION CIRCUITS             |  | P |
|------------|--|--|---|
| M.1        | General requirements   |  | P |
| M.2        | Safety of batteries and their cells                                      |  | P |
| M.2.1      | Requirements   |  | P |
| M.2.2      | Compliance and test method (identify method) ...:                        |  | P |
| M.3        | Protection circuits  |  | P |
| M.3.1      | Requirements   |  | P |
| M.3.2      | Tests  |  | P |
|            | - Overcharging of a rechargeable battery                                 |  | P |
|            | - Unintentional charging of a non-rechargeable battery                   |  | N |
|            | - Reverse charging of a rechargeable battery                             |  | N |
|            | - Excessive discharging rate for any battery                             |  | P |
| M.3.3      | Compliance .....   | No chemical leakage, no liquid spillage, no explosion, no emission fo flame or expulsion of molten metal | P |
| M.4        | Additional safeguards for equipment containing secondary lithium battery |  | P |
| M.4.1      | General  |  | P |
| M.4.2      | Charging safeguards  |  | P |
| M.4.2.1    | Charging operating limits  |  | P |
| M.4.2.2a)  | Charging voltage, current and temperature .....                          | (See appended table M.4)   | P |
| M.4.2.2 b) | Single faults in charging circuitry.....                                 | (See appended table M.4)   | P |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |  |         |
|------------|---|--|---------|
| Clause     | Requirement – Test  | Result - Remark  | Verdict |
| M.4.3      | Fire Enclosure  | The fire enclosure used for equipment containing the secondary lithium battery, and complied with Cl. 6.4.5.2. | P       |
| M.4.4      | Endurance of equipment containing a secondary lithium battery                           |  | P       |
| M.4.4.2    | Preparation   |  | P       |
| M.4.4.3    | Drop and charge/discharge function tests  |  | P       |
|            | Drop  | After test, Voltage difference less than 5% in 24H   | P       |
|            | Charge  |  | P       |
|            | Discharge   |  | P       |
| M.4.4.4    | Charge-discharge cycle test   |  | P       |
| M.4.4.5    | Result of charge-discharge cycle test   | No fire, no explosion, and no hazards produced during tests.   | P       |
| M.5        | Risk of burn due to short circuit during carrying                                       |  | P       |
| M.5.1      | Requirement   |  | P       |
| M.5.2      | Compliance and Test Method (Test of P.2.3)  |  | N       |
| M.6        | Prevention of short circuits and protection from other effects of electric current      | Compliance with clause 7.3.6 in IEC 62133-2  | P       |
| M.6.1      | Short circuits  |  | N       |
| M.6.1.1    | General requirements  |  | N       |
| M.6.1.2    | Test method to simulate an internal fault   |  | N       |
| M.6.1.3    | Compliance (Specify M.6.1.2 or alternative method) .....                                |  | N       |
| M.6.2      | Leakage current (mA) .....  |  | N       |
| M.7        | Risk of explosion from lead acid and NiCd batteries                                     |  | N       |
| M.7.1      | Ventilation preventing explosive gas concentration                                      |  | N       |
| M.7.2      | Compliance and test method  |  | N       |
| M.8        | Protection against internal ignition from external spark sources of lead acid batteries |  | N       |
| M.8.1      | General requirements  |  | N       |
| M.8.2      | Test method   |  | N       |
| M.8.2.1    | General requirements  |  | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result - Remark | Verdict |
| M.8.2.2    | Estimation of hypothetical volume Vz (m <sup>3</sup> /s).....:  |                 | —       |
| M.8.2.3    | Correction factors .....  |                 | —       |
| M.8.2.4    | Calculation of distance d (mm) .....  |                 | —       |
| M.9        | Preventing electrolyte spillage   |                 | N       |
| M.9.1      | Protection from electrolyte spillage  |                 | N       |
| M.9.2      | Tray for preventing electrolyte spillage  |                 | N       |
| M.10       | Instructions to prevent reasonably foreseeable misuse (Determination of compliance: inspection, data review; or abnormal testing) ..... |                 | P       |

|          |                                   |  |   |
|----------|-----------------------------------|--|---|
| <b>N</b> | <b>ELECTROCHEMICAL POTENTIALS</b> |  | N |
|          | Metal(s) used.....:               |  | — |

|          |   |             |   |
|----------|---|-------------|---|
| <b>O</b> | <b>MEASUREMENT OF CREEPAGE DISTANCES AND CLEARANCES</b> |             | P |
|          | Figures O.1 to O.20 of this Annex applied .....         | Considered. | — |

|          |   |                       |   |
|----------|---|-----------------------|---|
| <b>P</b> | <b>SAFEGUARDS AGAINST ENTRY OF FOREIGN OBJECTS AND SPILLAGE OF INTERNAL LIQUIDS</b>   |                       | P |
| P.1      | General requirements  | No openings           | N |
| P.2.2    | Safeguards against entry of foreign object  |                       | N |
|          | Location and Dimensions (mm) .....  |                       | — |
| P.2.3    | Safeguard against the consequences of entry of foreign object   |                       | N |
| P.2.3.1  | Safeguards against the entry of a foreign object  |                       | N |
|          | Openings in transportable equipment   |                       | N |
|          | Transportable equipment with metalized plastic parts.....:  |                       | N |
| P.2.3.2  | Openings in transportable equipment in relation to metallized parts of a barrier or enclosure (identification of supplementary safeguard) ..... |                       | N |
| P.3      | Safeguards against spillage of internal liquids   | No such construction. | N |
| P.3.1    | General requirements  |                       | N |
| P.3.2    | Determination of spillage consequences  |                       | N |
| P.3.3    | Spillage safeguards   |                       | N |
| P.3.4    | Safeguards effectiveness  |                       | N |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                       |         |
|------------|---|-----------------------|---------|
| Clause     | Requirement – Test                              | Result - Remark       | Verdict |
| P.4        | Metallized coatings and adhesive securing parts | No such construction. | N       |
| P.4.2 a)   | Conditioning testing                            |                       | N       |
|            | Tc (°C) .....                                   |                       | —       |
|            | Tr (°C).....                                    |                       | —       |
|            | Ta (°C).....                                    |                       | —       |
| P.4.2 b)   | Abrasion testing .....                          |                       | N       |
| P.4.2 c)   | Mechanical strength testing .....               |                       | N       |

| Q        | CIRCUITS INTENDED FOR INTERCONNECTION WITH BUILDING WIRING                                      |  | N |
|----------|---|--|---|
| Q.1      | Limited power sources   |  | N |
| Q.1.1 a) | Inherently limited output   |  | N |
| Q.1.1 b) | Impedance limited output  |  | N |
|          | - Regulating network limited output under normal operating and simulated single fault condition |  | N |
| Q.1.1 c) | Overcurrent protective device limited output  |  | N |
| Q.1.1 d) | IC current limiter complying with G.9   |  | N |
| Q.1.2    | Compliance and test method  |  | N |
| Q.2      | Test for external circuits – paired conductor cable   |  | N |
|          | Maximum output current (A) .....  |  | — |
|          | Current limiting method .....   |  | — |

| R   | LIMITED SHORT CIRCUIT TEST  |                        | N |
|-----|---|------------------------|---|
| R.1 | General requirements  | No such consideration. | N |
| R.2 | Determination of the overcurrent protective device and circuit      |                        | N |
| R.3 | Test method Supply voltage (V) and short-circuit current (A). ..... |                        | N |

| S   | TESTS FOR RESISTANCE TO HEAT AND FIRE  |  | N |
|-----|--|--|---|
| S.1 | Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power does not exceed 4 000 W | The fire enclosure used material was approved. | N |
|     | Samples, material.....   |  | — |
|     | Wall thickness (mm) .....  |  | — |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |  |                 |         |
|------------|--|-----------------|---------|
| Clause     | Requirement – Test   | Result - Remark | Verdict |
|            | Conditioning (°C).....:  |                 | —       |
|            | Test flame according to IEC 60695-11-5 with conditions as set out  |                 | N       |
|            | - Material not consumed completely   |                 | N       |
|            | - Material extinguishes within 30s   |                 | N       |
|            | - No burning of layer or wrapping tissue   |                 | N       |
| S.2        | Flammability test for fire enclosure and fire barrier integrity  |                 | N       |
|            | Samples, material.....:  |                 | —       |
|            | Wall thickness (mm).....:  |                 | —       |
|            | Conditioning (°C).....:  |                 | —       |
|            | Test flame according to IEC 60695-11-5 with conditions as set out  |                 | N       |
|            | Test specimen does not show any additional hole  |                 | N       |
| S.3        | Flammability test for the bottom of a fire enclosure   |                 | N       |
|            | Samples, material.....:  |                 | —       |
|            | Wall thickness (mm).....:  |                 | —       |
|            | Cheesecloth did not ignite   |                 | N       |
| S.4        | Flammability classification of materials   |                 | N       |
| S.5        | Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power does not exceed 4 000 W |                 | N       |
|            | Samples, material.....:  |                 | —       |
|            | Wall thickness (mm).....:  |                 | —       |
|            | Conditioning (test condition), (°C).....:  |                 | —       |
|            | Test flame according to IEC 60695-11-20 with conditions as set out   |                 | N       |
|            | After every test specimen was not consumed completely  |                 | N       |
|            | After fifth flame application, flame extinguished within 1 min   |                 | N       |

| T   | MECHANICAL STRENGTH TESTS     | P                          |
|-----|-------------------------------|----------------------------|
| T.1 | General requirements          | See the following details. |
| T.2 | Steady force test, 10 N.....: | N                          |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |                                      |   |         |
|------------|--------------------------------------|---|---------|
| Clause     | Requirement – Test                   | Result - Remark                                 | Verdict |
| T.3        | Steady force test, 30 N .....        |   | N       |
| T.4        | Steady force test, 100 N .....       | (See appended table T.4)                        | P       |
| T.5        | Steady force test, 250 N .....       |   | N       |
| T.6        | Enclosure impact test                |   | N       |
|            | Fall test                            |   | N       |
|            | Swing test                           |   | N       |
| T.7        | Drop test .....                      | (See appended table T.7)                        | P       |
| T.8        | Stress relief test.....              | (See appended table T.8)                        | P       |
| T.9        | Impact Test (glass)                  | No such glass provided within the equipment.    | N       |
| T.9.1      | General requirements                 | See above.                                      | N       |
| T.9.2      | Impact test and compliance           | See above.                                      | N       |
|            | Impact energy (J) .....              |   | —       |
|            | Height (m).....                      |   | —       |
| T.10       | Glass fragmentation test.....        | (See sub-clause 4.4.4.9)                        | N       |
| T.11       | Test for telescoping or rod antennas | No such antennas provided within the equipment. | N       |
|            | Torque value (Nm) .....              | See above.                                      | —       |

|          |   |                                       |   |
|----------|---|---------------------------------------|---|
| <b>U</b> | <b>MECHANICAL STRENGTH OF CATHODE RAY TUBES (CRT) AND PROTECTION AGAINST THE EFFECTS OF IMPLOSION</b> |                                       | N |
| U.1      | General requirements  | No CRT provided within the equipment. | N |
| U.2      | Compliance and test method for non-intrinsically protected CRTs                                       | See above.                            | N |
| U.3      | Protective Screen.....  | See above.                            | N |

|          |   |  |   |
|----------|---|--|---|
| <b>V</b> | <b>DETERMINATION OF ACCESSIBLE PARTS (FINGERS, PROBES AND WEDGES)</b> |  | P |
| V.1      | Accessible parts of equipment   | Following the probes test specified in this annex except Figure V.3., V.4 and V.5 is not suitable. | P |
| V.2      | Accessible part criterion   | No live parts can be accessible.   | P |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1  |  |                 |         |
|---|--|-----------------|---------|
| Clause  | Requirement – Test   | Result – Remark | Verdict |
| ATTACHMENT TO TEST REPORT IEC 62368-1<br>EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES<br>(Audio/video, information and communication technology equipment Part 1: Safety requirements) |  |                 |         |
| <b>CENELEC COMMON MODIFICATIONS (EN)</b>  |  |                 | --      |
| 1   | NOTE Z1  |                 | P       |
| 4.Z1  | Protective devices included as integral parts of the equipment or as parts of the building installation: |                 | N       |
|   | a) Included as parts of the equipment  |                 | N       |
|   | b) For components in series with the mains; by devices in the building installation                      |                 | N       |
|   | c) For pluggable type B or permanently connected; by devices in the building installation                |                 | N       |
| 5.4.2.3.2.4   | Interconnection with external circuit  |                 | N       |
| 10.2.1  | Additional requirements in 10.5.1  |                 | N       |
| 10.5.1  | RS1 compliance measurement conditions  |                 | P       |
| 10.6.2.1  | EN 71-1:2011, 4.20 and methods and distances   |                 | N       |
| 10.Z1   | Non-ionizing radiation from radio frequencies in the range 0 to 300 GHz                                  |                 | N       |
| G.7.1   | NOTE Z1  |                 | P       |

| ZB                   | ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)  |  | Verdict |
|----------------------|---|--|---------|
| 4.1.15               | <b>Denmark, Finland, Norway and Sweden:</b><br>Class I pluggable equipment type A marking   |  | N       |
| 4.7.3                | <b>United Kingdom:</b><br>Torque test socket-outlet BS 1363, and the plug part BS 1363.   |  | N       |
| 5.2.2.2              | <b>Denmark:</b><br>Warning for high touchcurrent  |  | N       |
| 5.4.11.1 and Annex G | <b>Finland and Sweden:</b><br>Separation of the telecommunication network from earth  |  | N       |
| 5.5.2.1              | <b>Norway:</b><br>Capacitors rated for the applicable line-to-line voltage (230 V).   |  | N       |
| 5.5.6                | <b>Finland, Norway and Sweden:</b><br>Resistors used as basic safeguard or bridging basic insulation comply with G.10.1 and G.10.2. |  | N       |
| 5.6.1                | <b>Denmark:</b><br>Protection for pluggable equipment type A; integral part of the equipment  |  | N       |
| 5.6.4.2.1            | <b>Ireland and United Kingdom:</b><br>The protective current rating is taken to be 13 A   |  | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1    |   |                 |         |
|---------------|---|-----------------|---------|
| Clause        | Requirement – Test  | Result – Remark | Verdict |
| 5.6.5.1       | <b>Ireland and United Kingdom:</b><br>Conductor sizes of flexible cords to be accepted by terminals for equipment rated 10 A to 13 A  |                 | N       |
| 5.7.5         | <b>Denmark:</b><br>The installation instruction affixed to the equipment if high protective conductor current   |                 | N       |
| 5.7.6.1       | <b>Norway and Sweden:</b><br>Television distribution system isolation text in user manual   |                 | N       |
| 5.7.6.2       | <b>Denmark:</b><br>Warning for high touch current   |                 | N       |
| B.3.1 and B.4 | <b>Ireland and United Kingdom:</b><br>Tests conducted using an external miniature circuit breaker or protective devices included as an integral part of the direct plug-in equipment                  |                 | N       |
| G.4.2         | <b>Denmark:</b><br>Appliances rated $\leq 13$ A provided with a plug according to DS 60884-2-D1:2011.   |                 | N       |
|               | Class I equipment provided with socket-outlets provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a.   |                 | N       |
|               | If a single-phase equipment having rated $>13$ A or poly-phase equipment provided with a supply cord with a plug, plug in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2. |                 | N       |
|               | Mains socket outlets intended for providing power to Class II apparatus rated 2,5 A in accordance with DS 60884-2-D1:2011 standard sheet DKA 1- 4a.   |                 | N       |
|               | Other current rating socket outlets in compliance with Standard Sheet DKA 1-3a or DKA 1-1c.   |                 | N       |
|               | Mains socket-outlets with earth in compliance with DS 60884-2-D1:2011 Standard Sheet DK 1- 3a, DK 1-1c, DK1-1d, DK 1-5a or DK 1-7a  |                 | N       |
| G.4.2         | <b>United Kingdom:</b><br>The plug part of direct plug-in equipment assessed to BS 1363   |                 | N       |
| G.7.1         | <b>United Kingdom:</b><br>Equipment fitted with a 'standard plug' in accordance with the Plugs and Sockets etc (Safety) Regulations 1994, Statutory Instrument 1994 No. 1768                          |                 | N       |
| G.7.1         | <b>Ireland:</b><br>Apparatus provided with a plug in accordance with Statutory Instrument 525: 1997, "13 A Plugs and Conversion Adapters for Domestic Use   |                 | N       |
| G.7.2         | <b>Ireland and United Kingdom:</b><br>A power supply cord for equipment which is rated over 10 A and up to and including 13 A.  |                 | N       |

|           |   |    |
|-----------|---|----|
| <b>ZC</b> | <b>ANNEX ZC, NATIONAL DEVIATIONS (EN)</b> | -- |
|-----------|---|----|

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| EN 62368-1 |   |                 |         |
|------------|---|-----------------|---------|
| Clause     | Requirement – Test  | Result – Remark | Verdict |
| 10.5.2     | <b>Germany:</b><br>Cathode ray tube intended for the display of visual images, authorization or application of type approval and marking. |                 | N       |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
 Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



| 4.1.2 TABLE: List of critical components |   |                  |  |                           | P   |
|--|---|------------------|--|---------------------------|---|
| Object / part No.                        | Manufacturer/ trademark                           | Type / model     | Technical data   | Standard                  | Mark(s) of conformity <sup>1</sup>          |
| Travel Charger                           | Shenzhen Tianyin Electronics Co., Ltd             | TPA-97050100VU   | Input: 100-240V~50/60Hz, 0.15A<br>output: DC5.0V 1A<br>(class II, LPS, 40°C )  | EN 62368-1: 2014+A11:2017 | Report No.: AGC0055220 0705ES02             |
| Battery                                  | Zhongshan Tianmao Battery Co., Ltd.               | NOTE 7           | 3.8V, 3100mAh<br>Max charge current: 1550mA;<br>Max discharge current: 3100mA; | IEC 62133-2:2017          | EN 62133<br>Report No.: AGC0108520 0303TA01 |
| -PCB of battery                          | Interchangeable                                   | Interchangeable  | 130°C , V-0  | UL94, UL796               | UL  |
| Panel                                    | HAIFEI Photoelectric development CO., LTD         | HF-65550-3565-B0 | 5.5 inch   | EN 62368-1: 2014+A11:2017 | Tested with appliance                       |
| Speaker                                  | XIAMEN GUANGXUN ELECTRIC CO., LTD.                | 101-1511-002010  | 8ohm, 1W   | EN 62368-1: 2014+A11:2017 | Tested with appliance                       |
| LED                                      | Shineon (Beijing) Technology Co., Ltd             | MOC2016          | If 500mA, Vf 3.3-4.0V, Exempt group  | IEC62471:2006             | Report No.: SHES151000 598501               |
| DC Motor                                 | Guangxi WeiYiTong Electronic Technology Co., Ltd. | VICR0827         | DC 3.0V, 80mA  | EN 62368-1: 2014+A11:2017 | Tested with appliance                       |
| PCB                                      | Interchangeable                                   | Interchangeable  | V-0, 130°C   | UL94, UL796               | UL  |
| Enclosure                                | DONGGUAN HONOUR E P LTD                           | H2216(#)         | Min. 0.75mm, V-0, 80°C   | UL94                      | UL<br>E341783                               |
| Supplementary information:--             |   |                  |  |                           |   |

| 4.8.4, 4.8.5 TABLE: Lithium coin/button cell batteries mechanical tests |          |                                    |          | N |
|---|----------|------------------------------------|----------|---|
| (The following mechanical tests are conducted in the sequence noted.)   |          |                                    |          |   |
| 4.8.4.2 TABLE: Stress relief test                                       |          |                                    |          | — |
| Part  | Material | Oven Temperature (°C)              | Comments |   |
| --  | --       | --                                 | --       |   |
| 4.8.4.3 TABLE: Battery replacement test                                 |          |                                    |          | — |
| Battery part no. .... :   |          | --                                 | —        |   |
| Battery Installation/withdrawal   |          | Battery Installation/Removal Cycle | Comments |   |
| --  |          | 1                                  | --       |   |
| --  |          | 2                                  | --       |   |
| --  |          | 3                                  | --       |   |
| --  |          | 4                                  | --       |   |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|  |   |                       |                           |                                   |
|--|---|-----------------------|---------------------------|-----------------------------------|
| <b>4.8.4, 4.8.5</b>  | <b>TABLE: Lithium coin/button cell batteries mechanical tests</b> |                       |                           | N                                 |
| <b>(The following mechanical tests are conducted in the sequence noted.)</b> |   |                       |                           |                                   |
|  |   |                       | 5                         | --                                |
|  |   |                       | 6                         | --                                |
|  |   |                       | 8                         | --                                |
|  |   |                       | 9                         | --                                |
|  |   |                       | 10                        | --                                |
| <b>4.8.4.4</b>   | <b>TABLE: Drop test</b>   |                       |                           | —                                 |
|  | <b>Impact Area</b>  | <b>Drop Distance</b>  | <b>Drop No.</b>           | <b>Observations</b>               |
|  | --  | --                    | 1                         | --                                |
|  | --  | --                    | 2                         | --                                |
|  | --  | --                    | 3                         | --                                |
| <b>4.8.4.5</b>   | <b>TABLE: Impact</b>  |                       |                           | —                                 |
|  | <b>Impacts per surface</b>  | <b>Surface tested</b> | <b>Impact energy (Nm)</b> | <b>Comments</b>                   |
|  | --  | --                    | --                        | --                                |
|  | --  | --                    | --                        | --                                |
|  | --  | --                    | --                        | --                                |
| <b>4.8.4.6</b>   | <b>TABLE: Crush test</b>  |                       |                           | —                                 |
|  | <b>Test position</b>  | <b>Surface tested</b> | <b>Crushing Force (N)</b> | <b>Duration force applied (s)</b> |
|  | --  | --                    | --                        | --                                |
|  | --  | --                    | --                        | --                                |
| Supplementary information:   |   |                       |                           |                                   |

|                            |   |                       |                  |                                   |
|----------------------------|---|-----------------------|------------------|-----------------------------------|
| <b>4.8.5</b>               | <b>TABLE: Lithium coin/button cell batteries mechanical test result</b> |                       |                  | N                                 |
|                            | <b>Test position</b>  | <b>Surface tested</b> | <b>Force (N)</b> | <b>Duration force applied (s)</b> |
|                            | --  | --                    | --               | --                                |
|                            | --  | --                    | --               | --                                |
| Supplementary information: |   |                       |                  |                                   |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| 5.2   |                       | Table: Classification of electrical energy sources |                                     |                    |                    |    | P        |
|---|-----------------------|--|-------------------------------------|--------------------|--------------------|----|----------|
| 5.2.2.2 – Steady State Voltage and Current conditions |                       |  |                                     |                    |                    |    |          |
| No.   | Supply Voltage        | Location (e.g. circuit designation)                | Test conditions                     | Parameters         |                    |    | ES Class |
|   |                       |  |                                     | U<br>(Vrms or Vpk) | I<br>(Apk or Arms) | Hz |          |
| 1   | 5.0V                  | Internal circuit                                   | Normal                              | 5.0                | --                 | DC | ES1      |
|   |                       |  | Abnormal                            | --                 | --                 | -- |          |
|   |                       |  | Single fault – SC/OC                | --                 | --                 | -- |          |
| 2   | Fully charged battery | Battery pack                                       | Normal                              | 4.35V              | 0                  | DC | ES1      |
|   |                       |  | Abnormal                            | --                 | --                 | -- |          |
|   |                       |  | Single fault – SC/OC: P- and B-, SC | 4.35V              | 0                  | DC |          |

| 5.2.2.3 – Capacitance Limits |                |                                     |                      |                 |         |          |  |
|------------------------------|----------------|-------------------------------------|----------------------|-----------------|---------|----------|--|
| No.                          | Supply Voltage | Location (e.g. circuit designation) | Test conditions      | Parameters      |         | ES Class |  |
|                              |                |                                     |                      | Capacitance, nF | Upk (V) |          |  |
| --                           | --             | --                                  | Normal               | --              | --      | --       |  |
|                              |                |                                     | Abnormal             | --              | --      |          |  |
|                              |                |                                     | Single fault – SC/OC | --              | --      |          |  |

| 5.2.2.4 – Single Pulses |                |                                     |                      |               |         |          |          |
|-------------------------|----------------|-------------------------------------|----------------------|---------------|---------|----------|----------|
| No.                     | Supply Voltage | Location (e.g. circuit designation) | Test conditions      | Parameters    |         |          | ES Class |
|                         |                |                                     |                      | Duration (ms) | Upk (V) | lpk (mA) |          |
| --                      | --             | --                                  | Normal               | --            | --      | --       | --       |
|                         |                |                                     | Abnormal             | --            | --      | --       |          |
|                         |                |                                     | Single fault – SC/OC | --            | --      | --       |          |

| 5.2.2.5 – Repetitive Pulses |                |                                     |                      |               |         |          |          |
|-----------------------------|----------------|-------------------------------------|----------------------|---------------|---------|----------|----------|
| No.                         | Supply Voltage | Location (e.g. circuit designation) | Test conditions      | Parameters    |         |          | ES Class |
|                             |                |                                     |                      | Off time (ms) | Upk (V) | lpk (mA) |          |
| --                          | --             | --                                  | Normal               | --            | --      | --       | --       |
|                             |                |                                     | Abnormal             | --            | --      | --       |          |
|                             |                |                                     | Single fault – SC/OC | --            | --      | --       |          |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|  |
|--|
| <p>Test Conditions:<br/>         Normal –<br/>         Abnormal –<br/>         Supplementary information: SC=Short Circuit, OC=Short Circuit</p> |
|--|

| 5.4.1.4, 6.3.2, 9.0, B.2.6   | TABLE: Temperature measurements   |                    |                     |                               | P      |                               |                  |
|--|---|--------------------|---------------------|-------------------------------|--------|-------------------------------|------------------|
| Supply voltage (V) .....   | a) 5V, charging condition<br>b) powered by fully charged internal battery |                    |                     | ---                           |        |                               |                  |
| Ambient T <sub>min</sub> (°C) .....  | --  | --                 | --                  | ---                           |        |                               |                  |
| Ambient T <sub>max</sub> (°C) .....  | --  | --                 | --                  | ---                           |        |                               |                  |
| T <sub>ma</sub> (°C) .....   | 40  | 40                 | 40                  | ---                           |        |                               |                  |
| Maximum measured temperature T of part/at:   | T (°C)  |                    |                     | Allowed T <sub>max</sub> (°C) |        |                               |                  |
| <b>Test condition No.:</b>   | a)  | b)                 |                     | --                            |        |                               |                  |
| Battery surface  | 53.6  | 51.8               |                     | Ref.                          |        |                               |                  |
| Wire from battery  | 52.8  | 51.3               |                     | 70                            |        |                               |                  |
| PCB near U601  | 63.5  | 60.8               |                     | 130                           |        |                               |                  |
| PCB near U801  | 61.0  | 57.4               |                     | 130                           |        |                               |                  |
| Motor  | 43.5  | 42.0               |                     | Ref.                          |        |                               |                  |
| Plastic enclosure inside near PCB  | 52.4  | 51.0               |                     | Ref.                          |        |                               |                  |
| Ambient  | 40.0  | 40.0               |                     | --                            |        |                               |                  |
| For accessible part  |   |                    |                     |                               |        |                               |                  |
| Panel  | 37.2  | 35.4               |                     | 48                            |        |                               |                  |
| Plastic enclosure outside near PCB   | 36.8  | 34.2               |                     | 48                            |        |                               |                  |
| Ambient  | 25.0  | 25.0               |                     | --                            |        |                               |                  |
| Supplementary information: *) Temperature limits for winding include less 10K for thermocouple measurement method. |   |                    |                     |                               |        |                               |                  |
| Temperature T of winding:  | t <sub>1</sub> (°C)   | R <sub>1</sub> (Ω) | t <sub>2</sub> (°C) | R <sub>2</sub> (Ω)            | T (°C) | Allowed T <sub>max</sub> (°C) | Insulation class |
| --   | --  | --                 | --                  | --                            | --     | --                            | --               |
| --   | --  | --                 | --                  | --                            | --     | --                            | --               |
| Supplementary information:   |   |                    |                     |                               |        |                               |                  |
| Note 1: T <sub>ma</sub> should be considered as directed by applicable requirement                                 |   |                    |                     |                               |        |                               |                  |
| Note 2: T <sub>ma</sub> is not included in assessment of Touch Temperatures (Clause 9)                             |   |                    |                     |                               |        |                               |                  |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|  |  |                       |                          |        |
|--|--|-----------------------|--------------------------|--------|
| <b>5.4.1.10.3</b>                      | <b>TABLE: Ball pressure test of thermoplastics</b> |                       |                          | N      |
| Allowed impression diameter (mm) ..... |  |                       |                          | ≤ 2 mm |
| Object/Part No./Material               | Manufacturer/trademark                             | Test temperature (°C) | Impression diameter (mm) |        |
| --                                     | --   | --                    | --                       |        |
| Supplementary information:             |  |                       |                          |        |

|  |  |              |                              |                  |                      |                               |         |
|--|--|--------------|------------------------------|------------------|----------------------|-------------------------------|---------|
| <b>5.4.2.2, 5.4.2.4 and 5.4.3</b>                                    | <b>TABLE: Minimum Clearances/Creepage distance</b> |              |                              |                  |                      |                               | N       |
| Clearance (cl) and creepage distance (cr) at/of/between:             | Up (V)   | U r.m.s. (V) | Frequency (kHz) <sup>1</sup> | Required cl (mm) | cl (mm) <sup>2</sup> | Required <sup>3</sup> cr (mm) | cr (mm) |
| --   | --   | --           | --                           | --               | --                   | --                            | --      |
| Supplementary information:   |  |              |                              |                  |                      |                               |         |
| Note 1: Only for frequency above 30 kHz                              |  |              |                              |                  |                      |                               |         |
| Note 2: See table 5.4.2.4 if this is based on electric strength test |  |              |                              |                  |                      |                               |         |
| Note 3: Provide Material Group                                       |  |              |                              |                  |                      |                               |         |

|                              |   |                  |                  |    |
|------------------------------|---|------------------|------------------|----|
| <b>5.4.2.3</b>               | <b>TABLE: Minimum Clearances distances using required withstand voltage</b> |                  |                  | N  |
| Overvoltage Category (OV):   |   |                  |                  | -- |
| Pollution Degree:            |   |                  |                  | -- |
| Clearance distanced between: | Required withstand voltage  | Required cl (mm) | Measured cl (mm) |    |
| --                           | --  | --               | --               |    |
| Supplementary information:   |   |                  |                  |    |

|                               |  |                                       |                    |   |
|-------------------------------|--|---------------------------------------|--------------------|---|
| <b>5.4.2.4</b>                | <b>TABLE: Clearances based on electric strength test</b> |                                       |                    | N |
| Test voltage applied between: | Required cl (mm)   | Test voltage (kV) peak/ r.m.s. / d.c- | Breakdown Yes / No |   |
| --                            | --   | --                                    | --                 |   |
| Supplementary information:    |  |                                       |                    |   |

|                                       |  |                 |          |                   |          |   |
|---------------------------------------|--|-----------------|----------|-------------------|----------|---|
| <b>5.4.4.2, 5.4.4.5 c) 5.4.4.9</b>    | <b>TABLE: Distance through insulation measurements</b> |                 |          |                   |          | N |
| Distance through insulation di at/of: | Peak voltage (V)                                       | Frequency (kHz) | Material | Required DTI (mm) | DTI (mm) |   |
| --                                    | --   | --              | --       | --                | --       |   |
| Supplementary information:            |  |                 |          |                   |          |   |

|              |                                       |   |
|--------------|---------------------------------------|---|
| <b>5.4.9</b> | <b>TABLE: Electric strength tests</b> | N |
|--------------|---------------------------------------|---|

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| Test voltage applied between: | Voltage shape (AC, DC) | Test voltage (V) | Breakdown Yes / No |
|-------------------------------|------------------------|------------------|--------------------|
| Functional:                   |                        |                  |                    |
| --                            | --                     | --               | --                 |
| Basic/supplementary:          |                        |                  |                    |
| --                            | --                     | --               | --                 |
| Reinforced:                   |                        |                  |                    |
| --                            | --                     | --               | --                 |
| Routine Tests:                |                        |                  |                    |
| --                            | --                     | --               | --                 |
| Supplementary information:    |                        |                  |                    |

| 5.5.2.2 TABLE: Stored discharge on capacitors   |               |                            |                           |                                    | N                 |
|---|---------------|----------------------------|---------------------------|------------------------------------|-------------------|
| Supply Voltage (V), Hz  | Test Location | Operating Condition (N, S) | Switch position On or off | Measured Voltage (after 2 seconds) | ES Classification |
| --  | --            | --                         | --                        | --                                 | --                |
| Supplementary information:<br>X-capacitors installed for testing are:<br><input type="checkbox"/> bleeding resistor rating:<br><input type="checkbox"/> ICX:<br>Notes:<br>A. Test Location:<br>Phase to Neutral; Phase to Phase; Phase to Earth; and/or Neutral to Earth<br>B. Operating condition abbreviations:<br>N – Normal operating condition (e.g., normal operation, or open fuse); S –Single fault condition |               |                            |                           |                                    |                   |

| 5.6.6.2 TABLE: Resistance of protective conductors and terminations |                  |                |                  |                | N |
|---|------------------|----------------|------------------|----------------|---|
| Accessible part   | Test current (A) | Duration (min) | Voltage drop (V) | Resistance (Ω) |   |
| --  | --               | --             | --               | --             |   |
| --  | --               | --             | --               | --             |   |
| --  | --               | --             | --               | --             |   |
| Supplementary information:  |                  |                |                  |                |   |

| 5.7.2.2, 5.7.4 TABLE: Earthed accessible conductive part |   | N |
|--|---|---|
| Supply voltage .....                                     | : | — |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| Location | Test conditions specified in 6.1 of IEC 60990 or Fault Condition No in IEC 60990 clause 6.2.2.1 through 6.2.2.8, except for 6.2.2.7 | Touch current (mA) |
|----------|---|--------------------|
| --       | 1   | --                 |
| --       | 2*  | --                 |
| --       | 3   | --                 |
| --       | 4   | --                 |
| --       | 5   | --                 |
| --       | 6   | --                 |
| --       | 7   | --                 |

Supplementary Information:

Notes:

[1] Supply voltage is the anticipated maximum Touch Voltage

[2] Earthed neutral conductor [Voltage differences less than 1% or more]

[3] Specify method used for measurement as described in IEC 60990 sub-clause 4.3

[4] IEC60990, sub-clause 6.2.2.7, Fault 7 not applicable.

[5] (\*) IEC60990, sub-clause 6.2.2.2 is not applicable if switch or disconnect device (e.g., appliance coupler) provided.

| 6.2.2   | Table: Electrical power sources (PS) measurements for classification |                      |                     |                                    | P                    |
|---------|--|----------------------|---------------------|------------------------------------|----------------------|
| Source  | Description  | Measurement          | Max Power after 3 s | Max Power after 5 s <sup>(*)</sup> | PS Classification    |
| 5Vdc    | Internal circuit   | Power (W) :          | --                  | --                                 | PS2<br>(by declared) |
|         |  | V <sub>A</sub> (V) : | --                  | --                                 |                      |
|         |  | I <sub>A</sub> (A) : | --                  | --                                 |                      |
| 4.35Vdc | Battery pack   | Power (W) :          | --                  | 22.31                              | PS2                  |
|         |  | V <sub>A</sub> (V) : | --                  | 3.21                               |                      |
|         |  | I <sub>A</sub> (A) : | --                  | 6.95                               |                      |
| 4.35Vdc | Battery cell   | Power (W) :          | --                  | 44.50                              | PS2                  |
|         |  | V <sub>A</sub> (V) : | --                  | 1.54                               |                      |
|         |  | I <sub>A</sub> (A) : | --                  | 28.9                               |                      |

Supplementary Information:

(\*) Measurement taken only when limits at 3 seconds exceed PS1 limits

| 6.2.3.1  | Table: Determination of Potential Ignition Sources (Arcing PIS) |                               |                              | N                    |
|----------|---|-------------------------------|------------------------------|----------------------|
| Location | Open circuit voltage After 3 s (Vp)                             | Measured r.m.s current (Irms) | Calculated value (Vp x Irms) | Arcing PIS? Yes / No |
| --       | --  | --                            | --                           | --                   |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



Supplementary information:  
An Arcing PIS requires a minimum of 50 V (peak) a.c. or d.c. An Arcing PIS is established when the product of the open circuit voltage ( $V_o$ ) and normal operating condition rms current ( $I_{rms}$ ) is greater than 15.

| 6.2.3.2                | Table: Determination of Potential Ignition Sources (Resistive PIS) |   |  |  | P                     |
|------------------------|--|---|--|--|-----------------------|
| Circuit Location (x-y) | Operating Condition (Normal / Describe Single Fault)               | Measured wattage or VA During first 30 s (W / VA) | Measured wattage or VA After 30 s (W / VA) | Protective Circuit, Regulator, or PTC Operated? Yes / No (Comment) | Resistive PIS? Yes/No |
| Battery pack           | Single Fault   | --  | --   | No   | Yes                   |
| Battery cell           | Single Fault   | --  | --   | No   | Yes                   |

Supplementary Information:  
A combination of voltmeter, VA and ammeter IA may be used instead of a wattmeter.  
If a separate voltmeter and ammeter are used, the product of (VA x IA) is used to determine Resistive PIS classification.  
A Resistive PIS: (a) dissipates more than 15 W, measured after 30 s of normal operation, or (b) under single fault conditions has either a power exceeding 100 W measured immediately after the introduction of the fault if electronic circuits, regulators or PTC devices are used, or has an available power exceeding 15 W measured 30 s after introduction of the fault.

| 8.5.5   | TABLE: High Pressure Lamp |                              | N |
|---|---------------------------|------------------------------|---|
| Description                                     | Values                    | Energy Source Classification |   |
| Lamp type.....:                                 |                           | ---                          |   |
| Manufacturer.....:                              |                           | ---                          |   |
| Cat no.....:                                    |                           | ---                          |   |
| Pressure (cold) (MPa).....:                     |                           | MS_                          |   |
| Pressure (operating) (MPa).....:                |                           | MS_                          |   |
| Operating time (minutes).....:                  |                           | ---                          |   |
| Explosion method.....:                          |                           | ---                          |   |
| Max particle length escaping enclosure (mm) ..: |                           | MS_                          |   |
| Max particle length beyond 1 m (mm).....:       |                           | MS_                          |   |
| Overall result.....:                            |                           |                              |   |

Supplementary information:

| B.2.5 | TABLE: Input test |             |       |             |         |            | P                   |
|-------|-------------------|-------------|-------|-------------|---------|------------|---------------------|
| U (V) | I (A)             | I rated (A) | P (W) | P rated (W) | Fuse No | I fuse (A) | Condition/status    |
| 4.35  | 0.83              | --          | 3.61  | ---         | --      | --         | Normal operation: a |
| 5.0   | 0.98              | 1.0         | 4.9   | ---         | --      | --         | Normal operation: b |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|  |                          |             |       |             |         |            |                  |   |
|--|--------------------------|-------------|-------|-------------|---------|------------|------------------|---|
| <b>B.2.5</b>   | <b>TABLE: Input test</b> |             |       |             |         |            |                  | P |
| U (V)  | I (A)                    | I rated (A) | P (W) | P rated (W) | Fuse No | I fuse (A) | Condition/status |   |
| Supplementary information:<br>a: when supplied by battery, the EUT was equipped with fully charge battery.<br>b: when supplied by Travel Charger, the EUT was equipped with fully discharge battery. |                          |             |       |             |         |            |                  |   |

| <b>B.3</b>  | <b>TABLE: Abnormal operating condition tests</b> |                     |               |          |                   |          |            | N           |
|---|--|---------------------|---------------|----------|-------------------|----------|------------|-------------|
| Ambient temperature (°C) .....                                  |  |                     |               |          | --                | ---      |            |             |
| Power source for EUT: Manufacturer, model/type, output rating : |  |                     |               |          | --                | ---      |            |             |
| Component No.   | Fault Condition                                  | Supply voltage, (V) | Test time (h) | Fuse no. | Fuse current, (A) | T-couple | Temp. (°C) | Observation |
| --  | --   | --                  | --            | --       | --                | --       | --         | --          |
| Supplementary information:                                      |  |                     |               |          |                   |          |            |             |

| <b>B.4</b>  | <b>TABLE: Fault condition tests</b> |                     |                |          |                   |          |   | P  |
|---|-------------------------------------|---------------------|----------------|----------|-------------------|----------|---|--|
| Ambient temperature (°C) .....                                    |                                     |                     |                |          | 23.0-25.0         |          | ---   |  |
| Power source for EUT: Manufacturer, model/type, output rating . : |                                     |                     |                |          | --                |          | ---   |  |
| Component No.   | Fault Condition                     | Supply voltage, (V) | Test time (ms) | Fuse no. | Fuse current, (A) | T-couple | Temp. (°C)  | Observation  |
| The EUT was equipped with fully charge battery.                   |                                     |                     |                |          |                   |          |   |  |
| Speaker   | S-C                                 | 4.35V               | 1h30min        | --       | --                | Type J   | Battery body: 43.3°C<br>Enclosure outside near PCB: 60.3°C<br>Ambient: 23.0°C | Unit working normally, No hazards, no damage. Battery current: 1.69A |
| Battery B- and P-   | Over charge, S-C                    | 5V                  | 7h             | --       | --                | --       | --  | Unit working normally. No damaged, no hazards.                       |
| Battery B- and P-   | Over discharge, S-C                 | 4.35V               | 3h             | --       | --                | --       | --  | Unit working normally. No damaged, no hazards.                       |
| P+ and P-, Discharging  | S-C                                 | 4.35V               | 5min           | --       | --                | --       | --  | Unit shutdown immediately, no damage and hazards.                    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|  |        |       |         |    |    |        |  |  |
|--|--------|-------|---------|----|----|--------|--|--|
| Motor  | Locked | 5V    | 7h      | -- | -- | Type J | Motor:<br>29.2°C<br>Ambient:<br>23.0°C   | No hazards, no damage  |
| B+ and B-,<br>Discharging                          | S-C    | 4.35V | 30min   | -- | -- | --     | --   | No fire, no explosion  |
| The EUT was equipped with fully discharge battery. |        |       |         |    |    |        |  |  |
| U550 Pin(3-5)                                      | S-C    | 5V    | 1h30min | -- | -- | Type J | Battery body:<br>39.6°C<br>Enclosure outside near PCB:<br>58.1°C<br>Ambient:<br>23.0°C | Unit working normally, No hazards, no damage. Battery current: 1.17A |
| Supplementary information:                         |        |       |         |    |    |        |  |  |

| Annex M   | TABLE: Batteries           |               |                         |                        |               |               |               |                   | P             |
|---|----------------------------|---------------|-------------------------|------------------------|---------------|---------------|---------------|-------------------|---------------|
| The tests of Annex M are applicable only when appropriate battery data is not available |                            |               |                         |                        |               |               |               |                   | --            |
| Is it possible to install the battery in a reverse polarity position? .....             |                            |               |                         |                        |               |               | --            | --                |               |
|   | Non-rechargeable batteries |               |                         | Rechargeable batteries |               |               |               |                   |               |
|   | Discharging                |               | Un-intentional charging | Charging               |               | Discharging   |               | Reversed charging |               |
|   | Meas. current              | Manuf. Specs. |                         | Meas. current          | Manuf. Specs. | Meas. current | Manuf. Specs. | Meas. current     | Manuf. Specs. |
| Max. current during normal condition  | --                         | --            | --                      | 891mA                  | 1550mA        | 830mA         | 3100mA        | --                | --            |
| Max. current during fault condition   | --                         | --            | --                      | 900mA                  | 1550mA        | 836mA         | 3100mA        | --                | --            |
| Test results:   |                            |               |                         |                        |               |               |               |                   | Verdict       |
| - Chemical leaks  |                            |               |                         |                        |               |               | No leaks      |                   | P             |
| - Explosion of the battery  |                            |               |                         |                        |               |               | No explosion  |                   | P             |
| - Emission of flame or expulsion of molten metal  |                            |               |                         |                        |               |               | No emission   |                   | P             |
| - Electric strength tests of equipment after completion of tests                        |                            |               |                         |                        |               |               | --            |                   | N             |
| Supplementary information:  |                            |               |                         |                        |               |               |               |                   |               |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| Annex M.4 Table: Additional safeguards for equipment containing secondary lithium batteries |                     |              |       |  | P           |
|---|---------------------|--------------|-------|--|-------------|
| Battery/Cell No.  | Test conditions     | Measurements |       |  | Observation |
|   |                     | U            | I (A) | Temp (C)                                   |             |
| 1   | Normal              | 4.35         | 0.89  | Battery body:<br>36.6°C<br>Ambient: 23.0°C | No hazards  |
| 1   | Abnormal            | 4.32         | 0.90  | Battery body:<br>37.3°C<br>Ambient: 23.0°C | No hazards  |
| 1   | Single fault –SC/OC | 4.35         | 0.90  | Battery body:<br>37.8°C<br>Ambient: 23.0°C | No hazards  |

Supplementary Information: see table Annex B.4 for detail

| Battery identification | Charging at T <sub>lowest</sub> (°C) | Observation             | Charging at T <sub>highest</sub> (°C) | Observation         |
|------------------------|--------------------------------------|-------------------------|---------------------------------------|---------------------|
| Li-ion                 | 0                                    | Charging current: 658mA | 55                                    | Charging current: 0 |

Supplementary Information:

| Annex Q.1 TABLE: Circuits intended for interconnection with building wiring (LPS) |            |                     |                     |       | N      |       |
|---|------------|---------------------|---------------------|-------|--------|-------|
| Note: Measured UOC (V) with all load circuits disconnected:                       |            |                     |                     |       |        |       |
| Output Circuit  | Components | U <sub>oc</sub> (V) | I <sub>sc</sub> (A) |       | S (VA) |       |
|   |            |                     | Meas.               | Limit | Meas.  | Limit |
| --  | --         | --                  | --                  | --    | --     | --    |
| --  | --         | --                  | --                  | --    | --     | --    |

Supplementary Information:  
S-C=Short circuit, O-C=Open circuit

| T.2, T.3, T.4, T.5 TABLE: Steady force test |          |                |          |                     | P           |
|---|----------|----------------|----------|---------------------|-------------|
| Part/Location                               | Material | Thickness (mm) | Force(N) | Test Duration (sec) | Observation |
| Top enclosure                               | Plastic  | Min. 1.2       | 100      | 5                   | No damaged  |
| Side enclosure                              | Plastic  | Min. 1.2       | 100      | 5                   | No damaged  |
| Bottom enclosure                            | Plastic  | Min. 1.2       | 100      | 5                   | No damaged  |

Supplementary information:

| T.6, T.9 | TABLE: Impact tests | N |
|----------|---------------------|---|
|----------|---------------------|---|

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| Part/Location | Material | Thickness (mm) | Vertical distance (mm) | Observation |
|---------------|----------|----------------|------------------------|-------------|
| --            | --       | --             | --                     | --          |
| --            | --       | --             | --                     | --          |
| --            | --       | --             | --                     | --          |

Supplementary information:

| T.7              | TABLE: Drop tests |                |                  |             | P |
|------------------|-------------------|----------------|------------------|-------------|---|
| Part/Location    | Material          | Thickness (mm) | Drop Height (mm) | Observation |   |
| Top enclosure    | Plastic           | Min. 1.2       | 1000             | No damaged  |   |
| Side enclosure   | Plastic           | Min. 1.2       | 1000             | No damaged  |   |
| Bottom enclosure | Plastic           | Min. 1.2       | 1000             | No damaged  |   |

Supplementary information:

| T.8              | TABLE: Stress relief test           |                |                       |              |                         | P |
|------------------|-------------------------------------|----------------|-----------------------|--------------|-------------------------|---|
| Part/Location    | Material                            | Thickness (mm) | Oven Temperature (°C) | Duration (h) | Observation             |   |
| Completed sample | Plastic enclosure (for all sources) | Min. 1.2       | 70                    | 7            | No damaged, no hazards. |   |

Supplementary information: For details refer to appended table 4.1.2.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



**Attachment A**  
**Photos of product**



Fig.1 – overview




Fig.2– overview

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>






Fig.3 – overview




Fig.4 – connector view

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agc-cert.com](mailto:agc@agc-cert.com) Web: <http://cn.agc-cert.com/>





Fig.5 – open view



Fig.6 – partview

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/






Fig.7 – partview




Fig.8 – partview

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/






Fig.9 – partview




Fig.10 – Battery

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agc-cert.com](mailto:agc@agc-cert.com) Web: <http://cn.agc-cert.com/>






Fig.11 – Battery




Fig.12 – top circuit of battery

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.






Fig.13 – bottom circuit of battery

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agc-cert.com](mailto:agc@agc-cert.com) Web: <http://cn.agc-cert.com/>







## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. The non-CMA report issued by AGC is only permitted to be used by the client as internal reference use and shall not be used for public demonstration purpose.
5. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
6. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
7. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
9. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
10. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

