



Appendix I for 5.8G WIFI RF Test Data

Product Name: Smartphone

Test Model: NOTE 40

Environmental Conditions

Temperature:	22.2° C
Relative Humidity:	52.7%
ATM Pressure:	100.0 kPa
Test Engineer:	Taylor Hu
Supervised by:	Ling Zhu





I.1 Equivalent Isotropically Radiated Power (EIRP)

EIRP(802.11a)---Transmitter					
Temperature (°C)	Power Supplied (V)	Test Result (EIRP, dBm)			Limit dBm
		Channel 149	Channel 157	Channel 165	
TL	VL	4.76	4.49	4.81	14
	VN	4.53	4.60	4.74	14
	VH	4.86	4.53	4.47	14
TN	VL	4.75	4.72	4.73	14
	VN	5.15	5.14	5.12	14
	VH	4.83	4.99	4.48	14
TH	VL	4.93	5.00	4.89	14
	VN	4.81	4.47	4.44	14
	VH	4.60	4.88	4.52	14

EIRP(802.11n20)---Transmitter					
Temperature (°C)	Power Supplied (V)	Test Result (EIRP, dBm)			Limit dBm
		Channel 149	Channel 157	Channel 165	
TL	VL	4.56	4.27	4.03	14
	VN	4.42	4.55	4.40	14
	VH	4.08	4.33	4.39	14
TN	VL	4.07	4.15	4.25	14
	VN	4.75	4.74	4.72	14
	VH	4.53	4.28	4.23	14
TH	VL	4.50	4.37	4.45	14
	VN	4.38	4.47	4.20	14
	VH	4.62	4.38	4.52	14



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



EIRP(802.11ac20)---Transmitter					
Temperature (°C)	Power Supplied (V)	Test Result (EIRP, dBm)			Limit dBm
		Channel 149	Channel 157	Channel 165	
TL	VL	4.25	4.33	4.18	14
	VN	4.21	4.28	3.99	14
	VH	4.06	4.34	4.09	14
TN	VL	3.96	4.08	3.78	14
	VN	4.49	4.48	4.46	14
	VH	4.25	3.86	4.34	14
TH	VL	3.96	3.96	3.89	14
	VN	4.34	4.26	4.23	14
	VH	3.91	3.97	4.23	14

EIRP(802.11n40)---Transmitter				
Temperature (°C)	Power Supplied (V)	Test Result (EIRP, dBm)		Limit dBm
		Channel 151	Channel 159	
TL	VL	7.86	7.75	14
	VN	7.66	8.11	14
	VH	7.81	7.96	14
TN	VL	7.91	7.89	14
	VN	8.33	8.32	14
	VH	7.92	8.14	14
TH	VL	8.08	7.98	14
	VN	8.22	7.78	14
	VH	8.14	8.17	14





EIRP(802.11ac40)---Transmitter				
Temperature (°C)	Power Supplied (V)	Test Result (EIRP, dBm)		Limit dBm
		Channel 151	Channel 159	
TL	VL	7.86	8.16	14
	VN	7.59	8.10	14
	VH	7.68	7.89	14
TN	VL	8.17	8.07	14
	VN	8.29	8.28	14
	VH	7.91	7.71	14
TH	VL	8.01	8.12	14
	VN	7.86	8.03	14
	VH	8.14	7.81	14

EIRP(802.11ac80)---Transmitter			
Temperature (°C)	Power Supplied (V)	Test Result (EIRP, dBm)	Limit dBm
		Channel 155	
TL	VL	3.64	14
	VN	4.16	14
	VH	3.69	14
TN	VL	4.01	14
	VN	4.28	14
	VH	4.06	14
TH	VL	3.93	14
	VN	3.93	14
	VH	4.17	14



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



I.2 Permitted Range of Operating Frequencies

802.11a---Transmitter			
Test Conditions		Frequency (MHz) at -30dBm/30KHz	
Temperature	Voltage(V)	fL at Low Channel >5725MHz	fH at High Channel (<5875MHz)
TL	VL	5728.52	5832.77
	VN	5728.53	5832.66
	VH	5728.83	5832.66
TN	VL	5728.57	5832.62
	VN	5729.08	5833.31
	VH	5728.75	5832.66
TH	VL	5728.69	5832.64
	VN	5728.38	5833.11
	VH	5728.38	5833.20
Limit	fH(5875MHz) - fL(5725MHz) = 150MHz		

802.11n20---Transmitter			
Test Conditions		Frequency (MHz) at -30dBm/30KHz	
Temperature	Voltage(V)	fL at Low Channel >5725MHz	fH at High Channel (<5875MHz)
TL	VL	5728.44	5832.98
	VN	5728.54	5833.19
	VH	5728.73	5832.74
TN	VL	5728.63	5832.76
	VN	5729.08	5833.31
	VH	5728.75	5832.92
TH	VL	5728.88	5832.92
	VN	5728.79	5833.13
	VH	5728.90	5833.01
Limit	fH(5875MHz) - fL(5725MHz) = 150MHz		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



802.11ac20---Transmitter			
Test Conditions		Frequency (MHz) at -30dBm/30KHz	
Temperature	Voltage(V)	fL at Low Channel >5725MHz	fH at High Channel (<5875MHz)
TL	VL	5728.98	5832.88
	VN	5728.67	5833.19
	VH	5728.59	5832.72
TN	VL	5728.79	5832.84
	VN	5729.08	5833.31
	VH	5728.93	5833.02
TH	VL	5728.66	5833.10
	VN	5728.46	5833.11
	VH	5728.79	5832.70
Limit	fH(5875MHz) - fL(5725MHz) = 150MHz		

802.11n40---Transmitter			
Test Conditions		Frequency (MHz) at -30dBm/30KHz	
Temperature	Voltage(V)	fL at Low Channel >5725MHz	fH at High Channel (<5875MHz)
TL	VL	5736.09	5812.81
	VN	5736.41	5813.25
	VH	5736.44	5812.77
TN	VL	5736.24	5813.20
	VN	5736.55	5813.36
	VH	5736.06	5813.09
TH	VL	5736.14	5813.12
	VN	5736.07	5812.74
	VH	5735.89	5813.22
Limit	fH(5875MHz) - fL(5725MHz) = 150MHz		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



802.11ac40---Transmitter			
Test Conditions		Frequency (MHz) at -30dBm/30KHz	
Temperature	Voltage(V)	fL at Low Channel >5725MHz	fH at High Channel (<5875MHz)
TL	VL	5735.86	5813.12
	VN	5736.23	5812.72
	VH	5736.36	5813.23
TN	VL	5736.19	5812.89
	VN	5736.55	5813.36
	VH	5735.93	5812.81
TH	VL	5736.38	5813.23
	VN	5736.21	5813.22
	VH	5735.95	5812.76
Limit	fH(5875MHz) - fL(5725MHz) = 150MHz		

802.11ac80---Transmitter			
Test Conditions		Frequency (MHz) at -30dBm/30KHz	
Temperature	Voltage(V)	fL at Low Channel >5725MHz	fH at High Channel (<5875MHz)
TL	VL	5735.58	5813.32
	VN	5735.68	5813.77
	VH	5735.58	5813.80
TN	VL	5735.69	5813.44
	VN	5736.12	5813.96
	VH	5735.50	5813.84
TH	VL	5735.42	5813.71
	VN	5735.89	5813.39
	VH	5735.91	5813.43
Limit	fH(5875MHz) - fL(5725MHz) = 150MHz		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



I.3 Unwanted Emissions in the Spurious Domain

Test Result of Unwanted Emissions In The Spurious Domain (802.11a)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
81.01	Vertical	-59.08	-36.00	Pass
284.16	V	-62.66	-36.00	
11490.00	V	-46.02	-30.00	
17235.00	V	-44.80	-30.00	
170.89	Horizontal	-60.27	-36.00	
535.66	H	-58.51	-54.00	
11490.00	H	-43.26	-30.00	
17235.00	H	-42.30	-30.00	
Middle Channel				
84.71	Vertical	-61.75	-36.00	Pass
297.35	V	-63.22	-36.00	
11570.00	V	-47.02	-30.00	
17355.00	V	-44.46	-30.00	
173.85	Horizontal	-60.41	-36.00	
528.28	H	-62.32	-54.00	
11570.00	H	-45.58	-30.00	
17355.00	H	-42.56	-30.00	
Highest Channel				
93.33	Vertical	-61.53	-54.00	Pass
278.88	V	-61.65	-36.00	
11650.00	V	-45.96	-30.00	
17475.00	V	-44.64	-30.00	
176.98	Horizontal	-58.20	-54.00	
561.13	H	-58.71	-54.00	
11650.00	H	-45.95	-30.00	
17475.00	H	-42.79	-30.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test Result of Unwanted Emissions In The Spurious Domain (802.11n20)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
83.02	Vertical	-57.61	-36.00	Pass
284.24	V	-60.22	-36.00	
11490.00	V	-46.02	-30.00	
17235.00	V	-44.09	-30.00	
168.14	Horizontal	-59.08	-36.00	
534.22	H	-58.97	-54.00	
11490.00	H	-44.32	-30.00	
17235.00	H	-42.17	-30.00	
Middle Channel				
86.00	Vertical	-62.21	-36.00	Pass
297.26	V	-62.63	-36.00	
11570.00	V	-45.70	-30.00	
17355.00	V	-46.36	-30.00	
172.65	Horizontal	-58.55	-36.00	
529.65	H	-62.15	-54.00	
11570.00	H	-45.07	-30.00	
17355.00	H	-44.16	-30.00	
Highest Channel				
88.81	Vertical	-59.82	-54.00	Pass
277.09	V	-62.63	-36.00	
11650.00	V	-45.86	-30.00	
17475.00	V	-44.72	-30.00	
172.72	Horizontal	-60.65	-36.00	
562.57	H	-58.40	-54.00	
11650.00	H	-44.35	-30.00	
17475.00	H	-44.23	-30.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test Result of Unwanted Emissions In The Spurious Domain (802.11ac20)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
84.00	Vertical	-58.88	-36.00	Pass
287.28	V	-60.99	-36.00	
11490.00	V	-47.73	-30.00	
17235.00	V	-45.87	-30.00	
169.70	Horizontal	-61.02	-36.00	
530.70	H	-59.67	-54.00	
11490.00	H	-45.15	-30.00	
17235.00	H	-43.42	-30.00	
Middle Channel				
84.08	Vertical	-60.36	-36.00	Pass
294.96	V	-64.85	-36.00	
11570.00	V	-47.41	-30.00	
17355.00	V	-44.09	-30.00	
172.53	Horizontal	-60.55	-36.00	
532.82	H	-60.91	-54.00	
11570.00	H	-43.89	-30.00	
17355.00	H	-43.16	-30.00	
Highest Channel				
90.57	Vertical	-60.63	-54.00	Pass
280.13	V	-61.83	-36.00	
11650.00	V	-44.44	-30.00	
17475.00	V	-43.53	-30.00	
174.31	Horizontal	-59.66	-54.00	
561.77	H	-59.82	-54.00	
11650.00	H	-47.44	-30.00	
17475.00	H	-44.93	-30.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test Result of Unwanted Emissions In The Spurious Domain (802.11n40)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
85.03	Vertical	-60.86	-36.00	Pass
298.24	V	-64.51	-36.00	
11510.00	V	-47.24	-30.00	
17265.00	V	-44.88	-30.00	
171.69	Horizontal	-58.34	-36.00	
536.57	H	-62.97	-54.00	
11510.00	H	-44.64	-30.00	
17265.00	H	-44.70	-30.00	
Highest Channel				
95.01	Vertical	-59.51	-54.00	Pass
278.82	V	-63.47	-36.00	
11590.00	V	-47.05	-30.00	
17385.00	V	-43.88	-30.00	
175.24	Horizontal	-59.69	-54.00	
565.94	H	-60.79	-54.00	
11590.00	H	-45.70	-30.00	
17385.00	H	-44.16	-30.00	





Test Result of Unwanted Emissions In The Spurious Domain (802.11ac40)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
89.35	Vertical	-59.52	-54.00	Pass
297.60	V	-62.80	-36.00	
11510.00	V	-44.50	-30.00	
17265.00	V	-46.41	-30.00	
168.93	Horizontal	-57.28	-36.00	
537.82	H	-62.42	-54.00	
11510.00	H	-46.14	-30.00	
17265.00	H	-42.90	-30.00	
Highest Channel				
90.74	Vertical	-60.10	-54.00	Pass
283.99	V	-63.02	-36.00	
11590.00	V	-45.96	-30.00	
17385.00	V	-44.36	-30.00	
177.55	Horizontal	-59.01	-54.00	
563.47	H	-59.52	-54.00	
11590.00	H	-45.07	-30.00	
17385.00	H	-43.96	-30.00	

Test Result of Unwanted Emissions In The Spurious Domain (802.11ac80)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
92.77	Vertical	-60.12	-54.00	Pass
281.29	V	-61.90	-36.00	
11550.00	V	-45.18	-30.00	
17325.00	V	-43.79	-30.00	
176.41	Horizontal	-58.22	-54.00	
565.09	H	-61.17	-54.00	
11550.00	H	-47.25	-30.00	
17325.00	H	-43.28	-30.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



I.4 Adjacent Channel Selectivity

Receiver category: 1								
Test Channel (Worst Case)		The signal of adjacent channel(signal generator B)						
		Adjacent channel		BW (MHz)	K (dB)	Test Value (dBm)	Limit (dBm)	Verdict
157	5785MHz	153	5765MHz(lower)	20	-28.26	-49.40	≥-58.26	Pass
		161	5805MHz(upper)	20	-28.26	-49.45	≥-58.26	Pass
151	5755MHz	/	5715MHz(lower)	40	-31.22	-59.48	≥-61.22	Pass
		159	5805MHz(upper)	40	-31.22	-59.40	≥-61.22	Pass

Note: The BW(channel bandwidth) is declared by the manufacturer of the equipment.





I.5 Blocking or Desensitization

Receiver category: 1									
Test Channel (Worst Case)		Lower or upper	Spacing	Frequency (MHz)	BW (MHz)	K (dB)	Test Value (dBm)	Limit (dBm)	Verdict
157	5785MHz	Lower	10*BW	5575	20	-28.26	-37.45	≥-58.26	Pass
			20*BW	5375	20	-28.26	-30.49	≥-58.26	Pass
			50*BW	4775	20	-28.26	-24.45	≥-58.26	Pass
		Upper	10*BW	5995	20	-28.26	-37.44	≥-58.26	Pass
			20*BW	6195	20	-28.26	-30.48	≥-58.26	Pass
			50*BW	6795	20	-28.26	-24.50	≥-58.26	Pass
151	5755MHz	Lower	10*BW	5325	40	-31.22	-37.47	≥-61.22	Pass
			20*BW	4925	40	-31.22	-30.41	≥-61.22	Pass
			50*BW	3725	40	-31.22	-24.46	≥-61.22	Pass
		Upper	10*BW	6175	40	-31.22	-37.49	≥-61.22	Pass
			20*BW	6575	40	-31.22	-30.48	≥-61.22	Pass
			50*BW	7775	40	-31.22	-24.44	≥-61.22	Pass

Note: The BW(channel bandwidth) is declared by the manufacturer of the equipment.





I.6 Spurious Radiations

Test Result of Spurious Radiations (802.11a)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
95.46	Vertical	-67.38	-57.00	Pass
746.33	V	-63.61	-57.00	
11490.00	V	-60.43	-47.00	
17235.00	V	-58.30	-47.00	
71.19	Horizontal	-67.06	-57.00	
157.74	H	-62.98	-57.00	
11490.00	H	-60.56	-47.00	
17235.00	H	-58.07	-47.00	
Middle Channel				
131.65	Vertical	-67.33	-57.00	Pass
564.85	V	-64.82	-57.00	
11570.00	V	-63.14	-47.00	
17355.00	V	-59.29	-47.00	
145.31	Horizontal	-68.69	-57.00	
609.51	H	-65.32	-57.00	
11570.00	H	-60.79	-47.00	
17355.00	H	-61.26	-47.00	
Highest Channel				
226.80	Vertical	-69.81	-57.00	Pass
786.83	V	-63.62	-57.00	
11650.00	V	-60.93	-47.00	
17475.00	V	-60.73	-47.00	
84.83	Horizontal	-67.53	-57.00	
464.82	H	-63.63	-57.00	
11650.00	H	-63.09	-47.00	
17475.00	H	-61.31	-47.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test Result of Spurious Radiations (802.11n20)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
92.63	Vertical	-66.90	-57.00	Pass
744.17	V	-65.03	-57.00	
11490.00	V	-63.13	-47.00	
17235.00	V	-61.11	-47.00	
76.08	Horizontal	-69.77	-57.00	
156.61	H	-63.43	-57.00	
11490.00	H	-60.41	-47.00	
17235.00	H	-60.12	-47.00	
Middle Channel				
131.97	Vertical	-69.64	-57.00	Pass
561.81	V	-63.33	-57.00	
11570.00	V	-60.54	-47.00	
17355.00	V	-59.88	-47.00	
148.20	Horizontal	-68.74	-57.00	
608.43	H	-62.66	-57.00	
11570.00	H	-61.22	-47.00	
17355.00	H	-59.62	-47.00	
Highest Channel				
225.09	Vertical	-69.83	-57.00	Pass
788.39	V	-65.72	-57.00	
11650.00	V	-61.97	-47.00	
17475.00	V	-61.17	-47.00	
83.22	Horizontal	-69.68	-57.00	
464.95	H	-62.38	-57.00	
11650.00	H	-61.32	-47.00	
17475.00	H	-59.55	-47.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test Result of Spurious Radiations (802.11ac20)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
95.76	Vertical	-66.80	-57.00	Pass
744.21	V	-64.32	-57.00	
11490.00	V	-61.97	-47.00	
17235.00	V	-58.11	-47.00	
74.80	Horizontal	-67.48	-57.00	
157.97	H	-64.83	-57.00	
11490.00	H	-62.06	-47.00	
17235.00	H	-58.81	-47.00	
Middle Channel				
133.81	Vertical	-68.97	-57.00	Pass
563.32	V	-65.11	-57.00	
11570.00	V	-62.71	-47.00	
17355.00	V	-61.42	-47.00	
148.12	Horizontal	-69.79	-57.00	
604.78	H	-64.19	-57.00	
11570.00	H	-63.43	-47.00	
17355.00	H	-59.35	-47.00	
Highest Channel				
224.73	Vertical	-69.00	-57.00	Pass
784.40	V	-65.42	-57.00	
11650.00	V	-61.62	-47.00	
17475.00	V	-59.11	-47.00	
84.45	Horizontal	-68.00	-57.00	
468.59	H	-64.81	-57.00	
11650.00	H	-62.46	-47.00	
17475.00	H	-60.17	-47.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test Result of Spurious Radiations (802.11n40)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
93.58	Vertical	-68.34	-57.00	Pass
745.02	V	-64.43	-57.00	
11510.00	V	-62.36	-47.00	
17265.00	V	-58.78	-47.00	
75.83	Horizontal	-68.28	-57.00	
157.63	H	-63.38	-57.00	
11510.00	H	-62.22	-47.00	
17265.00	H	-58.96	-47.00	
Highest Channel				
226.11	Vertical	-69.41	-57.00	Pass
788.39	V	-65.84	-57.00	
11590.00	V	-60.24	-47.00	
17385.00	V	-60.16	-47.00	
85.75	Horizontal	-67.49	-57.00	
469.63	H	-64.13	-57.00	
11590.00	H	-63.08	-47.00	
17385.00	H	-58.69	-47.00	





Test Result of Spurious Radiations (802.11ac40)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
Lowest Channel				
92.60	Vertical	-67.34	-57.00	Pass
743.81	V	-63.06	-57.00	
11510.00	V	-60.77	-47.00	
17265.00	V	-60.00	-47.00	
70.95	Horizontal	-67.31	-57.00	
154.10	H	-64.90	-57.00	
11510.00	H	-60.77	-47.00	
17265.00	H	-59.58	-47.00	
Highest Channel				
226.39	Vertical	-68.04	-57.00	Pass
786.81	V	-63.52	-57.00	
11590.00	V	-62.11	-47.00	
17385.00	V	-60.64	-47.00	
81.38	Horizontal	-68.42	-57.00	
464.71	H	-62.93	-57.00	
11590.00	H	-61.67	-47.00	
17385.00	H	-60.50	-47.00	

Test Result of Spurious Radiations (802.11ac80)				
Frequency (MHz)	Test Data		Limit (dBm)	Conclusion
	Polarization	Level (dBm)		
227.75	Vertical	-68.56	-57.00	Pass
785.94	V	-64.84	-57.00	
11550.00	V	-63.16	-47.00	
17325.00	V	-59.45	-47.00	
83.51	Horizontal	-68.11	-57.00	
466.71	H	-65.02	-57.00	
11550.00	H	-60.91	-47.00	
17325.00	H	-59.96	-47.00	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity