



RADIO TEST REPORT

For

Shenzhen Huafurui Technology Co., Ltd.

Smartphone

Test Model: NOTE 50

Prepared for : Shenzhen Huafurui Technology Co., Ltd.
Address : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 15, 2023
Number of tested samples : 2
Serial number : Prototype
Date of Test : May 15, 2023 ~ June 05, 2023
Date of Report : June 07, 2023



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel: + (86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



RADIO TEST REPORT	
ETSI EN 301 908-1 V15.2.1 (2023-01) & ETSI EN 301 908-13 V13.2.1 (2022-02)	
Report Reference No.	LCSA051523066EJ
Date of Issue.....	June 07, 2023
Testing Laboratory Name.....	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address.....	Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Testing Location/ Procedure....	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name.....	Shenzhen Huafurui Technology Co., Ltd.
Address.....	Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China
Test Specification	
Standard.....	ETSI EN 301 908-1 V15.2.1 (2023-01) ETSI EN 301 908-13 V13.2.1 (2022-02)
Test Report Form No.....	LCSEMC-1.0
TRF Originator.....	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	Dated 2017-06
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description..... : Smartphone	
Trade Mark.....	CUBOT
Test Model.....	NOTE 50
Ratings	Input: 5.0V=2.0A For AC Adapter Input: 100-240V~, 50/60Hz, 0.3A Adapter Output: 5.0V=2.0A, 10.0W DC 3.87V by Rechargeable Li-ion Battery, 5200mAh
Result	Positive

Compiled by:

Kevin Huang

Supervised by:

Cary Luo

Approved by:

Gavin Liang

Kevin Huang/ Administrator

Cary Luo/ Technique principal

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



RADIO -- TEST REPORT

Test Report No. : LCSA051523066EJ	June 07, 2023 Date of issue
-----------------------------------	--------------------------------

Test Model..... : NOTE 50

EUT..... : Smartphone

Applicant..... : Shenzhen Huafurui Technology Co., Ltd.

Address..... : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Telephone..... : /

Fax..... : /

Manufacturer..... : Shenzhen Huafurui Technology Co., Ltd.

Address..... : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Telephone..... : /

Fax..... : /

Factory..... : Shenzhen Huafurui Technology Co., Ltd.

Address..... : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Telephone..... : /

Fax..... : /

Test Result	Positive
-------------	----------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	June 07, 2023	Initial Issue	---



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street,
Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2. SUPPORT EQUIPMENT LIST	9
1.3. EXTERNAL I/O	9
1.4. OBJECTIVE	9
1.5. TEST CONDITIONS	9
1.6. DESCRIPTION OF TEST MODE	10
1.7. MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	10
1.8. DESCRIPTION OF TEST FACILITY	10
2. SYSTEM TEST CONFIGURATION	11
2.1. JUSTIFICATION	11
2.2. EUT EXERCISE SOFTWARE	11
2.3. SPECIAL ACCESSORIES	11
2.4. BLOCK DIAGRAM/SCHEMATICS	11
2.5. EQUIPMENT MODIFICATIONS	11
2.6. TEST SETUP	11
3. SUMMARY OF TEST RESULTS	12
4. LIST OF MEASURING EQUIPMENT	15
5. PHOTOGRAPHS OF TEST SETUP	16
6. PHOTOGRAPHS OF THE EUT	16





1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT	: Smartphone
Test Model	: NOTE 50
Power Supply	: Input: 5.0V \pm 2.0A For AC Adapter Input: 100-240V~, 50/60Hz, 0.3A Adapter Output: 5.0V \pm 2.0A, 10.0W DC 3.87V by Rechargeable Li-ion Battery, 5200mAh
Hardware Version	: G2233G-UF-V1.1
Software Version	: CUBOT_NOTE_50_D041C_V1.0
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (BDR/EDR) 40 channels for Bluetooth V5.0 (BT LE)
Channel Spacing	: 1MHz for Bluetooth V5.0 (BDR/EDR) 2MHz for Bluetooth V5.0 (BT LE)
Modulation Type	: GFSK, π /4-DQPSK, 8-DPSK for Bluetooth V5.0 (BDR/EDR) GFSK for Bluetooth V5.0 (BT LE)
Bluetooth Version	: V5.0
Antenna Description	: PIFA Antenna, 2.63dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2472MHz
Channel Spacing	: 5MHz
Channel Number	: 13 Channel for 20MHz bandwidth(2412~2472MHz)
Modulation Type	: 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 2.63dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 channels for 20MHz bandwidth(5180~5240MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 1.74dBi(Max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745~5825MHz)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



2 channels for 40MHz bandwidth(5755~5795MHz)	
1 channels for 80MHz bandwidth(5775MHz)	
Modulation Type	: 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 1.74dBi(Max.)
2G	:
Support Band	: <input checked="" type="checkbox"/> GSM 900 (EU-Band) <input checked="" type="checkbox"/> DCS 1800 (EU-Band)
Release Version	: R99
GPRS Class	: Class 12
EGPRS Class	: Class 12
Uplink	: GSM 900: 880MHz~915MHz DCS 1800: 1710MHz~1785MHz
Downlink	: GSM 900: 925MHz~960MHz DCS 1800: 1805MHz~1880MHz
Type Of Modulation	: GMSK for GSM/GPRS; GMSK/8PSK for EGPRS
Antenna Description	: PIFA Antenna -3.38dBi (max.) For GSM 900 -0.49dBi (max.) For DCS 1800
Power Class	: GSM 900: Level 5, DCS 1800: Level 0 EGPRS 900: Level 8, EGPRS 1800: Level 2
3G	:
Support Band	: <input checked="" type="checkbox"/> WCDMA Band I (EU-Band) <input checked="" type="checkbox"/> WCDMA Band VIII (EU-Band)
Release Version	: R8
Uplink	: WCDMA Band I: 1920MHz~1980MHz WCDMA Band VIII: 880MHz~915MHz
Downlink	: WCDMA Band I: 2110MHz~2170MHz WCDMA Band VIII: 925MHz~960MHz
Type Of Modulation	: QPSK/16QAM
Antenna Description	: PIFA Antenna -3.71dBi (max.) For WCDMA Band I -3.38dBi (max.) For WCDMA Band VIII
Power Class	: Level 3
LTE	:
Support Band	: <input checked="" type="checkbox"/> E-UTRA Band 1(EU-Band) <input checked="" type="checkbox"/> E-UTRA Band 3(EU-Band) <input checked="" type="checkbox"/> E-UTRA Band 7(EU-Band) <input checked="" type="checkbox"/> E-UTRA Band 8(EU-Band) <input checked="" type="checkbox"/> E-UTRA Band 20(EU-Band) <input checked="" type="checkbox"/> E-UTRA Band 38(EU-Band) <input checked="" type="checkbox"/> E-UTRA Band 40(EU-Band)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity





LTE Release Version : R9

FDD Band : Uplink: E-UTRA Band 1: 1920MHz~1980MHz
E-UTRA Band 3: 1710MHz~1785MHz
E-UTRA Band 7: 2500MHz~2570MHz
E-UTRA Band 8: 880MHz~915MHz
E-UTRA Band 20: 832MHz~862MHz
Downlink: E-UTRA Band 1: 2110MHz~2170MHz
E-UTRA Band 3: 1805MHz~1880MHz
E-UTRA Band 7: 2620MHz~2690MHz
E-UTRA Band 8: 925MHz~960MHz
E-UTRA Band 20: 791MHz~821MHz
TDD Band : E-UTRA Band 38: 2570MHz~2620MHz
E-UTRA Band 40: 2300MHz~2400MHz

Type Of Modulation : QPSK/16QAM

Antenna Description : PIFA Antenna
-3.71dBi (max.) For E-UTRA Band 1
-1.05dBi (max.) For E-UTRA Band 3
-0.80dBi (max.) For E-UTRA Band 7
-3.38dBi (max.) For E-UTRA Band 8
-1.60dBi (max.) For E-UTRA Band 20
-0.80dBi (max.) For E-UTRA Band 38
1.65dBi (max.) For E-UTRA Band 40

Power Class : Class 3

GPS Receiver :

Receive Frequency : 1575.42MHz

Channel Number : 1

Antenna Description : PIFA Antenna, 0.77dBi(Max.)

BDS Receiver :

Receive Frequency : 1561.098MHz

Channel Number : 1

Antenna Description : PIFA Antenna, 0.77dBi(Max.)

NFC :

Frequency Range : 13.56MHz

Modulation Type : ASK

Antenna Description : PIFA Antenna, 0dBi(Max.)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
ShenZhen HuaJin Electronics CO., LTD	AC Power Adapter	HJ-0502000W 2-EU	---	CE

1.3. External I/O

I/O Port Description	Quantity	Cable
Type-C USB Port	1	USB Cable: 1.0m, unshielded

1.4. Objective

Standard Referenced	Standard Title	Standard Version
ETSI EN 301 908-1	IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements; Release 15	V15.2.1 (2023-01)
ETSI EN 301 908-13	IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)	V13.2.1 (2022-02)
ETSI TS 136 521-1	LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing (3GPP TS 36.521-1 version 16.9.0 Release 16)	V16.9.0 (2021-03)

The objective is to determine compliance with ETSI EN 301 908-1 V15.2.1 (2023-01) & ETSI EN 301 908-13 V13.2.1 (2022-02).

1.5. Test Conditions

Conditions	Temperature	Voltage
Normal	21-25°C	DC 3.87V
Low extreme Temperature/Low extreme Voltage (TL/VL);	-20°C	DC 3.48V
Low extreme Temperature/High extreme Voltage (TL/VH);	-20°C	DC 4.45V
High extreme Temperature/Low extreme Voltage (TH/VL);	45°C	DC 3.48V
High extreme Temperature/High extreme Voltage (TH/VH).	45°C	DC 4.45V

Note1: For all conditions, the humidity range is: 40-75%, the pressure range is 86-106kPa. The High Voltage DC 4.45V and Low Voltage DC 3.48V was declared by manufacturer

Note2: Test Model narrower than 72 mm, so TRS/ TRP exempt from the test.





1.6. Description Of Test Mode

The following operating modes were applied for the related test items. For radiated measurement, the test was performed with EUT in X, Y, Z position and the worse case was found when EUT in Y position. All test modes were tested, only the result of the worst case was recorded in the report.

Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
	1.4	3	5	10	15	20	QPSK	16QAM	1	Part	Full	L	M	H
1	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
3	Y	/	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
7	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
8	Y	/	Y	Y	N/A	N/A	Y	Y	Y	Y	Y	Y	Y	Y
20	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
38	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y
40	N/A	N/A	Y	/	/	Y	Y	Y	Y	Y	Y	Y	Y	Y

Note:

- 1)The mark “Y” means that this configuration is chosen for testing.
- 2)The mark “/” means that this bandwidth is supported but is not chosen for testing.
- 3)The mark “N/A” means that this bandwidth is not supported.

1.7. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Radio Frequency	0.9×10^{-4}
Total RF Power, Conducted	1.0 dB
RF Power Density, Conducted	1.8 dB
Spurious Emissions, Conducted	1.8 dB
All Emissions, Radiated	3.1 dB
Temperature	0.5°C
Humidity	1 %
DC And Low Frequency Voltages	1 %

1.8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street,
Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



2. SYSTEM TEST CONFIGURATION

2.1. Justification

N/A

2.2. EUT Exercise Software

N/A

2.3. Special Accessories

The special accessories were supplied by Shenzhen LCS Compliance Testing Laboratory Ltd.

2.4. Block Diagram/Schematics

Please refer to the related document.

2.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

2.6. Test Setup

Please refer to the test setup photo.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3. SUMMARY OF TEST RESULTS

Test Engineer	:	Taylor Hu
Temperature/ Humidity:	:	24.3°C/ 54.4%

Reference Clause No. (ETSI EN 301 908-13)	Description of Test Items	Result				
		E-UTRA Band				
		Band 1	Band 3	Band 7	Band 8	Band 20
4.2.2	Transmitter Maximum Output Power					
	Normal	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass
4.2.5	Transmitter Minimum Output Power					
	Normal	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass
4.2.3	Transmitter Spectrum Emission Mask					
	Normal	Pass	Pass	Pass	Pass	Pass
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio					
	Normal	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass
4.2.4	Transmitter Spurious Emissions					
	Normal	Pass	Pass	Pass	Pass	Pass
4.2.10	Receiver Spurious Emissions					
	Normal	Pass	Pass	Pass	Pass	Pass
4.2.6	Receiver Adjacent Channel Selectivity (ACS)					
	Normal	Pass	Pass	Pass	Pass	Pass
4.2.7	Receiver Blocking Characteristics					
	Normal	Pass	Pass	Pass	Pass	Pass
4.2.8	Receiver Spurious Response					
	Normal	Pass	Pass	Pass	Pass	Pass
4.2.9	Receiver Intermodulation Characteristics					
	Normal	Pass	Pass	Pass	Pass	Pass



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4.2.12	Receiver Reference Sensitivity Level					
	Normal	Pass	Pass	Pass	Pass	Pass
	TL/VL	Pass	Pass	Pass	Pass	Pass
	TL/VH	Pass	Pass	Pass	Pass	Pass
	TH/VL	Pass	Pass	Pass	Pass	Pass
	TH/VH	Pass	Pass	Pass	Pass	Pass

Reference Clause No. (ETSI EN 301 908-1)	Description of Test Items	Result				
		E-UTRA Band				
		Band 1	Band 3	Band 7	Band 8	Band 20
4.2.2	Radiated emissions (UE)					
	Normal	Pass	Pass	Pass	Pass	Pass
4.2.4	Control and monitoring functions (UE)					
	Normal	Pass	Pass	Pass	Pass	Pass

Reference Clause No. (ETSI EN 301 908-13)	Description of Test Items	Result	
		E-UTRA Band	
		Band 38	Band 40
4.2.2	Transmitter Maximum Output Power		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
4.2.5	Transmitter Minimum Output Power		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
4.2.3	Transmitter Spectrum Emission Mask		
	Normal	Pass	Pass
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
4.2.4	Transmitter Spurious Emissions		
	Normal	Pass	Pass
4.2.10	Receiver Spurious Emissions		





	Normal	Pass	Pass
4.2.6	Receiver Adjacent Channel Selectivity (ACS)		
	Normal	Pass	Pass
4.2.7	Receiver Blocking Characteristics		
	Normal	Pass	Pass
4.2.8	Receiver Spurious Response		
	Normal	Pass	Pass
4.2.9	Receiver Intermodulation Characteristics		
	Normal	Pass	Pass
4.2.12	Receiver Reference Sensitivity Level		
	Normal	Pass	Pass
	TL/VL	Pass	Pass
	TL/VH	Pass	Pass
	TH/VL	Pass	Pass
	TH/VH	Pass	Pass
4.2.2	Radiated emissions (UE)		
	Normal	Pass	Pass
4.2.4	Control and monitoring functions (UE)		
	Normal	Pass	Pass

Reference Clause No. (ETSI EN 301 908-1)	Description of Test Items	Result	
		E-UTRA Band	
		Band 38	Band 40
4.2.2	Radiated emissions (UE)		
	Normal	Pass	Pass
4.2.4	Control and monitoring functions (UE)		
	Normal	Pass	Pass

***Note:

Result: Describes test result of Test Case.

Pass: Test Case passed on specified conformance test platform.

Normal(TN/VN): Normal temperature – 25°C; Normal voltage. – DC 3.87V

TH: High extreme Temperature – +45°C

VH: High extreme Voltage – DC 4.45V

TL: Low extreme Temperature – -20°C

VL: Low extreme Voltage – DC 3.48V

N/A: Not applicable.

—: Not test.





4. LIST OF MEASURING EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
2	RF Control Unit	Tonscend	JS0806-1	158060009	2022-10-29	2023-10-28
3	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2022-10-29	2023-10-28
4	DC Power Supply	Agilent	E3642A	N/A	2022-10-29	2023-10-28
5	MXG Vector Signal Generator	Agilent	N5182A	MY47071151	2022-06-16	2023-06-15
6	PSG Analog Signal Generator	Agilent	E8257D	MY4520521	2022-06-16	2023-06-15
7	Temperature & Humidity Chamber	GUANGZHOU GOGN WEN	GDS-100	70932	2022-10-06	2023-10-05
8	EMI Test Software	Farad	EZ	/	N/A	N/A
9	3m Full Anechoic Chamber	MRDIANZI	FAC-3M	MR009	2021-09-25	2024-09-24
10	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2021-08-29	2024-08-28
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2021-08-29	2024-08-28
15	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2022-06-16	2023-06-15
16	EMI Test Receiver	R&S	ESR 7	101181	2022-06-16	2023-06-15
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2022-10-29	2023-10-28
18	Broadband Preamplifier	/	BP-01M18G	P190501	2022-06-16	2023-06-15
19	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2022-06-16	2023-06-15
20	RF Filter	Micro-Tronics	BRC50718	017	2022-10-29	2023-10-28
21	RF Filter	Micro-Tronics	BRC50719	011	2022-10-29	2023-10-28
22	RF Filter	Micro-Tronics	BRC50720	011	2022-10-29	2023-10-28
23	RF Filter	Micro-Tronics	BRC50721	013	2022-10-29	2023-10-28
24	RF Filter	Micro-Tronics	BRM50702	195	2022-08-17	2023-08-16
25	6dB Attenuator	/	100W/6dB	1172040	2022-06-16	2023-06-15
26	3dB Attenuator	/	2N-3dB	/	2022-10-29	2023-10-28





5. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix D for Photographs of Test Setup_RF.

6. PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix C for Photographs of The EUT.





Annex A

Transmitter maximum output power

The Conducted Power Measurement Result for LTE Band					
Test Result for LTE Band 1					
Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Average Power (dBm, 16QAM)
		RB Size	RB Offset		
5MHz	Low Range	1	0	23.58	22.92
			max	23.45	22.69
		Partial	0	23.56	22.83
			max	23.41	22.70
	Mid Range	1	0	23.57	22.88
			max	23.67	23.04
		Partial	0	23.64	22.84
			max	23.73	23.02
	High Range	1	0	23.56	22.87
			max	23.48	22.85
		Partial	0	23.50	22.75
			max	23.45	22.71
20MHz	Low Range	1	0	23.61	22.91
			max	23.43	22.76
		Partial	0	23.39	22.64
			max	23.35	22.66
	Mid Range	1	0	23.58	22.90
			max	23.93	23.20
		Partial	0	23.40	22.73
			max	23.79	23.09
	High Range	1	0	23.49	22.72
			max	23.24	22.57
		Partial	0	23.77	23.17
			max	23.39	22.64





The Conducted Power Measurement Result for LTE Band					
Test Result for LTE Band 3					
Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Average Power (dBm, 16QAM)
		RB Size	RB Offset		
1.4MHz	Low Range	1	0	23.10	22.41
			max	23.11	22.45
		Partial	0	23.18	22.50
			max	23.17	22.46
	Mid Range	1	0	22.85	22.15
			max	22.82	22.19
		Partial	0	22.96	22.22
			max	22.94	22.14
	High Range	1	0	22.30	21.63
			max	22.33	21.62
		Partial	0	22.37	21.64
			max	22.41	21.77
5MHz	Low Range	1	0	23.23	22.61
			max	23.20	22.45
		Partial	0	23.19	22.50
			max	23.22	22.54
	Mid Range	1	0	23.04	22.40
			max	23.06	22.28
		Partial	0	22.89	22.23
			max	22.88	22.08
	High Range	1	0	22.49	21.85
			max	22.34	21.72
		Partial	0	22.41	21.68
			max	22.38	21.61
20MHz	Low Range	1	0	23.36	22.68
			max	23.30	22.70
		Partial	0	23.21	22.50
			max	23.05	22.37
	Mid Range	1	0	23.19	22.43
			max	23.02	22.41
		Partial	0	23.08	22.38
			max	22.95	22.27
	High Range	1	0	23.08	22.30
			max	22.82	22.18
		Partial	0	23.00	22.30
			max	22.59	21.92



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 7

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Average Power (dBm, 16QAM)
		RB Size	RB Offset		
5MHz	Low Range	1	0	21.83	21.12
			max	21.75	21.06
		Partial	0	21.80	21.14
			max	21.74	20.99
	Mid Range	1	0	21.78	21.22
			max	21.92	21.09
		Partial	0	21.71	20.98
			max	21.85	21.18
	High Range	1	0	21.80	20.98
			max	21.55	20.88
		Partial	0	21.93	21.19
			max	21.81	21.10
20MHz	Low Range	1	0	21.20	20.47
			max	21.92	21.25
		Partial	0	21.83	21.12
			max	21.52	20.81
	Mid Range	1	0	21.15	20.49
			max	21.39	20.74
		Partial	0	21.75	21.04
			max	21.76	21.02
	High Range	1	0	21.21	20.58
			max	21.06	20.36
		Partial	0	21.91	21.08
			max	21.90	21.19





The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 8

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Average Power (dBm, 16QAM)
		RB Size	RB Offset		
1.4MHz	Low Range	1	0	23.87	23.16
			max	23.84	23.20
		Partial	0	23.95	23.20
			max	24.02	23.24
	Mid Range	1	0	24.10	23.36
			max	24.07	23.42
		Partial	0	24.16	23.39
			max	24.17	23.32
	High Range	1	0	23.71	23.00
			max	23.69	23.01
		Partial	0	23.77	23.07
			max	23.81	22.99
5MHz	Low Range	1	0	24.57	23.86
			max	24.48	23.74
		Partial	0	24.52	23.84
			max	24.56	23.91
	Mid Range	1	0	24.43	23.71
			max	24.36	23.69
		Partial	0	24.41	23.66
			max	24.47	23.75
	High Range	1	0	24.46	23.84
			max	24.42	23.74
		Partial	0	24.30	23.64
			max	24.30	23.61
10MHz	Low Range	1	0	24.39	23.69
			max	24.33	23.67
		Partial	0	24.43	23.74
			max	24.54	23.80
	Mid Range	1	0	24.47	23.76
			max	24.30	23.57
		Partial	0	24.46	23.62
			max	24.37	23.62
	High Range	1	0	24.39	23.63
			max	24.16	23.48
		Partial	0	24.46	23.69
			max	24.36	23.71



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 20

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Average Power (dBm, 16QAM)
		RB Size	RB Offset		
5MHz	Low Range	1	0	22.03	21.36
			max	21.98	21.26
		Partial	0	21.49	20.79
			max	21.69	21.05
	Mid Range	1	0	21.73	21.10
			max	21.74	21.00
		Partial	0	21.49	20.76
			max	21.53	20.84
	High Range	1	0	22.32	21.62
			max	22.25	21.54
		Partial	0	21.44	20.73
			max	21.34	20.62
20MHz	Low Range	1	0	24.44	23.68
			max	24.40	23.77
		Partial	0	24.39	23.69
			max	24.22	23.54
	Mid Range	1	0	24.70	23.98
			max	24.50	23.88
		Partial	0	24.36	23.66
			max	24.35	23.61
	High Range	1	0	24.12	23.37
			max	23.92	23.22
		Partial	0	24.35	23.64
			max	24.12	23.39





The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 38

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Average Power (dBm, 16-QAM)
		RB Size	RB Offset		
5MHz	Low Range	1	0	21.12	20.38
			max	21.01	20.44
		Partial	0	21.13	20.42
			max	21.11	20.47
	Mid Range	1	0	20.84	20.31
			max	20.99	20.35
		Partial	0	20.89	20.36
			max	21.03	20.35
	High Range	1	0	21.21	20.50
			max	21.04	20.39
		Partial	0	21.27	20.60
			max	21.17	20.60
20MHz	Low Range	1	0	20.97	20.36
			max	20.81	20.32
		Partial	0	21.04	20.35
			max	20.85	20.33
	Mid Range	1	0	21.38	20.67
			max	21.05	20.35
		Partial	0	20.98	20.31
			max	20.66	20.33
	High Range	1	0	20.93	20.37
			max	20.80	20.31
		Partial	0	20.77	20.34
			max	20.68	20.36





The Conducted Power Measurement Result for LTE Band

Test Result for LTE Band 40

Channel Bandwidth	Channel	RB Allocation		Average Power (dBm, QPSK)	Average Power (dBm, 16-QAM)
		RB Size	RB Offset		
5MHz	Low Range	1	0	21.05	20.36
			max	21.07	20.34
		Partial	0	21.79	21.12
			max	21.78	21.03
	Mid Range	1	0	21.81	21.16
			max	21.89	21.13
		Partial	0	21.64	20.97
			max	21.63	20.87
	High Range	1	0	21.00	20.38
			max	21.04	20.38
		Partial	0	21.61	20.82
			max	21.75	20.91
20MHz	Low Range	1	0	21.97	21.24
			max	21.01	20.37
		Partial	0	21.73	21.05
			max	21.71	21.05
	Mid Range	1	0	21.09	20.35
			max	21.14	20.37
		Partial	0	21.65	20.82
			max	21.75	21.08
	High Range	1	0	21.95	21.18
			max	21.93	21.21
		Partial	0	21.81	21.03
			max	21.68	20.86





Annex of Radiated spurious emission

Radiated spurious emissions - MS allocated a channel(Worst Case)

LTE Band 1(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.60	Horizontal	-76.13	-36.00	Pass
949.34	H	-73.55	-36.00	
3905.86	H	-68.05	-30.00	
5850.45	H	-54.87	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.56	Vertical	-76.29	-36.00	Pass
823.09	V	-77.36	-36.00	
3904.95	V	-69.15	-30.00	
5855.99	V	-59.45	-30.00	

LTE Band 1(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.07	Horizontal	-78.17	-36.00	Pass
830.67	H	-79.00	-36.00	
3901.88	H	-69.13	-30.00	
5854.77	H	-50.83	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.09	Vertical	-74.94	-36.00	Pass
771.28	V	-80.19	-36.00	
3904.12	V	-65.52	-30.00	
5854.65	V	-53.21	-30.00	





LTE Band 1(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.57	Horizontal	-73.77	-36.00	Pass
807.66	H	-77.60	-36.00	
3905.81	H	-61.41	-30.00	
5852.35	H	-50.05	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.66	Vertical	-71.77	-36.00	Pass
753.42	V	-72.95	-36.00	
3903.15	V	-60.54	-30.00	
5851.01	V	-52.86	-30.00	

LTE Band 1(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.79	Horizontal	-73.32	-36.00	Pass
978.30	H	-71.08	-36.00	
3903.11	H	-64.21	-30.00	
5850.83	H	-55.58	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.57	Vertical	-80.42	-36.00	Pass
938.71	V	-71.90	-36.00	
3905.22	V	-64.01	-30.00	
5855.67	V	-55.24	-30.00	





LTE Band 3(1.4MHz, RB allocation=6): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.67	Horizontal	-70.82	-36.00	Pass
700.31	H	-78.64	-36.00	
3502.85	H	-67.73	-30.00	
5253.66	H	-53.58	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.95	Vertical	-78.77	-36.00	Pass
915.57	V	-70.59	-36.00	
3500.40	V	-61.98	-30.00	
5252.56	V	-52.75	-30.00	

LTE Band 3(1.4MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.96	Horizontal	-74.50	-36.00	Pass
870.29	H	-70.88	-36.00	
3504.38	H	-61.09	-30.00	
5253.01	H	-59.66	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.24	Vertical	-78.38	-36.00	Pass
897.23	V	-71.27	-36.00	
3500.71	V	-65.99	-30.00	
5251.06	V	-55.04	-30.00	





LTE Band 3(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.48	Horizontal	-77.52	-36.00	Pass
917.96	H	-71.83	-36.00	
3501.67	H	-67.26	-30.00	
5255.54	H	-57.04	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.69	Vertical	-80.66	-36.00	Pass
933.51	V	-76.09	-36.00	
3505.87	V	-65.59	-30.00	
5253.15	V	-50.63	-30.00	

LTE Band 3(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.38	Horizontal	-71.90	-36.00	Pass
944.65	H	-71.09	-36.00	
3501.88	H	-62.21	-30.00	
5255.37	H	-53.30	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.29	Vertical	-76.21	-36.00	Pass
921.98	V	-72.71	-36.00	
3505.05	V	-70.59	-30.00	
5254.71	V	-54.40	-30.00	





LTE Band 3(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.76	Horizontal	-78.51	-36.00	Pass
844.17	H	-75.55	-36.00	
3502.91	H	-60.87	-30.00	
5252.76	H	-54.59	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.60	Vertical	-71.73	-36.00	Pass
732.65	V	-70.33	-36.00	
3501.40	V	-60.03	-30.00	
5253.99	V	-60.51	-30.00	

LTE Band 3(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.03	Horizontal	-78.56	-36.00	Pass
732.00	H	-78.81	-36.00	
3505.67	H	-64.40	-30.00	
5255.06	H	-53.44	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.90	Vertical	-75.84	-36.00	Pass
904.46	V	-75.87	-36.00	
3503.68	V	-66.79	-30.00	
5251.39	V	-53.63	-30.00	





LTE Band 7(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.30	Horizontal	-73.81	-36.00	Pass
746.26	H	-77.56	-36.00	
5071.88	H	-62.60	-30.00	
7687.98	H	-60.02	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.37	Vertical	-73.51	-36.00	Pass
996.74	V	-74.43	-36.00	
5074.88	V	-66.05	-30.00	
7689.14	V	-54.97	-30.00	

LTE Band 7(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.13	Horizontal	-80.88	-36.00	Pass
758.38	H	-75.50	-36.00	
5072.17	H	-60.66	-30.00	
7687.04	H	-51.44	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.07	Vertical	-74.56	-36.00	Pass
969.37	V	-78.66	-36.00	
5071.63	V	-65.46	-30.00	
7690.40	V	-53.97	-30.00	





LTE Band 7(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.14	Horizontal	-79.50	-36.00	Pass
774.66	H	-79.65	-36.00	
5071.07	H	-68.54	-30.00	
7689.74	H	-56.10	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.12	Vertical	-78.12	-36.00	Pass
733.05	V	-71.22	-36.00	
5072.97	V	-61.73	-30.00	
7688.28	V	-50.86	-30.00	

LTE Band 7(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.79	Horizontal	-72.65	-36.00	Pass
905.13	H	-80.15	-36.00	
5075.91	H	-70.46	-30.00	
7688.21	H	-56.43	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.65	Vertical	-79.55	-36.00	Pass
880.04	V	-72.75	-36.00	
5070.53	V	-66.90	-30.00	
7685.02	V	-52.95	-30.00	





LTE Band 8(1.4MHz, RB allocation=6): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.04	Horizontal	-76.70	-36.00	Pass
833.75	H	-80.46	-36.00	
1796.28	H	-64.77	-30.00	
2691.53	H	-55.70	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.81	Vertical	-76.27	-36.00	Pass
954.17	V	-73.21	-36.00	
1800.12	V	-60.47	-30.00	
2690.34	V	-59.89	-30.00	

LTE Band 8(1.4MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.67	Horizontal	-80.77	-36.00	Pass
856.72	H	-79.69	-36.00	
1790.53	H	-62.01	-30.00	
2694.09	H	-52.77	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.08	Vertical	-78.13	-36.00	Pass
793.85	V	-74.80	-36.00	
1795.98	V	-68.60	-30.00	
2694.53	V	-59.26	-30.00	





LTE Band 8(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.64	Horizontal	-73.24	-36.00	Pass
743.06	H	-80.59	-36.00	
1795.85	H	-62.15	-30.00	
2695.07	H	-56.72	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.57	Vertical	-72.71	-36.00	Pass
758.06	V	-78.24	-36.00	
1798.79	V	-63.84	-30.00	
2690.43	V	-52.92	-30.00	

LTE Band 8(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
52.39	Horizontal	-71.16	-36.00	Pass
953.18	H	-79.42	-36.00	
1796.94	H	-65.92	-30.00	
2694.14	H	-56.96	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.98	Vertical	-71.86	-36.00	Pass
914.08	V	-75.02	-36.00	
1793.64	V	-67.90	-30.00	
2695.61	V	-52.44	-30.00	





LTE Band 8(10MHz, RB allocation=50): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.73	Horizontal	-79.82	-36.00	Pass
711.90	H	-71.06	-36.00	
1797.00	H	-63.51	-30.00	
2691.33	H	-60.76	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.46	Vertical	-70.92	-36.00	Pass
746.07	V	-70.10	-36.00	
1794.86	V	-67.83	-30.00	
2691.29	V	-51.48	-30.00	

LTE Band 8(10MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
57.34	Horizontal	-80.22	-36.00	Pass
986.88	H	-76.78	-36.00	
1793.30	H	-63.69	-30.00	
2691.36	H	-54.71	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.36	Vertical	-77.74	-36.00	Pass
701.06	V	-73.08	-36.00	
1790.77	V	-65.64	-30.00	
2690.43	V	-54.01	-30.00	





LTE Band 20(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
51.66	Horizontal	-76.80	-36.00	Pass
745.33	H	-74.09	-36.00	
1694.43	H	-61.15	-30.00	
2544.30	H	-60.76	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.03	Vertical	-77.18	-36.00	Pass
759.67	V	-78.89	-36.00	
1700.98	V	-64.44	-30.00	
2543.97	V	-59.23	-30.00	

LTE Band 20(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.36	Horizontal	-74.66	-36.00	Pass
746.75	H	-79.68	-36.00	
1700.42	H	-64.22	-30.00	
2543.13	H	-55.45	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.44	Vertical	-78.96	-36.00	Pass
712.31	V	-71.16	-36.00	
1691.76	V	-63.68	-30.00	
2543.68	V	-56.91	-30.00	





LTE Band 20(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
59.67	Horizontal	-73.26	-36.00	Pass
867.26	H	-71.74	-36.00	
1693.80	H	-64.28	-30.00	
2541.72	H	-54.74	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.37	Vertical	-80.18	-36.00	Pass
844.11	V	-72.69	-36.00	
1692.42	V	-61.51	-30.00	
2542.29	V	-60.85	-30.00	

LTE Band 20(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.22	Horizontal	-75.56	-36.00	Pass
808.12	H	-74.31	-36.00	
1693.66	H	-70.83	-30.00	
2540.78	H	-52.52	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.54	Vertical	-78.70	-36.00	Pass
711.80	V	-76.81	-36.00	
1690.97	V	-67.79	-30.00	
2543.39	V	-58.05	-30.00	





LTE Band 38(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.30	Horizontal	-79.65	-36.00	Pass
801.91	H	-71.08	-36.00	
5193.84	H	-60.87	-30.00	
7794.19	H	-50.03	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.78	Vertical	-75.61	-36.00	Pass
844.59	V	-74.58	-36.00	
5190.29	V	-63.90	-30.00	
7792.51	V	-56.75	-30.00	

LTE Band 38(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.91	Horizontal	-78.20	-36.00	Pass
939.97	H	-77.62	-36.00	
5195.32	H	-65.94	-30.00	
7795.44	H	-60.75	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
60.08	Vertical	-78.97	-36.00	Pass
812.86	V	-78.57	-36.00	
5193.56	V	-67.05	-30.00	
7792.86	V	-55.89	-30.00	





LTE Band 38(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.23	Horizontal	-71.25	-36.00	Pass
890.70	H	-80.33	-36.00	
5190.00	H	-66.12	-30.00	
7790.12	H	-57.42	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
55.86	Vertical	-73.14	-36.00	Pass
826.44	V	-74.85	-36.00	
5192.45	V	-61.99	-30.00	
7790.55	V	-50.41	-30.00	

LTE Band 38(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.85	Horizontal	-75.99	-36.00	Pass
880.51	H	-80.75	-36.00	
5191.65	H	-62.67	-30.00	
7791.57	H	-56.86	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.13	Vertical	-78.79	-36.00	Pass
716.39	V	-80.25	-36.00	
5190.64	V	-62.74	-30.00	
7795.19	V	-56.65	-30.00	





LTE Band 40(5MHz, RB allocation=25): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.06	Horizontal	-75.50	-36.00	Pass
884.67	H	-80.00	-36.00	
4703.45	H	-61.14	-30.00	
7052.08	H	-50.20	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.91	Vertical	-70.36	-36.00	Pass
702.63	V	-71.65	-36.00	
4700.28	V	-64.67	-30.00	
7052.47	V	-51.16	-30.00	

LTE Band 40(5MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
56.22	Horizontal	-77.69	-36.00	Pass
730.87	H	-74.14	-36.00	
4705.82	H	-64.04	-30.00	
7055.68	H	-60.70	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
53.86	Vertical	-76.04	-36.00	Pass
951.23	V	-78.63	-36.00	
4708.08	V	-68.30	-30.00	
7054.09	V	-51.91	-30.00	





LTE Band 40(20MHz, RB allocation=100): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.40	Horizontal	-70.15	-36.00	Pass
943.31	H	-72.24	-36.00	
4705.08	H	-68.76	-30.00	
7051.19	H	-57.83	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
54.36	Vertical	-78.15	-36.00	Pass
857.49	V	-78.69	-36.00	
4704.79	V	-60.78	-30.00	
7054.23	V	-57.56	-30.00	

LTE Band 40(20MHz, RB allocation=1): Middle Channel, Normal condition				
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
58.14	Horizontal	-70.72	-36.00	Pass
941.39	H	-70.51	-36.00	
4704.77	H	-63.33	-30.00	
7058.00	H	-55.58	-30.00	
Frequency (MHz)	Radiated Spurious Emission		Limit (dBm)	Test Result
	Polarization	Level(dBm)		
50.14	Vertical	-77.52	-36.00	Pass
800.71	V	-70.37	-36.00	
4704.73	V	-63.66	-30.00	
7056.11	V	-56.88	-30.00	

-----THE END OF REPORT-----

