

FCC EMC Test Report



Subject to
Supplier's Declaration of Conformity
Procedure

Product : Smartphone
Trade Mark : CUBOT
Model Number : KINGKONG POWER

Prepared for

Shenzhen Huafurui Technology Co., Ltd.
Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden),
Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District,
Shenzhen, P.R. China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District,
Shenzhen 518126 P.R.China.

Tel.: 400-800-6106, 0755-2320 0050 / 2320 0090 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's Name: Shenzhen Huafurui Technology Co., Ltd.
Unit 1401 &1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of
Address.....: Chongwen Garden), Crossing of the Liuxian Street and Tangling
Road, Taoyuan Street, Nanshan District, Shenzhen, P.R. China

Manufacturer's Name.....: Shenzhen Huafurui Technology Co., Ltd.
Unit 1401 &1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of
Address.....: Chongwen Garden), Crossing of the Liuxian Street and Tangling
Road, Taoyuan Street, Nanshan District, Shenzhen, P.R. China

Product description

Product Name: Smartphone
Model Number: KINGKONG POWER

Standards: 47 CFR FCC part 15 subpart B, 10-1-2022
ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Test Sample Number: S230228033010

Date of Test:

Date (s) of performance of tests: 01 Mar. 2023 ~ 12 Apr. 2023

Date of Issue: 12 Apr. 2023

Test Result.....: **Pass**

Testing Engineer :

Korka Lin

(Korka Lin)

Technical Manager :

Sky Zhang

(Sky Zhang)

Authorized Signatory :

Alex

(Alex)

Table of Contents

Page

1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 DESCRIPTION OF TEST SETUP	9
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	10
2.5 MEASUREMENT INSTRUMENTS LIST	11
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION	13
3.1.2 TEST PROCEDURE	14
3.1.3 TEST SETUP	14
3.1.4 EUT OPERATING CONDITIONS	14
3.1.5 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
3.2.2 LIMITS OF RADIATED EMISSION MEASUREMENT	17
3.2.3 TEST PROCEDURE	17
3.2.4 TEST SETUP	18
3.2.5 EUT OPERATING CONDITIONS	18
3.2.6 TEST RESULTS(30-1000MHz)	19
3.2.7 TEST RESULTS(Above 1000MHz)	21
4 . EUT TEST PHOTO	23
ATTACHMENT PHOTOGRAPHS OF EUT	25

1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
47 CFR FCC part 15 subpart B, 10-1-2022 ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd.

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

CNAS-Lab. : The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)
The Certificate Registration Number is L5516

IC-Registration : The Certificate Registration Number is CN0074

FCC- Accredited : Test Firm Registration Number: 463705
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Measurement Frequency Range	K	U(dB)
Conducted Emission	0.009kHz ~ 0.15MHz	2	2.66
Conducted Emission	0.15MHz ~ 30MHz	2	2.80
Telecom Conducted Emission(Cat 3)	0.15MHz ~ 30MHz	2	3.08
Telecom Conducted Emission(Cat 5)	0.15MHz ~ 30MHz	2	3.60
Telecom Conducted Emission(Cat 6)	0.15MHz ~ 30MHz	2	4.14
Radiated Emission	30MHz ~ 1000MHz	2	2.64
Radiated Emission	1000MHz ~ 18000MHz	2	5.10
Power Clamp	30MHz ~ 300MHz	2	2.20

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smartphone	
Model Number	KINGKONG POWER	
Additional Model Number(s)	N/A	
Model Difference	N/A	
Product Description	The EUT is a Smartphone.	
	Operating frequency:	5.8 GHz by WiFi (Declaration by factory)
	Connecting I/O port:	N/A
	Based on the application, features, or specification exhibited in User's Manual. More details of EUT technical specification, please refer to the User's Manual.	
Power Source	AC Voltage	
Power Rating	Adapter Model: HJ-PD33W-US Adapter Rating: Input: AC 100-240V, 50/60Hz, 0.8A Output: DC 5.0V, 3.0A, 15.0W OR DC 9.0V, 3.0A, 27.0W OR DC 12.0V, 2.75A, 33.0W Max. Battery Rating: DC 3.87V, 10600mAh, 41.022Wh	

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

All test modes in the table below are tested, the worst case is listed on this report.


Pretest Mode	Description
Mode 1	Charging + Lighting + TF Playing
Mode 2	Charging + Lighting + REC-Rear(Fill-in Lighting)
Mode 3	Charging + Lighting + REC-Front
Mode 4	Data Transmitter

For Conducted Test	
Final Test Mode	Description
Mode 1	Charging + Lighting + TF Playing
Mode 2	Charging + Lighting + REC-Rear(Fill-in Lighting)
Mode 3	Charging + Lighting + REC-Front
Mode 4	Data Transmitter

For Radiated Test	
Final Test Mode	Description
Mode 1	Charging + Lighting + TF Playing
Mode 2	Charging + Lighting + REC-Rear(Fill-in Lighting)
Mode 3	Charging + Lighting + REC-Front
Mode 4	Data Transmitter

2.3 DESCRIPTION OF TEST SETUP

Mode CE: Charging + Lighting + REC-Rear(Fill-in Lighting)



2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Smartphone	CUBOT	KINGKONG POWER	N/A	EUT
E-2	Adapter	CUBOT	HJ-PD33W-US	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C-1	YES	NO	100cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

2.5 MEASUREMENT INSTRUMENTS LIST

2.5.1 CONDUCTED TEST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Single Phase LISN	R&S	ENV216	101490	Jun. 28, 2022	Jun. 27, 2023	1 year
2	Single Phase LISN	R&S	ENV216	101313	Apr. 06, 2022	Apr. 05, 2023	1 year
3	Three-Phase LISN	SCHWARZBECK	NNLK 8129	8129245	Apr. 06, 2022	Apr. 05, 2023	1 year
4	Low Frequency Cable	N/A	C-01	N/A	May 11, 2020	May 10, 2023	3 years
5	50Ω Coaxial Switch	Anritsu	MP59B	6200983704	May 11, 2020	May 10, 2023	3 years
6	EMI Test Receiver	R&S	ESCI	101160	Apr. 06, 2022	Apr. 05, 2023	1 year

2.5.2 RADIATED TEST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	3m Anechoic Chamber	N/A	9*6*6	N/A	May 14, 2021	May 13, 2024	3 years
2	3m Anechoic Chamber	N/A	9*6*6	N/A	Jul. 28, 2022	Jul. 27, 2025	3 years
3	EMI Test Receiver	R&S	ESPI7	101318	Apr. 06, 2022 Mar. 27, 2023	Apr. 05, 2023 Mar. 26, 2024	1 year
4	Bilog Antenna	TESEQ	CBL6111D	31216	Mar. 30, 2022 Mar. 16, 2023	Mar. 29, 2023 Mar. 15, 2024	1 year
5	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	May 11, 2020	May 10, 2023	3 years
6	Cable	Talent Microwave	A81-NWMSM AM-12M	21120897	Dec. 16, 2021	Dec. 15, 2024	3 years
7	Cable	Talent Microwave	A81-NMNM-1 0M	22084896	Sep. 09, 2022	Sep. 08, 2025	3 years
8	Cable	Talent Microwave	A81-NMNM-2 M	22084895	Sep. 09, 2022	Sep. 08, 2025	3 years
9	Log-Periodic Antenna	SCHWARZB ECK	VULB 9162	584	Jan. 11, 2023	Jan. 10, 2024	1 year
10	Log-Periodic Antenna	SCHWARZB ECK	VULB 9162	586	Jan. 11, 2023	Jan. 10, 2024	1 year
11	Attenuator	Eastsheep	5W-N-JK-6G-6DB	N/A	Aug. 14, 2022	Aug. 13, 2023	1 year
12	Broadband Horn Antenna	EM	EM-AH-10180	2011071402	Mar. 31, 2022	Mar. 30, 2025	3 years
13	Broadband Horn Antenna	SCHWARZB ECK	BBHA 9120 D	2816	Jan. 12, 2023	Jan. 11, 2024	1 year
14	Broadband Horn Antenna	SCHWARZB ECK	BBHA 9120 D	2817	Jan. 12, 2023	Jan. 11, 2024	1 year
15	Spectrum Analyzer	Agilent	E4407B	MY45108040	Apr. 01, 2022	Mar. 31, 2023	1 year
16	Spectrum Analyzer	Agilent	E4440A	MY41000130	Mar. 27, 2023	Mar. 26, 2024	1 year
17	Pre-Amplifier	EMC	EMC051835S E	980246	Jun. 17, 2022	Jun. 16, 2023	1 year
18	Cable	Keysight	A40-2.92M2.9 2M-2M	1808041	Nov. 01, 2022	Oct. 31, 2023	3 years
19	Broadband Horn Antenna	SCHWARZB ECK	BBHA 9170	803	Nov. 07, 2022	Nov. 06, 2023	1 year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150kHz-30MHz)

FREQUENCY (MHz)	<input type="checkbox"/> Class A (dB μ V)		<input checked="" type="checkbox"/> Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 - 5.0	73.00	60.00	56.00	46.00
5.0 - 30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.


2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.1.5 TEST RESULTS

EUT:	Smartphone	Model Name:	KINGKONG POWER
Temperature:	21.8°C	Relative Humidity:	49%
Pressure:	1010hPa	Test Date:	2023-03-06
Test Mode:	Data Transmission	Phase:	L
Test Voltage:	DC 5V powered by PC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	51.19	9.60	60.79	65.99	-5.20	QP	
2		0.1500	29.96	9.60	39.56	55.99	-16.43	AVG	
3		0.1731	45.08	9.61	54.69	64.81	-10.12	QP	
4		0.1731	24.55	9.61	34.16	54.81	-20.65	AVG	
5		0.7900	31.03	9.68	40.71	56.00	-15.29	QP	
6		0.7900	20.59	9.68	30.27	46.00	-15.73	AVG	
7		1.7340	33.94	9.67	43.61	56.00	-12.39	QP	
8		1.7340	22.85	9.67	32.52	46.00	-13.48	AVG	
9		3.5700	26.42	9.74	36.16	56.00	-19.84	QP	
10		3.5700	16.09	9.74	25.83	46.00	-20.17	AVG	
11		14.5020	28.40	10.07	38.47	60.00	-21.53	QP	
12		14.5020	15.98	10.07	26.05	50.00	-23.95	AVG	


Remark:

Correct Factor = Insertion Loss + Cable Loss

Measurement Level = Reading Level + Correct Factor

Over Level = Measurement Level - Limit

EUT:	Smartphone	Model Name:	KINGKONG POWER
Temperature:	21.8°C	Relative Humidity:	49%
Pressure:	1010hPa	Test Date:	2023-03-06
Test Mode:	Data Transmission	Phase:	N
Test Voltage:	DC 5V powered by PC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	51.77	9.65	61.42	65.99	-4.57	QP	
2		0.1500	32.11	9.65	41.76	55.99	-14.23	AVG	
3		0.1980	43.14	9.62	52.76	63.69	-10.93	QP	
4		0.1980	26.86	9.62	36.48	53.69	-17.21	AVG	
5		0.7140	32.83	9.67	42.50	56.00	-13.50	QP	
6		0.7140	19.62	9.67	29.29	46.00	-16.71	AVG	
7		1.5780	35.09	9.67	44.76	56.00	-11.24	QP	
8		1.5780	24.35	9.67	34.02	46.00	-11.98	AVG	
9		3.8100	27.76	9.71	37.47	56.00	-18.53	QP	
10		3.8100	15.93	9.71	25.64	46.00	-20.36	AVG	
11		15.3180	28.90	10.06	38.96	60.00	-21.04	QP	
12		15.3180	17.18	10.06	27.24	50.00	-22.76	AVG	

Remark:

Correct Factor = Insertion Loss + Cable Loss

Measurement Level = Reading Level + Correct Factor

Over Level = Measurement Level - Limit

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT (30 MHz to 1000 MHz)

FREQUENCY (MHz)	<input type="checkbox"/> Class A (at 3m)	<input checked="" type="checkbox"/> Class B (at 3m)
	dB(μV/m)	
30 ~ 88	49.5	40.0
88 ~ 216	53.9	43.5
216 ~ 960	56.9	46.0
960 ~ 1000	60.0	54.0

3.2.2 LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

FREQUENCY (GHz)	<input type="checkbox"/> Class A (at 3m)		<input checked="" type="checkbox"/> Class B (at 3m)	
	dB(μV/m)			
	Average	Peak	Average	Peak
Above 1 GHz	60	80	54	74

Notes:


- (1) The limit for radiated test was performed according to as following: FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBμV/m)=20log Emission level (μV/m).

3.2.3 TEST PROCEDURE


- a. The measuring distance of at 3m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP(AV) Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.2.4 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz




3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS(30-1000MHz)

EUT:	Smartphone	Model Name:	KINGKONG POWER
Temperature:	25.4℃	Relative Humidity:	52%
Pressure:	1010hPa	Test Date:	2023-04-11
Test Mode:	Charging + Lighting + REC-Rear(Fill-in Lighting)	Polarization:	Horizontal
Test Power:	AC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		30.1052	6.09	26.41	32.50	40.00	-7.50	QP		
2		129.9225	6.14	18.87	25.01	43.50	-18.49	QP		
3		185.1379	12.98	16.65	29.63	43.50	-13.87	QP		
4		437.1197	7.24	23.94	31.18	46.00	-14.82	QP		
5		719.1992	8.37	28.24	36.61	46.00	-9.39	QP		
6	*	906.4823	10.51	30.86	41.37	46.00	-4.63	QP		

Remark:


Correct Factor = Antenna Factor + Cable Loss

Measurement Level = Reading Level + Correct Factor

Over Level = Measurement Level - Limit

EUT:	Smartphone	Model Name:	KINGKONG POWER
Temperature:	25.4℃	Relative Humidity:	52%
Pressure:	1010hPa	Test Date:	2023-04-11
Test Mode:	Charging + Lighting + REC-Rear(Fill-in Lighting)	Polarization:	Vertical
Test Power:	AC 120V/60Hz		

72.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	32.6340	10.29	25.00	35.29	40.00	-4.71	QP		
2		42.1542	13.19	19.78	32.97	40.00	-7.03	QP		
3		86.5029	10.74	16.28	27.02	40.00	-12.98	QP		
4		145.8611	11.98	18.60	30.58	43.50	-12.92	QP		
5		182.5592	18.84	16.80	35.64	43.50	-7.86	QP		
6		890.7278	8.60	30.69	39.29	46.00	-6.71	QP		

Remark:


Correct Factor = Antenna Factor + Cable Loss

Measurement Level = Reading Level + Correct Factor

Over Level = Measurement Level - Limit

3.2.7 TEST RESULTS(Above 1000MHz)

EUT:	Smartphone	Model Name:	KINGKONG POWER
Temperature:	25.5°C	Relative Humidity:	55%
Pressure:	1010hPa	Test Date:	2023-03-04
Test Mode:	Charging + Lighting + TF Playing	Polarization:	Horizontal
Test Power:	AC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		4825.000	35.54	19.83	55.37	74.00	-18.63	peak		
2		4825.000	22.51	19.83	42.34	54.00	-11.66	AVG		
3		7842.500	35.59	23.72	59.31	74.00	-14.69	peak		
4		7842.500	19.06	23.72	42.78	54.00	-11.22	AVG		
5		14132.50	34.03	28.45	62.48	74.00	-11.52	peak		
6	*	14132.50	14.69	28.45	43.14	54.00	-10.86	AVG		


Remark:

Correct Factor = Antenna Factor + Cable Loss – Pre-Amplifier gain

Measurement Level = Reading Level + Correct Factor

Over Level = Measurement Level - Limit

EUT:	Smartphone	Model Name:	KINGKONG POWER
Temperature:	25.5°C	Relative Humidity:	55%
Pressure:	1010hPa	Test Date:	2023-03-04
Test Mode:	Charging + Lighting + TF Playing	Polarization:	Vertical
Test Power:	AC 120V/60Hz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4782.500	37.10	19.50	56.60	74.00	-17.40	peak		
2		4782.500	21.85	19.50	41.35	54.00	-12.65	AVG		
3		9117.500	35.88	23.76	59.64	74.00	-14.36	peak		
4		9117.500	18.98	23.76	42.74	54.00	-11.26	AVG		
5		13367.50	33.33	29.19	62.52	74.00	-11.48	peak		
6	*	13367.50	14.22	29.19	43.41	54.00	-10.59	AVG		

Remark:



Correct Factor = Antenna Factor + Cable Loss – Pre-Amplifier gain

Measurement Level = Reading Level + Correct Factor

Over Level = Measurement Level - Limit

4. EUT TEST PHOTO

Radiated Measurement Photo



Conducted Measurement Photo



ATTACHMENT PHOTOGRAPHS OF EUT

Photo 1



Photo 2



Photo 3




Photo 4



Photo 5




Photo 6



Photo 7



Photo 8



Photo 9



Photo 10



Photo 11



Photo 12



Photo 13




Photo 14




Photo 15




Photo 16




Photo 17



Photo 18



Photo 19



Photo 20



Photo 21




Photo 22




Photo 23




Photo 24




Photo 25



----- End of Report -----